

Syer Line Industrial

Township of Cavan Monaghan
County of Peterborough

Traffic Impact Study Update for SLIP DEVCO INC.

Type of Document:
Final Report

Project Number:
JDE – 21179

Date Submitted:
March 21st, 2022
Revised: October 30th, 2023



John Northcote, P.Eng.
Professional License #: 100124071



ENGINEERING

JD Northcote Engineering Inc.
86 Cumberland Street
Barrie, ON
705.725.4035
www.JDEngineering.ca

Legal Notification

This report was prepared by **JD Northcote Engineering Inc.** for the account of **SLIP DEVCO INC.**

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. **JD Northcote Engineering Inc.** accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this project.

Executive Summary

This traffic impact study update was prepared in support of the proposed industrial development [Subject Site], located on the north side of Syer Line midblock between County Road 10 and Hutchinson Drive in the Township of Cavan Monaghan [Township], County of Peterborough [County]. This report assesses the impact of traffic related to the proposed development on the adjacent roadway and provides recommendations to accommodate this traffic in a safe and efficient manner.

The Subject Site includes one full-movement access roadway onto Syer Line [Street A].

The scope of this analysis includes a review of the following intersections:

- Highway 115 SB Ramp & Syer Line / County Road 10;
- Highway 115 NB Ramp & Syer Line / County Road 10; and
- Syer Line / Street A.

Conclusions

1. The proposed development is expected to generate a total of 123 AM and 112 PM peak hour trips.
2. Detailed turning movement traffic and pedestrian counts were completed at the intersections of Highway 115 SB Ramp & Syer Line / County Road 10 and Highway 115 NB Ramp & Syer Line / County Road 10, on Wednesday, March 1st, 2023.
3. An intersection operation analysis was completed at the study area intersections, using the existing (2023) and background (2028, 2033 and 2038) traffic volumes without the proposed development traffic. This enabled a review of existing and future traffic deficiencies that would be present without the influence of the proposed development. The following improvements are recommended:

Background (2028) Traffic Volumes

- Highway 115 SB Ramp & Syer Line / County Road 10
 - Installation of traffic signals.
- Highway 115 NB Ramp & Syer Line / County Road 10
 - Installation of traffic signals.

Background (2033) Traffic Volumes

- Highway 115 SB Ramp & Syer Line / County Road 10
 - Widen the SB Off-Ramp for the construction of a westbound left turn lane with 150 metre storage length, 40 parallel length and 100 metre taper length and
 - Adjust signal to accommodate a protected + permissive westbound left turn phase.
- Highway 115 NB Ramp & Syer Line / County Road 10
 - Widen County Road 10, north of the Highway 115 NB Ramp to provide two southbound lanes. The southbound configuration at the intersection should include a through + left lane and a through + right lane.
 - Widen SB Off-Ramp for the construction of an eastbound left turn lane with a 60 metre storage length, 40 parallel length and 100 metre taper length.
 - Extend the northbound left turn lane to provide a 230 metre storage length.

Long-Range Planning (Post 2033)

- Highway 115 NB Ramp & Syer Line / County Road 10
 - Twin the northbound left turn lane on County Road 10
 - Construct a second northbound on-ramp lane.
- 4. An estimate of the amount of traffic that would be generated by the Subject Site was prepared and assigned to the study area streets and intersections.
- 5. An intersection operation analysis was completed under total (2028, 2033 and 2038) traffic volumes with the proposed development operational at the study area intersections. No additional improvements are recommended within the study area.
- 6. It is recommended MTO and County monitor the queuing on County Road 10 and on the Highway 115 ramps as the future Millbrook developments become fully built-out and occupied (anticipated to start in the existing (2023) year), to determine the specific timing for the recommended infrastructure improvements noted for the 2028 and 2033 horizon years.
- 7. Street A will operate efficiently with full-movement access, with one-way stop control for southbound movements. A single ingress and egress lane at Street A will provide the necessary capacity to service the proposed development.
- 8. The available sight distance at Street A is sufficient for the intended use.
- 9. In summary, the proposed development will not cause any operational issues and will not add significant delay or congestion to the local roadway network.

Table of Contents

1	Introduction.....	1
1.1	Background.....	1
1.2	Study Area	1
1.3	Study Scope and Objectives	3
1.4	Horizon Year and Analysis Periods	3
2	Information Gathering.....	3
2.1	Street and Intersection Characteristics	3
2.2	Local Transportation Infrastructure Improvements.....	5
2.3	Transit Access	5
2.4	Other Developments within the Study Area	5
2.4.1	Towerhill Developments Phase 2.....	7
2.4.2	Vargas Development	7
2.4.3	Bromont Development.....	7
2.4.4	Millbrook Fire Hall.....	8
2.4.5	Syer West Development, Syer East Development & CR10 Development.....	9
2.5	Background Traffic Growth	22
2.6	Traffic Counts	22
2.7	Horizon Year Traffic Volumes.....	22
3	Intersection Operation without Proposed Development.....	27
3.1	Introduction	27
3.2	Existing (2023) Intersection Operation	28
3.3	Background (2028) Intersection Operation	29
3.4	Background (2033) Intersection Operation	30
3.5	Background (2038) Intersection Operation	32
4	Proposed Development Traffic Generation and Assignment.....	34
4.1	Traffic Generation	34
4.2	Traffic Assignment.....	34
4.3	Total Horizon Year Traffic Volumes with the Proposed Development	35
5	Intersection Operation with Proposed Development	40
5.1	Total (2028) Intersection Operation.....	40
5.2	Total (2033) Intersection Operation.....	41
5.3	Total (2038) Intersection Operation.....	42

5.4	Site Access	43
5.5	Sight Distance Review.....	43
6	Summary	44

List of Tables

Table 1 – Adjacent Development Traffic Distribution (Residential).....	8
Table 2 – Fire Hall Traffic Distribution	9
Table 3 – Estimated Traffic Generation for Syer West, Syer East & CR10 Development	9
Table 4 – Traffic Count Data	22
Table 5 – Level of Service Criteria for Intersections.....	27
Table 6 – Existing (2023) LOS	28
Table 7 – Background (2028) LOS.....	29
Table 8 – Background (2028) LOS with Improvements	30
Table 9 – Background (2033) LOS.....	31
Table 10 – Background (2033) LOS with Improvements	32
Table 11 – Background (2038) LOS.....	33
Table 12 – Estimated Traffic Generation of Proposed Development.....	34
Table 13 – Proposed Development Traffic Distribution.....	35
Table 14 – Total (2028) LOS	40
Table 15 – Total (2033) LOS	41
Table 16 – Total (2038) LOS	42

List of Figures

Figure 1 – Proposed Site Location and Study Area	2
Figure 2 – Existing (2023) Intersection Spacing and Lane Configuration within Study Area.....	4
Figure 3 – Adjacent Development Locations.....	6
Figure 4 – Adjacent Development – Bromont Development Traffic Volumes (2028)	11
Figure 5 – Adjacent Development – Bromont Development Traffic Volumes (2033 / 2038)	12
Figure 6 – Adjacent Development (Bromont TIS) Traffic Volumes (2028).....	13
Figure 7 – Adjacent Development (Bromont TIS ²) Traffic Volumes (2033 / 2038)	14
Figure 8 – Adjacent Development – Millbrook Fire Hall Traffic Volumes (2028)	15
Figure 9 – Adjacent Development – Syer West Development Traffic Volumes (2033)	16
Figure 10 – Adjacent Development – Syer East Development Traffic Volumes (2038)	17
Figure 11 – Adjacent Development – CR10 Development Traffic Volumes (2038).....	18
Figure 12 – Total Net Adjacent Development Traffic Volumes (2028).....	19
Figure 13 – Total Net Adjacent Development Traffic Volumes (2033).....	20
Figure 14 – Total Net Adjacent Development Traffic Volumes (2038).....	21
Figure 15 – Existing (2023) Traffic Volumes	23
Figure 16 – Background (2028) Traffic Volumes.....	24
Figure 17 – Background (2033) Traffic Volumes.....	25
Figure 18 – Background (2038) Traffic Volumes.....	26
Figure 19 – Proposed Development Traffic Assignment.....	36
Figure 20 – Total (2028) Traffic Volumes	37
Figure 21 – Total (2033) Traffic Volumes	38
Figure 22 – Total (2038) Traffic Volumes	39

List of Appendices

APPENDIX A – Concept Plan
APPENDIX B – Adjacent Development Reports
APPENDIX C – Traffic Count Data
APPENDIX D – Synchro Analysis Output – Existing Traffic Volumes
APPENDIX E – Synchro Analysis Output – Background Traffic Volumes
APPENDIX F – Synchro Analysis Output – Total Traffic Volumes
APPENDIX G – MTO Left Turn Analysis
APPENDIX H – OTM Signal Justification Sheets
APPENDIX I – Transportation Tomorrow Survey – Excerpt

1 Introduction

1.1 Background

SLIP DEVCO INC. [The Client] is proposing to develop a property [Subject Site], located on the north side of Syer Line, midblock between County Road 10 and Hutchinson Drive, in the Township of Cavan Monaghan [Township], County of Peterborough [County].

The proposed industrial subdivision will consist of 5 Blocks and is anticipated to include a total of 225 employees.

The proposed development includes one full-movement access roadway onto Syer Line [Street A]. One Block within the industrial subdivision (Block 5) will not have access via Street A. This Block will have frontage on Syer Line; however, the plan for accessing this Block has not been finalized at this time and will be subject to a future traffic review.

JD Northcote Engineering Inc. [JD Engineering] completed a traffic impact study [TIS] for the Subject Site (dated March 2022) [Syer TIS]. This report is an update to the Syer TIS which was based on a preliminary concept plan for the Subject Site.

The Client has retained JD Engineering to prepare this Traffic Impact Study Update in support of the development application for the proposed industrial development.

1.2 Study Area

Figure 1 shows the location of the Subject Site and study area intersections in relation to the surrounding area. The Concept Plan is provided in **Appendix A**.


It is noted, the Concept Plan illustrates lots on the southeast and southwest corners of the proposed development that are also owned by the Client. These lots are not a part of this application but were reviewed as part of a consent application submitted prior to the completion of this report.

The subject site is bound by Syer Line to the south, Highway 115 to the north, existing residential and RV dealership to the west and agricultural lands to the east.

The following intersections, which were included in the Syer TIS, are included in this traffic impact study update:

- Highway 115 SB Ramp & Syer Line / County Road 10;
- Highway 115 NB Ramp & Syer Line / County Road 10; and
- Syer Line / Street A.

Figure 1 – Proposed Site Location and Study Area



1.3 Study Scope and Objectives

The purpose of this study is to identify the potential impacts to traffic flow at the site access and on the surrounding roadway network. The study analysis includes the following tasks:

- Determine existing traffic volumes and circulation patterns;
- Estimate future traffic volumes if the proposed development was not constructed, including the impact of additional proposed developments in the area;
- Complete level-of-service [LOS] analysis of horizon year (without the proposed development) traffic conditions and identify operational deficiencies;
- Estimate the amount of traffic that would be generated by the proposed development and assign to the roadway network;
- Complete LOS analysis of horizon year (with the proposed development) traffic conditions and identify additional operational deficiencies;
- Complete a review of traffic operations at the proposed Street A access and study area intersections;
- Review the proposed configuration at the proposed Street A access and study area intersections;
- Review the available sight distance at the proposed Street A access; and
- Document findings and recommendations in a final report.

1.4 Horizon Year and Analysis Periods

Traffic scenarios for the existing year (2023) and horizon years (2028, 2033 & 2038) were selected for analysis of traffic operations in the study area. The weekday morning [AM] and weekday afternoon [PM] peak hours have been selected as the analysis periods for this study.

2 Information Gathering

2.1 Street and Intersection Characteristics


Highway 115 is a four-lane Class 1B freeway provincial highway with a rural cross-section. Highway 115 has a posted speed limit of 100km/h and is under jurisdiction of the Ontario Ministry of Transportation [MTO]. The Highway 115 on and off ramps (for both northbound and southbound directions) have posted advisory speed of 40 km/h and 70 km/h respectively.

County Road 10 is a two-lane arterial road with a rural cross-section and no sidewalks. County Road 10 has a posted speed limit of 80 km/h and is under jurisdiction of the County.

Syer Line is a two-lane local road with a rural cross-section and no sidewalks. Syer Line has a discontinuation east and west of County Road 10 (approximately 506 metres). Syer Line west of County Road 10 has a posted speed limit of 50 km/h and east of County Road 10 has an unposted (assumed) speed limit of 50km/h. Syer Line is under jurisdiction of the Township.

The existing intersection spacing and lane configuration within the study area is illustrated in **Figure 2**.

Figure 2 – Existing (2023) Intersection Spacing and Lane Configuration within Study Area



2.2 Local Transportation Infrastructure Improvements

Based on a review of the MTO's Highway's Programs interactive map, the County's Capital Works Project interactive map and the Township's Capital Budget (2023), there are no significant local road improvements scheduled in the study area that will impact traffic volumes or traffic patterns within the horizon years included in this analysis.

2.3 Transit Access

GO Transit provides the Route #88 (Peterborough / Oshawa) bus route which provides connections between the City of Oshawa and the City of Peterborough along Highway 115.

The Peterborough / Oshawa bus route operates on weekdays between 04:45 – 21:45 with daytime service every two hour and on weekends between 05:40 – 21:45 with service every two hours.

The closest bus stop for the Peterborough / Oshawa bus route is located in the southeast corner of the Highway 115 SB Ramp & Syer Line / County Road 10 intersection (1.7 km from the Subject Site).

2.4 Other Developments within the Study Area


Based on discussions with Township staff, the following developments are planned in the study area:

- Towerhill Development Phase 2;
- Vargas Development;
- Bromont Development;
- Millbrook Fire Hall;
- Syer West Development;
- Syer East Development; and
- CR10 Development.

The above noted developments are in various stages of development and are further described in the sections below. To be conservative in our analysis, we have assumed all of the developments will be built-out by the 2033 horizon year.

Figure 3 illustrates the location of these development relative to the study area.

Figure 3 – Adjacent Development Locations



2.4.1 Towerhill Developments Phase 2

Towerhill Developments Limited is proposing to develop a 52.1 hectare parcel of land, located northwest of the Fallis Line / County Road 10 intersection, south of the study area [Towerhill Developments Phase 2]. Towerhill Developments Phase 2 will consist of 328 single detached units, 245 townhouse units, 192 high-density residential units and an institutional block. JD Engineering completed a traffic impact study for Towerhill Developments Phase 2 (dated January 2021) [Towerhill TIS]. Towerhill Developments Phase 2 is approved and currently under construction. It is anticipated Towerhill Developments Phase 2 will be fully built-out by 2028.

For the future (2028, 2033 and 2038) scenarios, the traffic assignment for the Towerhill Developments Phase 2 is based on the traffic projections from the Bromont TIS, which is further discussed in Section 2.4.3. The traffic projections in the Bromont TIS applied the assumptions from the Towerhill TIS to determine the future traffic volumes on County Road 10 and added further context to the traffic projections in the Towerhill TIS.

2.4.2 Vargas Development

Vargas Properties Inc. is proposing a mixed-use development located on the southeast corner of the Fallis Line / County Road 10 intersection, south of the study area [Vargas Development]. Vargas Development will consist of 116 single detached units, 58 townhouse units, 70 medium density units and a commercial block. Asurza Engineers Limited completed a traffic impact study for the Vargas Development (dated April 2021) [Vargas TIS]. Vargas Development is pending site plan approval. It is anticipated the Vargas Development will be 50% occupied by 2025 and fully built-out and occupied by 2030.

The traffic assignment for the Vargas Development was determined in the Vargas TIS, however, will be based on the Bromont TIS, which is further discussed in Section 2.4.3. The Bromont TIS used the Vargas TIS to estimate the traffic assignment for the Vargas Development.

2.4.3 Bromont Development

Bromont Group is proposing a residential development located southwest of the Fallis Line / County Road 10 intersection, south of the study area [Bromont Development]. The Bromont Development will consist of 371 single detached units, 148 townhouse units and 150 mid-rise residential units. Asurza Engineers Limited completed a traffic impact study for the Bromont Development (dated January 2022) [Bromont TIS]. Bromont Development is pending site plan approval. It is anticipated the Bromont Development will be 50% occupied by 2025 and fully built-out and occupied by 2030.

The traffic assignment for the Bromont Development was obtained from the Bromont TIS (excerpts provided in **Appendix B**). **Figure 4** and **5** illustrates the traffic assignment for the Bromont Development for the 2028 and 2033 / 2038 horizon year, respectively.

The study area of this report extends beyond the study area included in the Bromont Development. The distribution of the Bromont Development traffic within the study area of this report has been estimated based on the 2016 Transportation Tomorrow Survey [TTS] data. The TTS data for the Township was retrieved using the TTS Internet Data Retrieval System [IDRS] (output attached as **Appendix I**). TTS data provides historical origin and destination work trip percentages for specific areas within the Town and southern Ontario.

Traffic distribution for the trips generated by the adjacent developments during the AM and PM peak hour is expected to generally follow commuter travel patterns. Our analysis is based on egress traffic during the AM peak hour. Logically, the distribution of ingress traffic will follow the inverse of the exiting

traffic distribution. For each of the individual areas identified in the TTS data, we have selected the probable route of travel, assuming that people will select their route primarily based on travel time.

Table 1 illustrates the traffic distribution for the Bromont, Towerhill Phase 2 and Vargas Developments, using the methodology outlined above.

Table 1 – Adjacent Development Traffic Distribution (Residential)

Travel Direction (to/from)	Percent of Total Traffic Generation
West via Highway 115*	17%
East via Highway 115	48%
South via County Road 10**	16%
North via County Road 10	2%
Total	100%

*Although traffic will be travelling west onto Highway 115, a large percentage will access the highway from beyond the study area and only a small portion will access Highway 115 via the interchange in the study area.

** Outside of the study area.

The Bromont TIS included traffic assignment for the Towerhill Developments Phase 2 and the Vargas Development. For the purposes of this study, the traffic assignment for the Towerhill Developments Phase 2, Vargas Development and other minor development in the Millbrook community have been estimated based on the Bromont TIS traffic projections (excerpts provided in **Appendix B**).

Figure 6 and **7** illustrates the traffic assignment for the adjacent developments noted in the Bromont TIS¹ for the 2028 and 2033 / 2038 horizon year respectively, in the AM and PM peak hours. The traffic distribution in the study area has been assumed based on Table 9 and the assumptions noted above.

2.4.4 Millbrook Fire Hall

The Township is proposing to construct a fire hall on a site municipally known as 988 County Road 10, located north of the Municipal Office [Millbrook Fire Hall]. The Millbrook Fire Hall will be occupied by two user groups: the Township's Fire and Emergency Service and the County's Paramedic Service. JD Engineering completed a traffic impact study for the Millbrook Fire Hall (dated October 2021) [Millbrook Fire Hall TIS]. The Millbrook Fire Hall is site plan approved and is assumed to be built-out by 2028.

The traffic assignment for the Millbrook Fire Hall was obtained from the Millbrook Fire Hall TIS (excerpts provided in **Appendix B**). **Figure 8** illustrates the traffic assignment for the Millbrook Fire Hall, for the AM and PM peak hour. The traffic distribution in the study area is based on the existing traffic in the study area, as illustrated in **Table 2**.

¹ The traffic assignment was determined by taking the difference between the background (2025 & 2030) traffic volumes and the existing (2021) traffic volumes, with a background traffic growth rate applied, to determine the equivalent 2025 and 2030 traffic volumes. To determine the 2028 traffic volumes, we have assumed linear growth based on the background (2025 & 2030) traffic volumes.

Table 2 – Fire Hall Traffic Distribution

Scenario	Direction	Ingress / Egress Traffic Direction			
		West	East	South*	North
AM	In	6%	16%	51%	27%
	Out	16%	23%	30%	31%
PM	In	18%	24%	30%	28%
	Out	9%	13%	45%	33%

*Outside of the study area.

2.4.5 Syer West Development, Syer East Development & CR10 Development

There are a number of rural properties zoned for employment in the study area, as illustrated in Figure 3, which have been reviewed as part of this study.

For the purpose of our analysis, it is assumed development will occur within the parcel located at the northwest corner of the Highway 115 SB Ramp & Syer Line / County Road 10 intersection [Syer West Development]. We have assumed the Syer West Development will have 20 employees and include access driveways onto County Road 10 north of the Highway 115 SB Ramp & Syer Line / County Road 10 intersection. We have assumed the Syer West Development will be built-out by 2033.

It is assumed development will occur within the parcel located east of the Highway 115 / County Road 10 interchange, west of the proposed development [Syer East Development]. We have assumed the Syer East Development will have 20 employees and include an access driveway onto Syer Line, west of Street A. We have assumed the Syer East Development will be built-out by 2038.

It is assumed development will occur within the parcel located at the northeast corner of the Highway 115 SB Ramp & Syer Line / County Road 10 intersection [CR10 Development]. We have assumed the CR10 Development will have 40 employees and include access driveways onto County Road 10 north of the Highway 115 SB Ramp & Syer Line / County Road 10 intersection. We have assumed the CR10 Development will be built-out by 2038.

For the above-noted properties, a development density of 5 jobs per hectare was used, which is consistent with the development density proposed for the Subject Site.

The traffic generation for the Syer West Development, Syer East Development & CR10 Development was estimated based Institute of Transportation Engineers [ITE] *Trip Generation Manual* (11th Edition), which used the following land use:

- ITE land use 110 (General Light Industrial) – General Urban/Suburban Setting

The traffic generated by the Syer West Development, Syer East Development & CR10 Development is illustrated in **Table 3**.

Table 3 – Estimated Traffic Generation for Syer West, Syer East & CR10 Development

Development	Land Use	Size	AM Peak Hour			PM Peak Hour		
			IN	OUT	TOTAL	IN	OUT	TOTAL
Syer West Development	General Light Industrial ITE Land Use: 110	20 employees	9	2	11	2	8	10
Syer East Development		20 employees	9	2	11	2	8	10
CR10 Development		40 employees	18	4	22	4	16	20

The traffic distribution for the Syer West Development, Syer East Development & CR10 Development is based on the traffic distribution for the proposed development as noted in Table 13 in Section 4.2.

Figure 9, 10 and 11 illustrates the traffic assignment for the Syer West Development, Syer East Development & CR10 Development, in the AM and PM peak hours.

Figures 12, 13 and 14 illustrates total traffic assignment for the 2028, 2033 and 2038 horizon years respectively, for the adjacent developments in the study area during the AM and PM peak hour.

Figure 4 – Adjacent Development – Bromont Development Traffic Volumes (2028)




Figure 5 – Adjacent Development – Bromont Development Traffic Volumes (2033 / 2038)





Figure 6 – Adjacent Development (Bromont TIS²) Traffic Volumes (2028)



² Adjacent development in the Bromont TIS includes the Towerhill Developments Phase 2, the Vargas Development and other minor development in the Millbrook community.

Figure 7 – Adjacent Development (Bromont TIS²) Traffic Volumes (2033 / 2038)




Figure 8 – Adjacent Development – Millbrook Fire Hall Traffic Volumes (2028)




Figure 9 – Adjacent Development – Syer West Development Traffic Volumes (2033)




Figure 10 – Adjacent Development – Syer East Development Traffic Volumes (2038)




Figure 11 – Adjacent Development – CR10 Development Traffic Volumes (2038)




Figure 12 – Total Net Adjacent Development Traffic Volumes (2028)




Figure 13 – Total Net Adjacent Development Traffic Volumes (2033)





Figure 14 – Total Net Adjacent Development Traffic Volumes (2038)



2.5 Background Traffic Growth

The background traffic growth rate on Highway 115 was calculated based on the MTO's Traffic Volumes Program between 2006 – 2016. A background traffic growth rate of 2.3% was applied on Highway 115. Based on correspondence with the County a general background traffic growth rate of 2% was applied on County Road 10. A general background traffic growth rate of 2% was assumed for Syer Line.

2.6 Traffic Counts

Detailed turning movement traffic and pedestrian counts were completed at the study area intersections.

Table 4 summarizes the traffic count data collection information.

Table 4 – Traffic Count Data

Intersection (E-W Street / N-S Street)	Count Date	AM Peak Hour	PM Peak Hour	Source
Highway 115 SB Ramp* & Syer Line / County Road 10	Wednesday, March 1 st , 2023	07:30 – 08:30	16:30 – 17:30	JD Eng.**
Highway 115 NB Ramp* & Syer Line / County Road 10	Wednesday, March 1 st , 2023	07:45 – 08:45	16:30 – 17:30	JD Eng.**

* The traffic count data in Appendix C incorrectly labels the Highway 115 SB / NB Ramp in the diagrams; where the Highway 115 Ramp on the east leg is the Highway 115 SB Ramp and the Highway 115 Ramp on the west leg is the Highway 115 NB Ramp

** The traffic counts were completed by Accu Traffic Inc. on behalf of JD Engineering.

Detailed traffic count data can be found in **Appendix C**. The peak hours of traffic generation for the study area intersections generally aligned with the anticipated peak hour of traffic generation by the proposed development. Although the AM and PM peak periods at all study area intersections did not exactly align, for the purpose of this report, we have assumed that the AM and PM peak hours are concurrent.

Heavy vehicle percentages from the traffic count data have also been included in the Synchro analysis.

The south leg traffic at the Highway 115 SB Ramp & Syer Line / County Road 10 intersection has been adjusted to match the north leg traffic at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection as there are slight discrepancies due to the peak hours not exactly aligning in the traffic count data.

Figure 15 illustrates the existing (2023) AM and PM peak hour traffic volumes within the study area.

2.7 Horizon Year Traffic Volumes

The background (2028, 2033 and 2038) traffic volumes were estimated using the existing (2023) AM and PM peak hour traffic volumes and applying the background traffic growth rate discussed in Section 2.5 and the adjacent development traffic identified in Section 2.4.

The proposed Street A access has been assumed to be located directly across from the existing driveway on Syer Line, which provides access to one single detached unit. The traffic generation for the single detached unit has been based on the ITE Trip Generation Manual. The following ITE land use has been applied to estimate the traffic generated by the single detached unit:

- ITE land use 210 (Single-Family Detached Housing) – General Urban/Suburban Setting

Figures 16, 17 and 18 for the background (2028, 2033 and 2038) respectively, in the AM and PM peak hour traffic volumes for the study area (excluding the proposed development traffic volumes).

Figure 15 – Existing (2023) Traffic Volumes




Figure 16 – Background (2028) Traffic Volumes




Figure 17 – Background (2033) Traffic Volumes





Figure 18 – Background (2038) Traffic Volumes



3 Intersection Operation without Proposed Development

3.1 Introduction

Intersection performance was measured using the traffic analysis software, Synchro 11, a deterministic model that employs Highway Capacity Manual and Intersection Capacity Utilization methodologies for analysing intersection operations. These procedures are accepted by provincial and municipal agencies throughout North America.

Synchro 11 enables the study area to be graphically defined in terms of streets and intersections, along with their geometric and traffic control characteristics. The user is able to evaluate both signalized and unsignalized intersections in relation to each other, thus not only providing level of service for the individual intersections, but also enabling an assessment of the impact the various intersections in a network have on each other in terms of spacing, traffic congestion, delay, and queuing.

Individual turning movements with a volume-to-capacity [V/C] ratio of 0.85 or greater are considered to be critical movements and have been highlighted in the LOS tables.

The intersection operations were also evaluated in terms of the LOS. LOS is a common measure of the quality of performance at an intersection and is defined in terms of vehicular delay. This delay includes deceleration delay, queue move-up time, stopped delay, and acceleration delay. LOS is expressed on a scale of A through F, where LOS A represents very little delay (i.e. less than 10 seconds per vehicle) and LOS F represents very high delay (i.e. greater than 50 seconds per vehicle for a stop sign controlled intersection and greater than 80 seconds per vehicle for a signalized intersection).

The LOS criteria for signalized and stop sign controlled intersections are shown in **Table 5**. A description of traffic performance characteristics is included for each LOS.

Table 5 – Level of Service Criteria for Intersections

LOS	LOS Description	Control Delay (seconds per vehicle)	
		Signalized Intersections	Stop Controlled Intersections
A	Very low delay; most vehicles do not stop (Excellent)	less than 10.0	less than 10.0
B	Higher delay; more vehicles stop (Very Good)	between 10.0 and 20.0	between 10.0 and 15.0
C	Higher level of congestion; number of vehicles stopping is significant, although many still pass through intersection without stopping (Good)	between 20.0 and 35.0	between 15.0 and 25.0
D	Congestion becomes noticeable; vehicles must sometimes wait through more than one red light; many vehicles stop (Satisfactory)	between 35.0 and 55.0	between 25.0 and 35.0
E	Vehicles must often wait through more than one red light; considered by many agencies to be the limit of acceptable delay	between 55.0 and 80.0	between 35.0 and 50.0
F	This level is considered to be unacceptable to most drivers; occurs when arrival flow rates exceed the capacity of the intersection (Unacceptable)	greater than 80.0	greater than 50.0

3.2 Existing (2023) Intersection Operation

The results of the LOS analysis under existing (2023) traffic volumes during the AM and PM peak hour can be found below in **Table 6**. Existing intersection geometry and traffic control have been utilized for this scenario. Detailed output of the Synchro analysis can be found in **Appendix D**.

Table 6 – Existing (2023) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (unsignalized)	-	6.0	A	-	-	-	7.8	A	-	-
EB	0.05	9.9	A	2	-	0.06	10.5	B	2	-
WB	0.22	13.3	B	7	-	0.46	18.4	C	20	-
NB	0.01	1.0	A	1	-	0.01	0.7	A	1	-
SBL	0.04	7.5	A	2	82	0.02	7.7	A	1	82
SBTR	0.05	0.0	A	0	-	0.06	0.0	A	0	-
Highway 115 NB Ramp & Syer Line / County Road 10 (unsignalized)	-	4.2	A	-	-	-	9.3	A	-	-
EB	0.10	17.8	C	3	-	0.62	43.2	E	29	-
WB	0.02	11.7	B	1	-	0.09	18.7	C	3	-
NBL	0.14	8.1	A	4	85	0.18	8.6	A	6	85
NBTR	0.06	0.0	A	0	-	0.10	0.0	A	0	-
SB	0.01	0.4	A	1	-	0.01	0.3	A	1	-

The results of the LOS analysis indicate that all study area intersections are operating within the typical design limits noted in Section 3.1.

There are no issues regarding the anticipated queue for all movements in the study area.

An analysis was completed for left turn movements at the unsignalized intersections in the study area, based on the criteria outlined in Appendix 9A of the Ontario Ministry of Transportation Design Supplement for TAC Geometric Design Guide for Canadian Roads June 2017 [MTO DS] (results are provided in **Appendix G**). Based on the above noted criteria additional auxiliary left-turn lanes are not warranted in the study area.

A review of the need for an auxiliary right turn lane at the unsignalized intersections in the study area was completed as part of our analysis. The results of the Synchro analysis indicate that there is excess capacity for all movements; consequently, auxiliary right turn lanes are not recommended.

Based on the Ontario Traffic Manual Book 12 *Signal Justification*, traffic signals are not warranted at unsignalized intersections in the study area (results are provided in **Appendix H**).

No improvements are recommended within the study area for the existing horizon year.

3.3 Background (2028) Intersection Operation

The results of the LOS analysis under background (2028) traffic volumes during the AM and PM peak hour can be found below in **Table 7**. Existing intersection geometry and traffic control have been utilized for this scenario. Detailed output of the Synchro analysis can be found in **Appendix E**.

Table 7 – Background (2028) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (unsignalized)	-	16.6	B	-	-	-	170.9	F	-	-
EB	0.06	10.4	B	2	-	0.08	11.1	B	2	-
WB	0.75	31.3	D	51	-	1.59	299.1	F	304	-
NB	0.01	0.8	A	1	-	0.02	0.7	A	1	-
SBL	0.05	7.6	A	2	82	0.03	7.9	A	1	82
SBTR	0.06	0.0	A	0	-	0.08	0.0	A	0	-
Highway 115 NB Ramp & Syer Line / County Road 10 (unsignalized)	-	21.2	D	-	-	-	948.9	F	-	-
EB	1.30	449.9	F	37	-	30.34	Error	F	Error	-
WB	0.15	62.2	F	4	-	1.80	884.8	F	33	-
NBL	0.59	13.0	B	33	85	0.74	21.4	C	54	85
NBTR	0.08	0.0	A	0	-	0.12	0.0	A	0	-
SB	0.01	0.2	A	1	-	0.01	0.3	A	0	-

The LOS analysis indicates that the Highway 115 SB Ramp & Syer Line / County Road 10 is operating outside the typical design limits as noted in Section 3.1. Based on the Ontario Traffic Manual Book 12 *Signal Justification*, signals are not warranted at the Highway 115 SB Ramp & Syer Line / County Road 10 intersection (results are provided in **Appendix H**). However, based on the anticipated control delay for the Syer Line / Highway 115 SB Ramp approaches, it is anticipated that this intersection will need to be signalized. As previously noted in Section 3.2, the warrant for signalization is the result of the future developments in the Millbrook community. It is recommended the MTO continue to monitor the traffic at the Highway 115 SB Ramp & Syer Line / County Road 10 intersection closer to the 2028 horizon year as the development in the Millbrook community progresses, to determine the exact timing of the signalization.

The results of the LOS analysis indicates that the eastbound movement at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection is operating outside the typical design limits noted in Section 3.1. Based on the Ontario Traffic Manual Book 12 *Signal Justification*, traffic signals are not warranted at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection (results are provided in **Appendix H**). Based on the anticipated control delay for the Syer Line / Highway 115 NB Ramp approaches, it is recommended the intersection is signalized. It is noted that signalization will be warranted based on the future developments in the Millbrook community³; it is recommended the MTO review the traffic at the intersection closer as the build-out of the Millbrook community progresses, to determine the exact timing of the signalization.

³ The full build-out of the Towerhill Developments Phase 2 is the only adjacent development assumed in the existing (2023) scenario.

To accommodate the above noted signalization, it is recommended the signal heads accommodate a northbound protected + permissive left turn phase at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection.

The results of the LOS analysis under background (2028) traffic volumes with the above noted improvements during the AM and PM peak hour can be found below in **Table 8**. Detailed output of the Synchro analysis can be found in **Appendix E**.

Table 8 – Background (2028) LOS with Improvements

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (signalized)	0.47	22.8	C	-	-	0.80	36.7	D	-	-
EB	0.04	12.1	B	7	-	0.04	7.2	A	6	-
WB	0.59	22.0	C	87	-	0.82	25.1	C	206	-
NB	0.28	25.8	C	42	-	0.76	62.5	E	120	-
SBL	0.18	24.5	C	22	82	0.25	47.3	D	20	82
SBTR	0.17	24.1	C	29	-	0.31	45.9	D	51	-
Highway 115 NB Ramp & Syer Line / County Road 10 (signalized)	0.77	14.1	B	-	-	1.01	57.6	E	-	-
EB	0.47	50.0	D	18	-	0.80	74.3	E	70	-
WB	0.04	43.9	D	7	-	0.08	48.0	D	13	-
NBL	0.77	10.3	B	74	85	1.02	70.4	E	183	85
NBTR	0.10	1.8	A	11	-	0.16	4.8	A	26	-
SB	0.56	18.9	B	134	-	0.99	58.8	E	347	-

The results of the LOS analysis indicate that the Highway 115 NB Ramp & Syer Line / County Road 10 intersection is operating marginally outside the typical design limits as noted in Section 3.1. Since the delay is under LOS F and the V/C ratio marginally exceeds the theoretical capacity of 1.0, no further improvements are recommended. As noted above, it is recommended the MTO monitor the queuing at the intersection closer to the 2028 horizon year as the development in the Millbrook community progresses, to determine if further improvements are recommended.

The anticipated queuing for northbound left turn movements at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection is anticipated to extend past the existing storage length; however, the excess queue will not block any adjacent intersection. As noted above, it is recommended this queuing is monitored as the development in the Millbrook community progresses.

There are no issues regarding the anticipated queue for all other movements in the study area.

No further infrastructure improvements are recommended for the background (2028) scenario within the study area.

3.4 Background (2033) Intersection Operation

The results of the LOS analysis under background (2033) traffic volumes during the AM and PM peak hour can be found below in **Table 9**. The recommended improvements identified in Section 3.3 have been utilized in this scenario. Detailed output of the Synchro analysis can be found in **Appendix E**.

Table 9 – Background (2033) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (signalized)	0.51	24.0	C	-	-	0.88	43.4	D	-	-
EB	0.04	12.2	B	8	-	0.05	7.2	A	7	-
WB	0.65	23.9	C	99	-	0.90	33.5	C	278	-
NB	0.32	26.5	C	47	-	0.83	69.1	E	142	-
SBL	0.21	25.0	C	25	82	0.31	50.3	D	23	82
SBTR	0.19	24.3	C	32	-	0.36	46.9	D	57	-
Highway 115 NB Ramp & Syer Line / County Road 10 (signalized)	0.82	26.1	C	-	-	1.14	92.7	F	-	-
EB	0.40	46.8	D	19	-	0.85	79.1	E	83	-
WB	0.03	42.7	D	7	-	0.08	47.3	D	14	-
NBL	0.83	20.7	C	155	85	1.18	127.7	F	228	85
NBTR	0.12	2.3	A	12	-	0.18	5.4	A	28	-
SB	0.81	37.8	D	165	-	1.10	95.4	F	401	-

The results of the LOS analysis indicate that the Highway 115 SB Ramp & Syer Line / County Road 10 and Highway 115 NB Ramp & Syer Line / County Road 10 intersections are operating outside the typical design limits as noted in Section 3.1. It is noted the southbound traffic is beyond the typical planning capacity for a single lane arterial roadway (850 vph) in the southbound direction in the PM peak hour.

Due to the long-term estimates (10 years) and the increase in traffic in the study area being dependent on the adjacent development in the Milbrook community as noted in Section 2.4, it is recommended the MTO and County monitor the queuing on County Road 10 and on the Highway 115 ramps as the future Millbrook developments become fully built-out and occupied, to determine if infrastructure improvements are warranted. Based on the traffic projections identified in this report, the following improvements should be considered to improve the capacity issues at both intersections:

- Highway 115 SB Ramp & Syer Line / County Road 10
 - Widen the SB Off-Ramp for the construction of a westbound left turn lane with 150 metre storage length, 40 parallel length and 100 metre taper length and
 - Provide a protected + permissive westbound left turn phase.
- Highway 115 NB Ramp & Syer Line / County Road 10
 - Widen the County Road 10, north of the Highway 115 NB Ramp to provide two southbound lanes. The southbound configuration at the intersection should include a through / left lane and a through / right lane.
 - Widen SB Off-Ramp for the construction of an eastbound left turn lane with a 60 metre storage length, 40 parallel length and 100 metre taper length
 - Extend the northbound left turn lane to provide a 230 metre storage length.

The results of the LOS analysis under background (2033) traffic volumes with the above noted improvements during the AM and PM peak hour can be found below in **Table 10**. Detailed output of the Synchro analysis can be found in **Appendix E**.

Table 10 – Background (2033) LOS with Improvements

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (signalized)	0.48	25.0	C	-	-	0.78	29.4	C	-	-
EB	0.04	15.4	B	9	-	0.07	29.1	C	15	-
WBL	0.64	27.7	C	105	190	0.81	20.9	C	149	190
WBTR	0.02	15.6	B	5	-	0.02	8.9	A	5	-
NB	0.29	24.7	C	47	-	0.69	46.1	D	107	-
SBL	0.18	23.4	C	24	82	0.21	35.0	D	18	82
SBTR	0.17	22.8	C	32	-	0.30	35.0	C	47	-
Highway 115 NB Ramp & Syer Line / County Road 10 (signalized)	0.83	14.0	B	-	-	0.91	41.0	D	-	-
EBL	0.52	51.6	D	17	100	0.70	54.1	D	50	100
EBTR	0.02	43.7	D	7	-	0.05	39.4	D	12	-
WB	0.04	43.9	D	7	-	0.08	39.7	D	12	-
NBL	0.83	12.1	B	93	230	0.93	45.8	D	200	230
NBTR	0.11	1.9	A	12	-	0.18	4.6	A	27	-
SB	0.35	16.1	B	70	-	0.89	44.9	D	161	-

The results of the LOS analysis indicate that the Highway 115 SB Ramp & Syer Line / County Road 10 intersection is operating marginally outside the typical design limits as noted in Section 3.1. Since the delay is under LOS F and the anticipated queuing is not anticipated to cause any notable issues as noted below, no further improvements are recommended.

There are no issues regarding the anticipated queue for all other movements in the study area.

No further infrastructure improvements are recommended for the background (2033) scenario within the study area.

3.5 Background (2038) Intersection Operation

The results of the LOS analysis under background (2038) traffic volumes during the AM and PM peak hour can be found below in **Table 11**. The recommended improvements identified in Section 3.2, 3.3 and 3.4 have been utilized in this scenario. Detailed output of the Synchro analysis can be found in **Appendix E**.

Table 11 – Background (2038) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (signalized)	0.52	25.8	C	-	-	0.84	32.7	C	-	-
EB	0.05	15.4	B	9	-	0.08	30.0	C	16	-
WBL	0.68	29.4	C	114	190	0.85	23.9	C	163	190
WBTR	0.03	15.7	B	6	-	0.02	8.9	A	6	-
NB	0.33	25.4	C	53	-	0.77	50.8	D	127	-
SBL	0.21	23.9	C	27	82	0.27	36.8	D	21	82
SBTR	0.19	23.1	C	35	-	0.35	35.9	D	54	-
Highway 115 NB Ramp & Syer Line / County Road 10 (signalized)	0.83	19.8	B	-	-	0.98	52.8	D	-	-
EBL	0.44	47.5	D	20	100	0.73	56.2	E	55	100
EBTR	0.03	42.6	D	8	-	0.05	38.8	D	12	-
WB	0.05	42.8	D	8	-	0.11	39.3	D	15	-
NBL	0.84	17.8	B	124	230	1.00	66.5	E	229	230
NBTR	0.13	2.4	A	14	-	0.20	5.2	A	32	-
SB	0.47	24.3	C	77	-	0.97	56.6	E	183	-

The results of the LOS analysis indicate that the Highway 115 SB Ramp & Syer Line / County Road 10 and Highway 115 NB Ramp & Syer Line / County Road 10 intersections are operating marginally outside the typical design limits as noted in Section 3.1. Since the delay is under LOS F and the anticipated queuing is not anticipated to cause any notable issues as noted below, no further improvements are recommended.

There are no issues regarding the anticipated queue for all other movements in the study area.

No additional infrastructure improvements are recommended for the background (2038) scenario within the study area.

Notwithstanding, based on the traffic operations at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection the following additional long-term interchange improvements should also be considered for planning purposes:

- Highway 115 NB Ramp & Syer Line / County Road 10
 - Twin the northbound left turn lane on County Road 10
 - Construct a second northbound on-ramp lane.

4 Proposed Development Traffic Generation and Assignment

4.1 Traffic Generation

The traffic generation for the Subject Site has been based on the ITE Trip Generation Manual. The following ITE land use has been applied to estimate the traffic from the proposed development:

- ITE land use 110 (General Light Industrial) – General Urban/Suburban Setting

The estimated trip generation of the proposed development is illustrated below in **Table 12**. The AM and PM peak traffic generation for the proposed development does not exactly align with the AM and PM peak hour in the traffic counts; consequently, we have applied the peak hour of adjacent street traffic values provided in the ITE Trip Generation Manual.

Table 12 – Estimated Traffic Generation of Proposed Development

Land Use	Size	AM Peak Hour			PM Peak Hour		
		IN	OUT	TOTAL	IN	OUT	TOTAL
General Light Industrial ITE Land Use: 110	225 employees	102	21	123	25	87	112

No transportation modal split has been applied to the above-noted traffic generation calculation in order to be conservative.

4.2 Traffic Assignment

For the purposes of this study, it has been assumed that all traffic generated by the proposed development will be new traffic and would not be in the study area if the development was not constructed.

The ITE data provides the anticipated percentage of new traffic entering and exiting during the peak hour.

The distribution of traffic within the study area has been calculated based on the 2016 TTS data for the Township, retrieved using the TTS IDRS (output attached as **Appendix I**). TTS data provides historical origin and destination work trip percentages for specific areas within the Town and southern Ontario.

Traffic distribution for the trips generated by the proposed development during the AM and PM peak hour is expected to generally follow commuter travel patterns. Our analysis is based on ingress traffic during the AM peak hour. Logically, the distribution of ingress traffic will follow the inverse of the exiting traffic distribution. For each of the individual areas identified in the TTS data, we have selected the probable route of travel, assuming that people will select their route primarily based on travel time.

Table 13 illustrates the traffic distribution for the automobile trips in the proposed development, using the methodology outlined above.

Table 13 – Proposed Development Traffic Distribution

Travel Direction (to/from)	Percent of Total Traffic Generation
West via Highway 115	10%
East via Highway 115	52%
South via County Road 10	12%
North via County Road 10	26%
Total	100%

Using the traffic distribution patterns noted above, the traffic assignment for the proposed development was calculated for the AM and PM peak hour and is illustrated in **Figure 19**.

4.3 Total Horizon Year Traffic Volumes with the Proposed Development

For the total (2028, 2033 and 2038) horizon year traffic volumes, the proposed development traffic was added to the background (2028, 2033 and 2038) traffic volumes. The resulting total (2028, 2033 and 2038) horizon year traffic volumes for the AM and PM peak hour are illustrated in **Figures 20, 21 and 22** respectively.

Figure 19 – Proposed Development Traffic Assignment




Figure 20 – Total (2028) Traffic Volumes




Figure 21 – Total (2033) Traffic Volumes





Figure 22 – Total (2038) Traffic Volumes



5 Intersection Operation with Proposed Development

5.1 Total (2028) Intersection Operation

The results of the LOS analysis under total (2028) traffic volumes during the AM and PM peak hour can be found below in **Table 14**. The recommended improvements identified in Section 3.3 has been utilized in this scenario. Detailed output of the Synchro analysis can be found in **Appendix F**.

Table 14 – Total (2028) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (signalized)	0.53	24.6	C	-	-	0.83	39.7	D	-	-
EB	0.04	12.1	B	7	-	0.04	7.2	A	6	-
WB	0.69	25.3	C	108	-	0.83	26.4	C	216	-
NB	0.30	26.1	C	44	-	0.83	68.9	E	142	-
SBL	0.18	24.6	C	22	82	0.28	49.0	D	20	82
SBTR	0.21	24.7	C	36	-	0.33	46.2	D	53	-
Highway 115 NB Ramp & Syer Line / County Road 10 (signalized)	0.80	19.8	B	-	-	1.05	71.6	E	-	-
EB	0.44	47.1	D	21	-	0.90	93.5	F	85	-
WB	0.16	43.6	D	13	-	0.40	50.6	D	48	-
NBL	0.81	14.4	B	86	85	1.06	83.6	F	188	85
NBTR	0.12	2.3	A	12	-	0.17	5.7	A	26	-
SB	0.74	26.4	C	199	-	1.05	78.1	E	364	-
Syer Line / Street A (unsignalized)	-	6.5	A	-	-	-	6.0	A	-	-
NB	0.00	10.6	B	0	-	0.00	10.3	B	0	-
SB	0.02	8.4	A	1	-	0.09	8.8	A	3	-

The results of the LOS analysis indicate that the Highway 115 NB Ramp & Syer Line / County Road 10 intersection is operating marginally outside the typical design limits as noted in Section 3.1. Since the delay is under LOS F and the V/C ratio marginally exceeds the theoretical capacity of 1.0, no further improvements are recommended. As noted above, it is recommended the MTO monitor the queuing at the intersection closer to the 2028 horizon year as the development in the Millbrook community progresses, to determine if further improvements are recommended.

The anticipated queuing for northbound left turn movements at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection is anticipated to extend past the existing storage length; however, the excess queue will not block any adjacent intersection. As noted above, it is recommended this queuing is monitored as the development in the Millbrook community progresses.

There are no issues regarding the anticipated queue for all other movements in the study area.

An analysis was completed for left turn movements at the Syer Line / Street A intersection, based on the criteria outlined in Appendix 9A of the MTO DS (results are provided in **Appendix G**). Based on the

above noted criteria additional auxiliary left-turn lane is not warranted at the Syer Line / Street A intersection.

A review of the need for an auxiliary right turn lane at the Syer Line / Street A intersection was completed as part of our analysis. The results of the Synchro analysis indicate that there is excess capacity for all movements; consequently, auxiliary right turn lanes are not recommended.

Based on the Ontario Traffic Manual Book 12 *Signal Justification*, traffic signals are not warranted at Syer Line / Street A intersection (results are provided in **Appendix H**).

No further infrastructure improvements are recommended for the total (2028) scenario within the study area.

5.2 Total (2033) Intersection Operation

The results of the LOS analysis under total (2033) traffic volumes during the AM and PM peak hour can be found below in **Table 15**. The recommended improvements identified in Sections 3.3 and 3.4 have been utilized in this scenario. Detailed output of the Synchro analysis can be found in **Appendix F**.

Table 15 – Total (2033) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (signalized)	0.53	27.2	C	-	-	0.82	31.5	C	-	-
EB	0.04	15.4	B	9	-	0.07	27.4	C	14	-
WBL	0.73	31.9	C	129	190	0.83	22.5	C	154	190
WBTR	0.02	15.6	B	5	-	0.02	8.9	A	5	-
NB	0.30	24.9	C	49	-	0.76	49.8	D	120	-
SBL	0.18	23.4	C	24	82	0.23	35.8	D	18	82
SBTR	0.21	23.3	C	38	-	0.31	35.2	D	49	-
Highway 115 NB Ramp & Syer Line / County Road 10 (signalized)	0.81	20.7	C	-	-	0.95	48.1	D	-	-
EBL	0.39	46.8	D	17	100	0.80	66.3	E	52	100
EBTR	0.11	43.3	D	11	-	0.06	38.7	D	13	-
WB	0.16	43.7	D	13	-	0.41	42.2	D	40	-
NBL	0.83	18.1	B	116	230	0.96	54.3	D	212	230
NBTR	0.13	2.3	A	13	-	0.19	5.2	A	30	-
SB	0.55	25.0	C	86	-	0.95	53.2	D	174	-
Syer Line / Street A (unsignalized)	-	6.5	A	-	-	-	5.8	A	-	-
NB	0.00	10.7	B	0	-	0.00	10.3	B	0	-
SB	0.02	8.4	A	1	-	0.09	8.8	A	3	-

The results of the LOS analysis indicate that the Highway 115 SB Ramp & Syer Line / County Road 10 intersection is operating marginally outside the typical design limits as noted in Section 3.1. Since the delay is under LOS F and the anticipated queuing is not anticipated to cause any notable issues as noted below, no further improvements are recommended.

There are no issues regarding the anticipated queue for all other movements in the study area.

An analysis was completed for left turn movements at the Syer Line / Street A intersection, based on the criteria outlined in Appendix 9A of the MTO DS (results are provided in **Appendix G**). Based on the above noted criteria additional auxiliary left-turn lane is not warranted at the Syer Line / Street A intersection.

A review of the need for an auxiliary right turn lane at the Syer Line / Street A intersection was completed as part of our analysis. The results of the Synchro analysis indicate that there is excess capacity for all movements; consequently, auxiliary right turn lanes are not recommended.

Based on the Ontario Traffic Manual Book 12 *Signal Justification*, traffic signals are not warranted at Syer Line / Street A intersection (results are provided in **Appendix H**).

No further infrastructure improvements are recommended for the total (2033) scenario within the study area.

5.3 Total (2038) Intersection Operation

The results of the LOS analysis under total (2038) traffic volumes during the AM and PM peak hour can be found below in **Table 16**. The recommended improvements identified in Sections 3.3 and 3.4 have been utilized in this scenario. Detailed output of the Synchro analysis can be found in **Appendix F**.

Table 16 – Total (2038) LOS

Location (E-W Street / N-S Street)	Weekday AM Peak Hour					Weekday PM Peak Hour				
	V/C	Delay (s)	LOS	95 th Percentile Queue		V/C	Delay (s)	LOS	95 th Percentile Queue	
				Model	Storage				Model	Storage
Highway 115 SB Ramp & Syer Line / County Road 10 (unsignalized)	0.58	28.5	C	-	-	0.87	35.2	D	-	-
EB	0.05	15.4	B	9	-	0.08	30.4	C	16	-
WBL	0.78	34.6	C	141	190	0.86	25.2	C	168	190
WBTR	0.03	15.7	B	6	-	0.02	8.9	A	6	-
NB	0.34	25.6	C	55	-	0.84	56.2	E	145	-
SBL	0.21	23.9	C	27	82	0.29	38.1	D	21	82
SBTR	0.23	23.7	C	42	-	0.36	36.1	D	56	-
Highway 115 NB Ramp & Syer Line / County Road 10 (unsignalized)	0.82	25.1	C	-	-	1.01	63.0	E	-	-
EBL	0.45	47.6	D	20	100	0.85	73.3	E	62	100
EBTR	0.12	43.2	D	12	-	0.06	38.1	D	13	-
WB	0.19	43.8	D	115	-	0.42	41.8	D	44	-
NBL	0.84	20.8	C	148	230	1.03	73.7	E	229	230
NBTR	0.14	2.4	A	14	-	0.21	5.9	A	32	-
SB	0.69	32.9	C	101	-	1.03	73.0	E	192	-
Syer Line / Street A (unsignalized)	-	6.4	A	-	-	-	5.6	A	-	-
NB	0.00	10.7	B	0	-	0.00	10.4	B	0	-
SB	0.02	8.4	A	1	-	0.09	8.8	A	3	-

The results of the LOS analysis indicate that the Highway 115 SB Ramp & Syer Line / County Road 10 and Highway 115 NB Ramp & Syer Line / County Road 10 intersections are operating marginally outside the typical design limits as noted in Section 3.1. Since the delay is under LOS F and the

anticipated queuing is not anticipated to cause any notable issues as noted below, no further improvements are recommended.

There are no issues regarding the anticipated queue for all other movements in the study area.

An analysis was completed for left turn movements at the Syer Line / Street A intersection, based on the criteria outlined in Appendix 9A of the MTO DS (results are provided in **Appendix G**). Based on the above noted criteria additional auxiliary left-turn lane is not warranted at the Syer Line / Street A intersection.

A review of the need for an auxiliary right turn lane at the Syer Line / Street A intersection was completed as part of our analysis. The results of the Synchro analysis indicate that there is excess capacity for all movements; consequently, auxiliary right turn lanes are not recommended.

Based on the Ontario Traffic Manual Book 12 *Signal Justification*, traffic signals are not warranted at Syer Line / Street A intersection (results are provided in **Appendix H**).

No further infrastructure improvements are recommended for the total (2038) scenario within the study area.

As noted in Section 3.5, based on the traffic operations at the Highway 115 NB Ramp & Syer Line / County Road 10 intersection the following additional long-term interchange improvements should also be considered for planning purposes:

- Highway 115 NB Ramp & Syer Line / County Road 10
 - Twin the northbound left turn lane on County Road 10
 - Construct a second northbound on-ramp lane.

5.4 Site Access

Street A will operate efficiently as a full-movement access, with one-way stop control for southbound movements. No lane improvements are recommended on Syer Line at Street A. A single ingress and egress lane at Street A will provide the necessary capacity to service the proposed development.

The proposed spacing between Street A and County Road 10 (1.11 km) and Street A and Hutchinson Drive (2.67 km) is greater than the desired spacing between adjacent intersections on a local road (40 metres) identified in Section 9.4.2.1 of the TAC Guidelines.

5.5 Sight Distance Review

A review of the available sight distance for the Street A access was completed as part of this analysis.

The sight distance east and west of Street A (greater than 200 metres) is greater than the minimum stopping and intersection sight distance requirements as per the TAC Guidelines for a design speed of 60 km/h (85 and 130 metres respectively).

The sight distance east and west of the potential driveway for Block 5 in the proposed development onto Syer Line (greater than 200 metres) is greater than the minimum stopping and intersection sight distance requirements as per the TAC Guidelines for a design speed of 60 km/h (85 and 130 metres respectively).

Consequently, there are no issues with the sight distance available for the proposed access.

6 Summary

The **SLIP DEVCO INC.** retained **JD Engineering** to prepare this traffic impact study in support of a proposed rezoning of an undeveloped property (Subject Site), for use as light industrial / employment lands. The Subject Site is located on the north side of Syer Line midblock between County Road 10 and Hutchinson Drive in the Township of Cavan Monaghan, County of Peterborough. This chapter summarizes the conclusions and recommendations from the study.

1. The proposed development is expected to generate a total of 123 AM and 112 PM peak hour trips.
2. Detailed turning movement traffic and pedestrian counts were completed at the intersections of Highway 115 SB Ramp & Syer Line / County Road 10 and Highway 115 NB Ramp & Syer Line / County Road 10, completed on Wednesday, March 1st, 2023.
3. An intersection operation analysis was completed at the study area intersections, using the existing (2023) and background (2028, 2033 and 2038) traffic volumes without the proposed development traffic. This enabled a review of existing and future traffic deficiencies that would be present without the influence of the proposed development. The following improvements are recommended:

Background (2028) Traffic Volumes

- Highway 115 SB Ramp & Syer Line / County Road 10
 - Installation of traffic signals.
- Highway 115 NB Ramp & Syer Line / County Road 10
 - Installation of traffic signals.

Background (2033) Traffic Volumes



- Highway 115 SB Ramp & Syer Line / County Road 10
 - Widen the SB Off-Ramp for the construction of a westbound left turn lane with 150 metre storage length, 40 parallel length and 100 metre taper length and
 - Adjust signal to accommodate a protected + permissive westbound left turn phase.
- Highway 115 NB Ramp & Syer Line / County Road 10
 - Widen the County Road 10, north of the Highway 115 NB Ramp to provide two southbound lanes. The southbound configuration at the intersection should include a through + left lane and a through + right lane.
 - Widen SB Off-Ramp for the construction of an eastbound left turn lane with a 60 metre storage length, 40 parallel length and 100 metre taper length.
 - Extend the northbound left turn lane to provide a 230 metre storage length.

Long-Range Planning (Post 2033)

- Highway 115 NB Ramp & Syer Line / County Road 10
 - Twin the northbound left turn lane on County Road 10
 - Construct a second northbound on-ramp lane.

4. An estimate of the amount of traffic that would be generated by the Subject Site was prepared and assigned to the study area streets and intersections.
5. An intersection operation analysis was completed under total (2028, 2033 and 2038) traffic volumes with the proposed development operational at the study area intersections. No additional improvements are recommended within the study area.
6. It is recommended the MTO and County monitor the queuing on County Road 10 and on the Highway 115 ramps as the future Millbrook developments become fully built-out and occupied (anticipated to start in the existing (2023) year), to determine if infrastructure improvements are warranted noted for the 2028 and 2033 horizon years.
7. Street A will operate efficiently with full-movement access, with one-way stop control for southbound movements. A single ingress and egress lane at Street A will provide the necessary capacity to service the proposed development.
8. The available sight distance at Street A is sufficient for the intended use.
9. In summary, the proposed development will not cause any operational issues and will not add significant delay or congestion to the local roadway network.

Appendix A – Concept Plan



SUECT PROPERT		
AREA = 4293567.78m² (29.35ha)		
LEGEND		
SUBJECT BOUNDARY		
EXISTING PARCEL		
EXISTING ROAD		
ENVIRONMENTAL CONSTRAINTS		
EXISTING WETLANDS		
WETLAND BUFFER (30m)		
WATERCOURSE		
WATERCOURSE BUFFER (30m)		

SITE STATISTICS		
BLOCK/LOT #	AREA (ha)	DESCRIPTION
BLOCK 1	1.17	20 m Right of Way
BLOCK 2	20.54	Developable Area
BLOCK 3	3.23	Developable Area
BLOCK 4	3.23	Environmental Constraints
BLOCK 5	1.14	Wild Drainage Easement
TOTAL	29.34	Developable Area

Subsition Requirements

ADDITIONAL INFORMATION REQUIRED UNDER SECTION 51-17 (a-1) THE PLANNING ACT

a) As shown on this Draft Plan
b) As shown on this Draft Plan
c) As shown on this Draft Plan
d) Rural Employment
e) Agricultural
f) As shown on this Draft Plan
g) As shown on this Draft Plan
h) N/A
i) As shown on this Draft Plan
j) As shown on this Draft Plan
k) None
l) As shown on this Draft Plan

OWNERS CERTIFICATE

I hereby authorize EcoVue Consulting Services Inc. to prepare and submit this plan to the County of Hastings

Sip DeVCo Inc. Date

SURVEYORS CERTIFICATE

This Draft Plan accurately shows the boundaries of all lands proposed to be subdivided.

Certified by:

Elliott and Parr Date
(Peterborough) LTD.



EcoVue Consulting Services Inc.
311 George St. N., Suite 200
Peterborough ON K9J 3H3
Tel: 705-876-8540 Fax: 705-742-8343
www.ecovueconsulting.com

DRAWN BY:	PP	PROJECT NO.:	23-2530
APPROVED BY:		HORIZ. SCALE:	1:1,500
REVISION DATE:	OCTOBER 16, 2023	PLOT DATE:	OCTOBER 16, 2023
Syer Line Industrial Subdivision Sip DeVCo Inc.			
PART OF LOT 14, CONCESSION 18 NOW IN THE TOWNSHIP OF EAVAN, MIDDLESEX COUNTY (PETERBOROUGH)			
CONCEPT PLAN		CP1	

Appendix B – Adjacent Development Reports

Bromont TIS

Traffic Impact Study

Residential Development (West of CR10)

Fallis Line, Millbrook, ON

Township of Cavan Monaghan,

County of Peterborough



January 31, 2022
Project N° 2124-19

AM Peak Hour - Existing Volumes 2021




Exhibit 4: Existing AM Peak Hour Traffic Volumes (2021).



PM Peak Hour - Existing Volumes 2021




Exhibit 5: Existing PM Peak Hour Traffic Volumes (2021).



3 Background Traffic Volumes

3.1 Background Traffic Volumes

In order to establish base conditions for comparison and evaluation of future scenarios, it is necessary to review results of traffic operations over time. The estimated normal growth traffic volumes are based under the premise that existing geometric conditions is maintained and that traffic growth is expected over the next years.

As part of the background volumes; the study includes those major proposed developments that are approved or in construction; the background volumes also include the proposed development “Commercial and Residential” east of CR10 on Fallis Line; the sketch of these developments is shown in Exhibit 7. The traffic volumes of these developments were obtained from the “Millbrook Development Phase 2 – Traffic Impact Study for the Tower Hill Developments Ltd.” Prepared by JD Engineering; these trips are included in the appendix.

Annual growth rate was estimated at 2.0% per year; this rate was used to project existing traffic volumes over the next years.

For estimation of the horizons years traffic volumes, the growth rate was applied to the existing volumes. The growth rate is yearly compounded.

The following Exhibits 8, 9 and 10 show the projected traffic volumes for the morning, afternoon and Saturday peak hours for the horizon years 2025 and 2030, respectively.



Sketch of Developments Within the Area




Exhibit 7: Sketch of Developments Within the Area.






Exhibit 14: AM Peak Hour Development Trips - 2025.

PM Site Generated Trips With Diverted Trips - 2025 (Residential Site West of CR10)




Exhibit 15: PM Peak Hour Development Trips - 2025.



AM Site Generated Trips With Diverted Trips - 2030 (Residential Site West of CR10)




Exhibit 17: AM Peak Hour Development Trips - 2030.



PM Site Generated Trips With Diverted Trips - 2030 (Residential Site West of CR10)




Exhibit 18: PM Peak Hour Development Trips - 2030.



AM Peak Hour - Total Trips - 2025




Exhibit 20: AM Peak Hour Total Trips - 2025.






Exhibit 21: PM Peak Hour Total Trips - 2025.

AM Peak Hour - Total Trips - 2030




Exhibit 23: AM Peak Hour Total Trips - 2030.



PM Peak Hour - Total Trips - 2030




Exhibit 24: PM Peak Hour Total Trips - 2030.



Millbrook Fire Hall TIS



Millbrook Fire Hall

Township of Cavan Monaghan,
County of Peterborough

Traffic Impact Study for the Township of Cavan Monaghan

Type of Document:
Draft Report

Project Number:
JDE – 21138

Date Submitted:
October 29th, 2021

John Northcote, P.Eng.
Professional License #: 100124071

Maitham Dinani, P.Eng.
Professional License #: 100192544



JD Northcote Engineering Inc.
86 Cumberland Street
Barrie, ON
705.725.4035
www.JDEngineering.ca

Table 4 – Background (2026) LOS

Location (N-S Street / E-W Street)	Weekday AM Peak Hour			Weekday PM Peak Hour		
	V/C	Delay (s)	LOS	V/C	Delay (s)	LOS
County Road 10 / Street B (unsignalized)	-	12.8	A	-	7.0	A
EB	0.92	85.1	F	0.82	82.9	F
County Road 10 / Municipal Office & Community Centre Driveway (unsignalized)	-	0.3	A	-	0.3	A
EB	0.03	12.5	B	0.06	21.0	C

The results of the LOS analysis indicate that the eastbound movements at the County Road 10 / Street B intersection are operating outside the typical design limits; however, no improvements are recommended as it is anticipated that eastbound traffic volumes at this intersection will redistribute as the eastbound control delay increases, to the signalized County Road 10 / Fallis Line intersection via the internal road network and various intersections constructed on Fallis Line in Phase 2 of the Millbrook Development.

The results of the LOS analysis indicate that all other intersections in the study area are operating within the typical design limits noted in Section 3.1.

For right turn movements at the unsignalized intersections in the study area, the criteria outlined in Appendix G of the VDOT RDM were applied. Based on the above noted criteria, a right turn lane is not warranted at any of the unsignalized intersections in the study area (results provided in **Appendix I**).

Based on the Ontario Traffic Manual Book 12 *Signal Justification*, traffic signals are not warranted at any of the unsignalized intersections in the study area (results are provided in **Appendix H**).

The anticipated 95th percentile queue can be accommodated for all proposed storage lanes in the study area.

No additional improvements are recommended within the study area for the background (2026) scenario.

4 Proposed Development Traffic Generation and Assignment

4.1 Traffic Generation

The proposed development will be occupied by two user groups; the Township's Fire and Emergency Service and the County's Paramedic Service. Each service will generate varying levels of traffic based on the following factors: staffing / shift changes, number of emergency calls, number of visitors, number of deliveries. The AM and PM traffic generation for each service has been confirmed through discussions with Township and County staff.

The proposed development's breakdown of use by each service is summarized in **Table 5**.

Table 5 – Proposed Development Operational Data

Service	Number of Employees	Number of Emergency Calls	Number of Visitors	Number of Deliveries
County Paramedic Service	2 staff from 8:00 – 20:00 2 staff from 20:00 – 8:00	2 in a 24 hour period	None	1 per week
Township Fire Service	3 staff from 8:30 – 16:30*	2 in a 24 hour period	1-2 per week	2 per week

* Calls are responded to from home, outside staff hours

Based on our review of the information provided by the two user groups, the estimated trip generation during the AM and PM peak hour for each user group of the subject site is illustrated below in **Tables 6 and 7**. The total estimated trip generation for the proposed development is illustrated below in **Table 8**.

Table 6 – Estimated Traffic Generation for the County's Paramedic Services

	AM Peak Hour			PM Peak Hour		
	IN	OUT	TOTAL	IN	OUT	TOTAL
Employees*	2	2	4	-	-	-
Emergency Calls**	1	1	2	1	1	2
Visitors	-	-	-	-	-	-
Deliveries***	1	1	2	1	1	2
TOTAL TRIPS	4	4	8	2	2	4

*The morning shift change occurs in the AM peak hour and the evening shift change occurs outside the peak hours

** It is assumed one emergency call will occur during each peak hour

*** It is assumed one delivery will occur during each peak hour

Table 7 – Estimated Traffic Generation for the Township's Fire Services

	AM Peak Hour			PM Peak Hour		
	IN	OUT	TOTAL	IN	OUT	TOTAL
Employees*	3	0	3	0	3	3
Emergency Calls**	1	1	2	1	1	2
Visitors***	1	1	2	1	1	2
Deliveries****	1	1	2	1	1	2
TOTAL TRIPS	6	3	9	3	6	9

*It is assumed all staff will arrive in the AM peak hour and exit in the PM peak hour

** It is assumed one emergency call will occur during each peak hour

*** It is assumed one visitor will visit during each peak hour

**** It is assumed one delivery will occur during each peak hour

Table 8 – Estimated Traffic Generation Summary for Proposed Development

Service	AM Peak Hour			PM Peak Hour		
	IN	OUT	TOTAL	IN	OUT	TOTAL
County's Paramedic Services	4	4	8	2	2	4
Township's Fire and Emergency Services	6	3	9	3	6	9
TOTAL TRIPS	10	7	17	5	8	13

No transportation modal split reduction has been applied to the above-noted traffic generation calculation.

4.2 Traffic Assignment


The distribution of traffic for the proposed development is based on the distribution of the existing traffic volumes within the study area. **Table 9** illustrates the calculation of the distribution of ingress and egress traffic for the proposed development.

Table 9 – Proposed Development Traffic Distribution

Travel Direction (to / from)	AM Peak Hour		PM Peak Hour	
	Ingress	Egress	Ingress	Egress
North via County Road 10	43%	57%	57%	43%
South via County Road 10	57%	43%	43%	57%
TOTAL	100%	100%	100%	100%

Using the traffic distributions pattern noted above, the traffic assignment for the proposed development was calculated for the AM and PM peak hour and is illustrated in **Figure 12**.

Figure 12 – Proposed Development Traffic Assignment



Appendix C – Traffic Count Data

Morning Peak Diagram		Specified Period From: 7:00:00 To: 9:00:00	One Hour Peak From: 7:30:00 To: 8:30:00
Municipality: Cavan-Monaghan Site #: 2305000001 Intersection: County Rd 10 & Syer Line TFR File #: 1 Count date: 1-Mar-23		Weather conditions: Person counted: Person prepared: Person checked:	
** Non-Signalized Intersection **		Major Road: County Rd 10 runs N/S	

North Leg Total: 218 North Entering: 141 North Peds: 0 Peds Cross:	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Heavys</td> <td style="text-align: right;">0</td> <td style="text-align: right;">1</td> <td style="text-align: right;">0</td> <td style="border-left: 1px solid black; text-align: right;">1</td> </tr> <tr> <td style="text-align: right;">Trucks</td> <td style="text-align: right;">0</td> <td style="text-align: right;">0</td> <td style="text-align: right;">0</td> <td style="border-left: 1px solid black; text-align: right;">0</td> </tr> <tr> <td style="text-align: right;">Cars</td> <td style="text-align: right;">6</td> <td style="text-align: right;">75</td> <td style="text-align: right;">59</td> <td style="border-left: 1px solid black; text-align: right;">140</td> </tr> <tr> <td style="text-align: right;">Totals</td> <td style="text-align: right;">6</td> <td style="text-align: right;">76</td> <td style="text-align: right;">59</td> <td style="border-left: 1px solid black; text-align: right;"></td> </tr> </table>	Heavys	0	1	0	1	Trucks	0	0	0	0	Cars	6	75	59	140	Totals	6	76	59		<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Heavys</td> <td style="text-align: right;">8</td> </tr> <tr> <td style="text-align: right;">Trucks</td> <td style="text-align: right;">1</td> </tr> <tr> <td style="text-align: right;">Cars</td> <td style="text-align: right;">68</td> </tr> <tr> <td style="text-align: right;">Totals</td> <td style="text-align: right;">77</td> </tr> </table>	Heavys	8	Trucks	1	Cars	68	Totals	77	East Leg Total: 205 East Entering: 116 East Peds: 0 Peds Cross:
Heavys	0	1	0	1																											
Trucks	0	0	0	0																											
Cars	6	75	59	140																											
Totals	6	76	59																												
Heavys	8																														
Trucks	1																														
Cars	68																														
Totals	77																														

Heavys	Trucks	Cars	Totals
2	0	20	22

County Rd 10

Cars	Trucks	Heavys	Totals
3	0	1	4
3	0	1	4
103	1	4	108
109	1	6	

N
S
E
W

Heavys	Trucks	Cars	Totals
1	0	6	7
1	0	4	5
1	0	22	23
3	0	32	

Syer Line

Cars	Trucks	Heavys	Totals
88	0	1	89

Highway 115 NB Ramp

Cars	Trucks	Heavys	Totals
11	59	25	95
0	1	0	1
1	6	0	7
12	66	25	

County Rd 10

Cars	Trucks	Heavys	Totals
200	1	6	207

Peds Cross: West Peds: 0 West Entering: 35 West Leg Total: 57	Cars 200 Trucks 1 Heavys 6 Totals 207	Cars 11 Trucks 0 Heavys 1 Totals 12	Cars 59 Trucks 1 Heavys 6 Totals 66	Cars 25 Trucks 0 Heavys 0 Totals 25	Peds Cross: South Peds: 0 South Entering: 103 South Leg Total: 310
--	--	--	--	--	---

Comments

Afternoon Peak Diagram		Specified Period From: 16:00:00 To: 19:00:00	One Hour Peak From: 16:30:00 To: 17:30:00
Municipality: Cavan-Monaghan Site #: 2305000001 Intersection: County Rd 10 & Syer Line TFR File #: 1 Count date: 1-Mar-23		Weather conditions: Person counted: Person prepared: Person checked:	
** Non-Signalized Intersection **		Major Road: County Rd 10 runs N/S	

North Leg Total: 348 North Entering: 125 North Peds: 0 Peds Cross:	<table style="width: 100%; border-collapse: collapse;"> <tr><td>Heavys</td><td>0</td><td>2</td><td>0</td><td>2</td></tr> <tr><td>Trucks</td><td>0</td><td>1</td><td>0</td><td>1</td></tr> <tr><td>Cars</td><td>5</td><td>87</td><td>30</td><td>122</td></tr> <tr><td>Totals</td><td>5</td><td>90</td><td>30</td><td></td></tr> </table>	Heavys	0	2	0	2	Trucks	0	1	0	1	Cars	5	87	30	122	Totals	5	90	30		<table style="width: 100%; border-collapse: collapse;"> <tr><td>Heavys</td><td>1</td></tr> <tr><td>Trucks</td><td>3</td></tr> <tr><td>Cars</td><td>219</td></tr> <tr><td>Totals</td><td>223</td></tr> </table>	Heavys	1	Trucks	3	Cars	219	Totals	223	East Leg Total: 271 East Entering: 222 East Peds: 0 Peds Cross:
Heavys	0	2	0	2																											
Trucks	0	1	0	1																											
Cars	5	87	30	122																											
Totals	5	90	30																												
Heavys	1																														
Trucks	3																														
Cars	219																														
Totals	223																														

Heavys	Trucks	Cars	Totals
2	1	34	37

County Rd 10

County Rd 10

Cars	Trucks	Heavys	Totals
2	0	0	2
11	1	1	13
207	0	0	207
220	1	1	

Heavys	Trucks	Cars	Totals
0	0	11	11
1	0	6	7
1	0	24	25
2	0	41	

Syer Line

Highway 115 NB Ramp

Heavys	Trucks	Cars	Totals
0	0	11	11
1	0	6	7
1	0	24	25
2	0	41	

County Rd 10

Cars	Trucks	Heavys	Totals
48	0	1	49

Peds Cross: West Peds: 0 West Entering: 43 West Leg Total: 80	<table style="width: 100%; border-collapse: collapse;"> <tr><td>Cars</td><td>318</td></tr> <tr><td>Trucks</td><td>1</td></tr> <tr><td>Heavys</td><td>3</td></tr> <tr><td>Totals</td><td>322</td></tr> </table>	Cars	318	Trucks	1	Heavys	3	Totals	322	<table style="width: 100%; border-collapse: collapse;"> <tr><td>Cars</td><td>18</td><td>206</td><td>12</td><td>236</td></tr> <tr><td>Trucks</td><td>0</td><td>3</td><td>0</td><td>3</td></tr> <tr><td>Heavys</td><td>1</td><td>1</td><td>0</td><td>2</td></tr> <tr><td>Totals</td><td>19</td><td>210</td><td>12</td><td></td></tr> </table>	Cars	18	206	12	236	Trucks	0	3	0	3	Heavys	1	1	0	2	Totals	19	210	12		Peds Cross: South Peds: 0 South Entering: 241 South Leg Total: 563
Cars	318																														
Trucks	1																														
Heavys	3																														
Totals	322																														
Cars	18	206	12	236																											
Trucks	0	3	0	3																											
Heavys	1	1	0	2																											
Totals	19	210	12																												

Comments

Total Count Diagram


Municipality: Cavan-Monaghan
Site #: 2305000001
Intersection: County Rd 10 & Syer Line
TFR File #: 1
Count date: 1-Mar-23

Weather conditions:

Person counted:
Person prepared:
Person checked:

**** Non-Signalized Intersection ****

Major Road: County Rd 10 runs N/S



Traffic Count Summary

Intersection: County Rd 10 & Syer Line					Count Date: 1-Mar-23		Municipality: Cavan-Monaghan					
North Approach Totals						North/South Total Approaches	South Approach Totals					
Hour Ending	Includes Cars, Trucks, & Heavys				Total Peds		Hour Ending	Includes Cars, Trucks, & Heavys				Total Peds
	Left	Thru	Right	Grand Total				Left	Thru	Right	Grand Total	
7:00:00	0	0	0	0	0	0	7:00:00	0	0	0	0	0
8:00:00	73	63	3	139	0	229	8:00:00	5	56	29	90	0
9:00:00	45	66	4	115	0	218	9:00:00	11	73	19	103	0
16:00:00	0	0	0	0	0	0	16:00:00	0	0	0	0	0
17:00:00	24	76	8	108	0	337	17:00:00	20	193	16	229	0
18:00:00	31	86	1	118	0	335	18:00:00	17	186	14	217	0
19:00:00	22	46	4	72	0	188	19:00:00	9	100	7	116	0

Morning Peak Diagram		Specified Period From: 7:00:00 To: 9:00:00	One Hour Peak From: 7:45:00 To: 8:45:00
Municipality: Cavan-Monaghan Site #: 2305000002 Intersection: County Rd 10 & Syer Line TFR File #: 1 Count date: 1-Mar-23		Weather conditions: Person counted: Person prepared: Person checked:	
** Non-Signalized Intersection **		Major Road: County Rd 10 runs N/S	

North Leg Total: 316 North Entering: 200 North Peds: 0 Peds Cross:	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Heavys</td> <td style="text-align: right;">1</td> <td style="text-align: right;">2</td> <td style="text-align: right;">0</td> <td style="border-left: 1px solid black; text-align: right;">3</td> </tr> <tr> <td style="text-align: right;">Trucks</td> <td style="text-align: right;">0</td> <td style="text-align: right;">0</td> <td style="text-align: right;">0</td> <td style="border-left: 1px solid black; text-align: right;">0</td> </tr> <tr> <td style="text-align: right;">Cars</td> <td style="text-align: right;">13</td> <td style="text-align: right;">175</td> <td style="text-align: right;">9</td> <td style="border-left: 1px solid black; text-align: right;">197</td> </tr> <tr> <td style="text-align: right;">Totals</td> <td style="text-align: right;">14</td> <td style="text-align: right;">177</td> <td style="text-align: right;">9</td> <td style="border-left: 1px solid black; text-align: right;">197</td> </tr> </table>	Heavys	1	2	0	3	Trucks	0	0	0	0	Cars	13	175	9	197	Totals	14	177	9	197	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Heavys</td> <td style="text-align: right;">8</td> </tr> <tr> <td style="text-align: right;">Trucks</td> <td style="text-align: right;">2</td> </tr> <tr> <td style="text-align: right;">Cars</td> <td style="text-align: right;">106</td> </tr> <tr> <td style="text-align: right;">Totals</td> <td style="text-align: right;">116</td> </tr> </table>	Heavys	8	Trucks	2	Cars	106	Totals	116	East Leg Total: 20 East Entering: 9 East Peds: 0 Peds Cross:
Heavys	1	2	0	3																											
Trucks	0	0	0	0																											
Cars	13	175	9	197																											
Totals	14	177	9	197																											
Heavys	8																														
Trucks	2																														
Cars	106																														
Totals	116																														

Heavys	Trucks	Cars	Totals
4	0	188	192

Highway 115 SB Ramp

Heavys	Trucks	Cars	Totals
4	1	19	24
0	0	1	1
1	0	3	4
5	1	23	

County Rd 10

Cars	Trucks	Heavys	Totals
6	0	0	6
1	0	0	1
1	0	1	2
8	0	1	

Syer Line

Cars	Trucks	Heavys	Totals
11	0	0	11

Peds Cross: West Peds: 0 West Entering: 29 West Leg Total: 221	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Cars</td> <td style="text-align: right;">179</td> </tr> <tr> <td style="text-align: right;">Trucks</td> <td style="text-align: right;">0</td> </tr> <tr> <td style="text-align: right;">Heavys</td> <td style="text-align: right;">4</td> </tr> <tr> <td style="text-align: right;">Totals</td> <td style="text-align: right;">183</td> </tr> </table>	Cars	179	Trucks	0	Heavys	4	Totals	183	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: right;">Cars</td> <td style="text-align: right;">174</td> <td style="text-align: right;">81</td> <td style="text-align: right;">1</td> <td style="border-left: 1px solid black; text-align: right;">256</td> </tr> <tr> <td style="text-align: right;">Trucks</td> <td style="text-align: right;">0</td> <td style="text-align: right;">1</td> <td style="text-align: right;">0</td> <td style="border-left: 1px solid black; text-align: right;">1</td> </tr> <tr> <td style="text-align: right;">Heavys</td> <td style="text-align: right;">3</td> <td style="text-align: right;">4</td> <td style="text-align: right;">0</td> <td style="border-left: 1px solid black; text-align: right;">7</td> </tr> <tr> <td style="text-align: right;">Totals</td> <td style="text-align: right;">177</td> <td style="text-align: right;">86</td> <td style="text-align: right;">1</td> <td style="border-left: 1px solid black; text-align: right;">264</td> </tr> </table>	Cars	174	81	1	256	Trucks	0	1	0	1	Heavys	3	4	0	7	Totals	177	86	1	264	Peds Cross: South Peds: 0 South Entering: 264 South Leg Total: 447
Cars	179																														
Trucks	0																														
Heavys	4																														
Totals	183																														
Cars	174	81	1	256																											
Trucks	0	1	0	1																											
Heavys	3	4	0	7																											
Totals	177	86	1	264																											

Comments

Afternoon Peak Diagram		Specified Period From: 16:00:00 To: 19:00:00	One Hour Peak From: 16:30:00 To: 17:30:00
Municipality: Cavan-Monaghan Site #: 2305000002 Intersection: County Rd 10 & Syer Line TFR File #: 1 Count date: 1-Mar-23		Weather conditions: Person counted: Person prepared: Person checked:	
** Non-Signalized Intersection **		Major Road: County Rd 10 runs N/S	

North Leg Total: 562 North Entering: 321 North Peds: 0 Peds Cross:	<table style="width: 100%; border-collapse: collapse;"> <tr><td>Heavys</td><td>1</td><td>2</td><td>0</td><td>3</td></tr> <tr><td>Trucks</td><td>0</td><td>1</td><td>0</td><td>1</td></tr> <tr><td>Cars</td><td>18</td><td>288</td><td>11</td><td>317</td></tr> <tr><td>Totals</td><td>19</td><td>291</td><td>11</td><td></td></tr> </table>	Heavys	1	2	0	3	Trucks	0	1	0	1	Cars	18	288	11	317	Totals	19	291	11		<table style="width: 100%; border-collapse: collapse;"> <tr><td>Heavys</td><td>2</td></tr> <tr><td>Trucks</td><td>3</td></tr> <tr><td>Cars</td><td>236</td></tr> <tr><td>Totals</td><td>241</td></tr> </table>	Heavys	2	Trucks	3	Cars	236	Totals	241	East Leg Total: 45 East Entering: 22 East Peds: 0 Peds Cross:
Heavys	1	2	0	3																											
Trucks	0	1	0	1																											
Cars	18	288	11	317																											
Totals	19	291	11																												
Heavys	2																														
Trucks	3																														
Cars	236																														
Totals	241																														

Heavys	Trucks	Cars	Totals
3	0	211	214

Highway 115 SB Ramp

Heavys	Trucks	Cars	Totals
1	2	93	96
0	0	2	2
0	0	26	26
1	2	121	

County Rd 10

Cars	Trucks	Heavys	Totals
9	0	0	9
7	0	0	7
6	0	0	6
22	0	0	

Syer Line

Cars	Trucks	Heavys	Totals
23	0	0	23

Peds Cross: West Peds: 0 West Entering: 124 West Leg Total: 338	<table style="width: 100%; border-collapse: collapse;"> <tr><td>Cars</td><td>320</td></tr> <tr><td>Trucks</td><td>1</td></tr> <tr><td>Heavys</td><td>2</td></tr> <tr><td>Totals</td><td>323</td></tr> </table>	Cars	320	Trucks	1	Heavys	2	Totals	323	<table style="width: 100%; border-collapse: collapse;"> <tr><td>Cars</td><td>186</td><td>134</td><td>10</td><td>330</td></tr> <tr><td>Trucks</td><td>0</td><td>1</td><td>0</td><td>1</td></tr> <tr><td>Heavys</td><td>2</td><td>1</td><td>0</td><td>3</td></tr> <tr><td>Totals</td><td>188</td><td>136</td><td>10</td><td></td></tr> </table>	Cars	186	134	10	330	Trucks	0	1	0	1	Heavys	2	1	0	3	Totals	188	136	10		Peds Cross: South Peds: 0 South Entering: 334 South Leg Total: 657
Cars	320																														
Trucks	1																														
Heavys	2																														
Totals	323																														
Cars	186	134	10	330																											
Trucks	0	1	0	1																											
Heavys	2	1	0	3																											
Totals	188	136	10																												

Comments

Total Count Diagram


Municipality: Cavan-Monaghan
Site #: 2305000002
Intersection: County Rd 10 & Syer Line
TFR File #: 1
Count date: 1-Mar-23

Weather conditions:

Person counted:
Person prepared:
Person checked:

**** Non-Signalized Intersection ****

Major Road: County Rd 10 runs N/S



Comments

Traffic Count Summary

Intersection: County Rd 10 & Syer Line					Count Date: 1-Mar-23		Municipality: Cavan-Monaghan					
North Approach Totals						North/South Total Approaches	South Approach Totals					
Hour Ending	Includes Cars, Trucks, & Heavys				Total Peds		Hour Ending	Includes Cars, Trucks, & Heavys				Total Peds
	Left	Thru	Right	Grand Total				Left	Thru	Right	Grand Total	
7:00:00	0	0	0	0	0	0	7:00:00	0	0	0	0	0
8:00:00	5	147	12	164	0	351	8:00:00	124	62	1	187	0
9:00:00	10	159	14	183	0	428	9:00:00	162	81	2	245	0
16:00:00	0	0	0	0	0	0	16:00:00	0	0	0	0	0
17:00:00	9	263	15	287	0	586	17:00:00	170	120	9	299	0
18:00:00	7	258	17	282	0	515	18:00:00	119	110	4	233	0
19:00:00	2	142	11	155	0	267	19:00:00	63	48	1	112	0

Appendix D – Synchro Analysis Output – Existing Traffic Volumes

Syer Line Industrial

HCM Unsignalized Intersection Capacity Analysis

1: County Road 10 & Syer Line/Highway 115 SB Ramp

Existing (2023) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	7	5	23	108	4	4	14	74	28	59	76	6
Future Volume (Veh/h)	7	5	23	108	4	4	14	74	28	59	76	6
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Hourly flow rate (vph)	7	5	24	115	4	4	15	79	30	63	81	6
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	340	349	84	358	337	94	87			109		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	340	349	84	358	337	94	87			109		
tC, single (s)	7.2	6.7	6.2	7.1	6.8	6.5	4.2			4.1		
tC, 2 stage (s)												
tF (s)	3.6	4.2	3.3	3.5	4.2	3.5	2.3			2.2		
p0 queue free %	99	99	98	79	99	100	99			96		
cM capacity (veh/h)	562	519	970	551	520	903	1472			1494		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1	SB 2							
Volume Total	36	123	124	63	87							
Volume Left	7	115	15	63	0							
Volume Right	24	4	30	0	6							
cSH	769	557	1472	1494	1700							
Volume to Capacity	0.05	0.22	0.01	0.04	0.05							
Queue Length 95th (m)	1.2	6.7	0.2	1.1	0.0							
Control Delay (s)	9.9	13.3	1.0	7.5	0.0							
Lane LOS	A	B	A	A								
Approach Delay (s)	9.9	13.3	1.0	3.2								
Approach LOS	A	B										
Intersection Summary												
Average Delay			6.0									
Intersection Capacity Utilization			33.9%			ICU Level of Service			A			
Analysis Period (min)			15									

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	24	1	4	2	1	6	177	86	1	9	183	14
Future Volume (Veh/h)	24	1	4	2	1	6	177	86	1	9	183	14
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	26	1	4	2	1	7	192	93	1	10	199	15
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	711	704	206	708	712	94	214			94		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	711	704	206	708	712	94	214			94		
tC, single (s)	7.3	6.5	6.5	7.6	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.7	4.0	3.5	4.0	4.0	3.3	2.2			2.2		
p0 queue free %	91	100	99	99	100	99	86			99		
cM capacity (veh/h)	285	310	779	259	307	969	1356			1513		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	SB 1							
Volume Total	31	10	192	94	224							
Volume Left	26	2	192	0	10							
Volume Right	4	7	0	1	15							
cSH	311	549	1356	1700	1513							
Volume to Capacity	0.10	0.02	0.14	0.06	0.01							
Queue Length 95th (m)	2.6	0.4	3.9	0.0	0.2							
Control Delay (s)	17.8	11.7	8.1	0.0	0.4							
Lane LOS	C	B	A		A							
Approach Delay (s)	17.8	11.7	5.4		0.4							
Approach LOS	C	B										
Intersection Summary												
Average Delay			4.2									
Intersection Capacity Utilization			37.8%			ICU Level of Service		A				
Analysis Period (min)			15									

Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp

HCM Unsignalized Intersection Capacity Analysis

Existing (2023) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	11	7	25	207	13	2	19	210	12	30	90	5
Future Volume (Veh/h)	11	7	25	207	13	2	19	210	12	30	90	5
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Hourly flow rate (vph)	11	7	26	213	13	2	20	216	12	31	93	5
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	428	426	96	446	422	222	98			228		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	428	426	96	446	422	222	98			228		
tC, single (s)	7.1	6.6	6.2	7.1	6.7	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.1	3.3	3.5	4.1	3.3	2.2			2.2		
p0 queue free %	98	99	97	57	97	100	99			98		
cM capacity (veh/h)	514	485	956	492	486	823	1476			1352		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1	SB 2							
Volume Total	44	228	248	31	98							
Volume Left	11	213	20	31	0							
Volume Right	26	2	12	0	5							
cSH	698	493	1476	1352	1700							
Volume to Capacity	0.06	0.46	0.01	0.02	0.06							
Queue Length 95th (m)	1.6	19.2	0.3	0.6	0.0							
Control Delay (s)	10.5	18.4	0.7	7.7	0.0							
Lane LOS	B	C	A	A								
Approach Delay (s)	10.5	18.4	0.7	1.9								
Approach LOS	B	C										
Intersection Summary												
Average Delay			7.8									
Intersection Capacity Utilization			47.3%			ICU Level of Service			A			
Analysis Period (min)			15									

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	96	2	26	6	7	9	188	136	10	11	292	19
Future Volume (Veh/h)	96	2	26	6	7	9	188	136	10	11	292	19
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	109	2	30	7	8	10	214	155	11	12	332	22
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	964	961	343	986	966	160	354			166		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	964	961	343	986	966	160	354			166		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	43	99	96	96	96	99	82			99		
cM capacity (veh/h)	193	211	704	187	209	890	1210			1424		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	SB 1							
Volume Total	141	25	214	166	366							
Volume Left	109	7	214	0	12							
Volume Right	30	10	0	11	22							
cSH	228	287	1210	1700	1424							
Volume to Capacity	0.62	0.09	0.18	0.10	0.01							
Queue Length 95th (m)	29.0	2.3	5.1	0.0	0.2							
Control Delay (s)	43.2	18.7	8.6	0.0	0.3							
Lane LOS	E	C	A		A							
Approach Delay (s)	43.2	18.7	4.9		0.3							
Approach LOS	E	C										
Intersection Summary												
Average Delay			9.3									
Intersection Capacity Utilization			54.2%			ICU Level of Service			A			
Analysis Period (min)			15									

Appendix E – Synchro Analysis Output – Background Traffic Volumes


												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	8	6	25	335	4	4	15	100	45	66	96	7
Future Volume (Veh/h)	8	6	25	335	4	4	15	100	45	66	96	7
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Hourly flow rate (vph)	9	6	27	356	4	4	16	106	48	70	102	7
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	414	432	106	434	411	130	109			154		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	414	432	106	434	411	130	109			154		
tC, single (s)	7.2	6.7	6.2	7.1	6.8	6.5	4.2			4.1		
tC, 2 stage (s)												
tF (s)	3.6	4.2	3.3	3.5	4.2	3.5	2.3			2.2		
p0 queue free %	98	99	97	26	99	100	99			95		
cM capacity (veh/h)	499	461	943	484	468	862	1445			1439		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1	SB 2							
Volume Total	42	364	170	70	109							
Volume Left	9	356	16	70	0							
Volume Right	27	4	48	0	7							
cSH	704	486	1445	1439	1700							
Volume to Capacity	0.06	0.75	0.01	0.05	0.06							
Queue Length 95th (m)	1.5	50.6	0.3	1.2	0.0							
Control Delay (s)	10.4	31.3	0.8	7.6	0.0							
Lane LOS	B	D	A	A								
Approach Delay (s)	10.4	31.3	0.8	3.0								
Approach LOS	B	D										
Intersection Summary												
Average Delay			16.6									
Intersection Capacity Utilization			52.8%			ICU Level of Service			A			
Analysis Period (min)			15									

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	27	1	11	2	1	7	586	127	1	10	428	16
Future Volume (Veh/h)	27	1	11	2	1	7	586	127	1	10	428	16
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	29	1	12	2	1	8	637	138	1	11	465	17
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	1916	1908	474	1920	1916	138	482			139		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	1916	1908	474	1920	1916	138	482			139		
tC, single (s)	7.3	6.5	6.5	7.6	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.7	4.0	3.5	4.0	4.0	3.3	2.2			2.2		
p0 queue free %	0	96	98	90	96	99	41			99		
cM capacity (veh/h)	23	28	546	19	28	915	1081			1457		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	SB 1							
Volume Total	42	11	637	139	493							
Volume Left	29	2	637	0	11							
Volume Right	12	8	0	1	17							
cSH	32	74	1081	1700	1457							
Volume to Capacity	1.30	0.15	0.59	0.08	0.01							
Queue Length 95th (m)	37.0	4.0	32.1	0.0	0.2							
Control Delay (s)	449.9	62.2	13.0	0.0	0.2							
Lane LOS	F	F	B		A							
Approach Delay (s)	449.9	62.2	10.7		0.2							
Approach LOS	F	F										
Intersection Summary												
Average Delay			21.2									
Intersection Capacity Utilization			78.0%			ICU Level of Service			D			
Analysis Period (min)			15									

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	12	8	28	638	15	2	21	246	23	34	118	6
Future Volume (Veh/h)	12	8	28	638	15	2	21	246	23	34	118	6
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Hourly flow rate (vph)	12	8	29	658	15	2	22	254	24	35	122	6
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	514	517	125	535	508	266	128			278		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	514	517	125	535	508	266	128			278		
tC, single (s)	7.1	6.6	6.2	7.1	6.7	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.1	3.3	3.5	4.1	3.3	2.2			2.2		
p0 queue free %	97	98	97	0	97	100	98			97		
cM capacity (veh/h)	445	427	920	424	431	778	1440			1296		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1	SB 2							
Volume Total	49	675	300	35	128							
Volume Left	12	658	22	35	0							
Volume Right	29	2	24	0	6							
cSH	635	425	1440	1296	1700							
Volume to Capacity	0.08	1.59	0.02	0.03	0.08							
Queue Length 95th (m)	2.0	303.3	0.4	0.7	0.0							
Control Delay (s)	11.1	299.1	0.7	7.9	0.0							
Lane LOS	B	F	A	A								
Approach Delay (s)	11.1	299.1	0.7	1.7								
Approach LOS	B	F										
Intersection Summary												
Average Delay			170.9									
Intersection Capacity Utilization			80.0%			ICU Level of Service				D		
Analysis Period (min)			15									

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	107	2	44	7	8	10	505	174	11	12	747	21
Future Volume (Veh/h)	107	2	44	7	8	10	505	174	11	12	747	21
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	122	2	50	8	9	11	574	198	12	14	849	24
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type								None			None	
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	2250	2247	861	2292	2253	204	873			210		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	2250	2247	861	2292	2253	204	873			210		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	0	82	86	4	17	99	26			99		
cM capacity (veh/h)	4	11	358	8	11	842	777			1373		
Direction, Lane #	EB 1	WB 1	NB 1	NB 2	SB 1							
Volume Total	174	28	574	210	887							
Volume Left	122	8	574	0	14							
Volume Right	50	11	0	12	24							
cSH	6	16	777	1700	1373							
Volume to Capacity	30.34	1.80	0.74	0.12	0.01							
Queue Length 95th (m)	Err	32.9	53.7	0.0	0.2							
Control Delay (s)	Err	884.8	21.5	0.0	0.3							
Lane LOS	F	F	C		A							
Approach Delay (s)	Err	884.8	15.8		0.3							
Approach LOS	F	F										
Intersection Summary												
Average Delay			948.9									
Intersection Capacity Utilization			101.3%			ICU Level of Service				G		
Analysis Period (min)			15									

1: County Road 10 & Syer Line/Highway 115 SB Ramp Background (2028) AM Peak w/ Improvements



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↕		↕		↕	↕	↕
Traffic Volume (vph)	8	6	335	4	15	100	66	96
Future Volume (vph)	8	6	335	4	15	100	66	96
Lane Group Flow (vph)	0	42	0	364	0	170	70	109
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	64.0	64.0	64.0	64.0	46.0	46.0	46.0	46.0
Total Split (%)	58.2%	58.2%	58.2%	58.2%	41.8%	41.8%	41.8%	41.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9		5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.06		0.59		0.30	0.18	0.17
Control Delay		6.5		22.7		23.4	25.1	23.6
Queue Delay		0.0		0.0		0.0	0.0	0.0
Total Delay		6.5		22.7		23.4	25.1	23.6
Queue Length 50th (m)		1.5		53.8		23.6	10.6	15.8
Queue Length 95th (m)		6.9		86.2		41.4	21.6	28.8
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)							82.0	
Base Capacity (vph)		748		614		571	399	632
Starvation Cap Reductn		0		0		0	0	0
Spillback Cap Reductn		0		0		0	0	0
Storage Cap Reductn		0		0		0	0	0
Reduced v/c Ratio		0.06		0.59		0.30	0.18	0.17

Intersection Summary

Cycle Length: 110


Actuated Cycle Length: 110

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 65


Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	8	6	25	335	4	4	15	100	45	66	96	7
Future Volume (vph)	8	6	25	335	4	4	15	100	45	66	96	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9			5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00			1.00			1.00		1.00	1.00	
Frt		0.91			1.00			0.96		1.00	0.99	
Flt Protected		0.99			0.95			1.00		0.95	1.00	
Satd. Flow (prot)		1458			1580			1557		1662	1717	
Flt Permitted		0.93			0.70			0.97		0.62	1.00	
Satd. Flow (perm)		1369			1160			1521		1087	1717	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	9	6	27	356	4	4	16	106	48	70	102	7
RTOR Reduction (vph)	0	12	0	0	0	0	0	13	0	0	3	0
Lane Group Flow (vph)	0	30	0	0	364	0	0	157	0	70	106	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		59.1			58.2			40.4		40.4	40.4	
Effective Green, g (s)		59.1			58.2			40.4		40.4	40.4	
Actuated g/C Ratio		0.54			0.53			0.37		0.37	0.37	
Clearance Time (s)		4.9			5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0			3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		735			613			558		399	630	
v/s Ratio Prot											0.06	
v/s Ratio Perm		0.02			0.31			0.10		0.06		
v/c Ratio		0.04			0.59			0.28		0.18	0.17	
Uniform Delay, d1		12.0			17.8			24.6		23.5	23.5	
Progression Factor		1.00			1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1			4.2			1.3		1.0	0.6	
Delay (s)		12.1			22.0			25.8		24.5	24.1	
Level of Service		B			C			C		C	C	
Approach Delay (s)		12.1			22.0			25.8			24.2	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay		22.8			HCM 2000 Level of Service			C				
HCM 2000 Volume to Capacity ratio		0.47										
Actuated Cycle Length (s)		110.0			Sum of lost time (s)			11.4				
Intersection Capacity Utilization		61.6%			ICU Level of Service			B				
Analysis Period (min)		15										
c Critical Lane Group												

2: Highway 115 NB Ramp/Syer Line & County Road 10 Background (2028) AM Peak w/ Improvements



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔	↔	↔		↔
Traffic Volume (vph)	27	1	2	1	586	127	10	428
Future Volume (vph)	27	1	2	1	586	127	10	428
Lane Group Flow (vph)	0	42	0	11	637	139	0	493
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.0	86.4	44.4	44.4
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.0%	72.0%	37.0%	37.0%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)		5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio		0.33		0.07	0.74	0.10		0.54
Control Delay		40.2		27.9	9.6	2.3		24.0
Queue Delay		0.0		0.0	0.0	0.0		0.0
Total Delay		40.2		27.9	9.6	2.3		24.0
Queue Length 50th (m)		5.9		0.6	29.8	5.2		79.6
Queue Length 95th (m)		17.3		6.1	73.2	10.3		133.6
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)		324		395	980	1437		905
Starvation Cap Reductn		0		0	0	0		0
Spillback Cap Reductn		0		0	0	0		0
Storage Cap Reductn		0		0	0	0		0
Reduced v/c Ratio		0.13		0.03	0.65	0.10		0.54

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 96.3

Natural Cycle: 100


Control Type: Semi Act-Uncoord

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	27	1	11	2	1	7	586	127	1	10	428	16
Future Volume (vph)	27	1	11	2	1	7	586	127	1	10	428	16
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor		1.00			1.00		1.00	1.00			1.00	
Frt		0.96			0.90		1.00	1.00			1.00	
Flt Protected		0.97			0.99		0.95	1.00			1.00	
Satd. Flow (prot)		1337			1434		1630	1650			1720	
Flt Permitted		0.79			0.93		0.40	1.00			0.99	
Satd. Flow (perm)		1089			1340		681	1650			1711	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	29	1	12	2	1	8	637	138	1	11	465	17
RTOR Reduction (vph)	0	11	0	0	8	0	0	0	0	0	1	0
Lane Group Flow (vph)	0	31	0	0	3	0	637	139	0	0	492	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		6.0			6.0		81.4	81.4			50.9	
Effective Green, g (s)		6.0			6.0		81.4	81.4			50.9	
Actuated g/C Ratio		0.06			0.06		0.82	0.82			0.52	
Clearance Time (s)		5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)		3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)		66			81		825	1359			881	
v/s Ratio Prot							c0.21	0.08				
v/s Ratio Perm		c0.03			0.00		c0.42				0.29	
v/c Ratio		0.47			0.04		0.77	0.10			0.56	
Uniform Delay, d1		44.9			43.7		5.8	1.7			16.3	
Progression Factor		1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2		5.1			0.2		4.5	0.2			2.6	
Delay (s)		50.0			43.9		10.3	1.8			18.9	
Level of Service		D			D		B	A			B	
Approach Delay (s)		50.0			43.9			8.8			18.9	
Approach LOS		D			D			A			B	
Intersection Summary												
HCM 2000 Control Delay		14.1			HCM 2000 Level of Service			B				
HCM 2000 Volume to Capacity ratio		0.77										
Actuated Cycle Length (s)		98.8			Sum of lost time (s)			14.4				
Intersection Capacity Utilization		83.9%			ICU Level of Service			E				
Analysis Period (min)		15										
c Critical Lane Group												

1: County Road 10 & Syer Line/Highway 115 SB Ramp Background (2028) PM Peak w/ Improvements



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↔	↔	↔
Traffic Volume (vph)	12	8	638	15	21	246	34	118
Future Volume (vph)	12	8	638	15	21	246	34	118
Lane Group Flow (vph)	0	49	0	675	0	300	35	128
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	101.0	101.0	101.0	101.0	39.0	39.0	39.0	39.0
Total Split (%)	72.1%	72.1%	72.1%	72.1%	27.9%	27.9%	27.9%	27.9%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9		5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.05		0.82		0.76	0.25	0.32
Control Delay		3.8		26.5		62.7	48.8	45.8
Queue Delay		0.0		0.0		0.0	0.0	0.0
Total Delay		3.8		26.5		62.7	48.8	45.8
Queue Length 50th (m)		1.7		131.5		81.2	8.3	30.5
Queue Length 95th (m)		5.9		205.5		#119.2	19.5	50.2
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)							82.0	
Base Capacity (vph)		919		824		395	141	404
Starvation Cap Reductn		0		0		0	0	0
Spillback Cap Reductn		0		0		0	0	0
Storage Cap Reductn		0		0		0	0	0
Reduced v/c Ratio		0.05		0.82		0.76	0.25	0.32

Intersection Summary

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green


Natural Cycle: 90

Control Type: Actuated-Coordinated

95th percentile volume exceeds capacity, queue may be longer.


Queue shown is maximum after two cycles.

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	12	8	28	638	15	2	21	246	23	34	118	6
Future Volume (vph)	12	8	28	638	15	2	21	246	23	34	118	6
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9			5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00			1.00			1.00		1.00	1.00	
Frt		0.92			1.00			0.99		1.00	0.99	
Flt Protected		0.99			0.95			1.00		0.95	1.00	
Satd. Flow (prot)		1520			1662			1690		1662	1689	
Flt Permitted		0.86			0.70			0.97		0.34	1.00	
Satd. Flow (perm)		1326			1213			1647		592	1689	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	12	8	29	658	15	2	22	254	24	35	122	6
RTOR Reduction (vph)	0	9	0	0	0	0	0	2	0	0	2	0
Lane Group Flow (vph)	0	40	0	0	675	0	0	298	0	35	126	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		96.1			95.2			33.4		33.4	33.4	
Effective Green, g (s)		96.1			95.2			33.4		33.4	33.4	
Actuated g/C Ratio		0.69			0.68			0.24		0.24	0.24	
Clearance Time (s)		4.9			5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0			3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		910			824			392		141	402	
v/s Ratio Prot											0.07	
v/s Ratio Perm		0.03			c0.56			c0.18		0.06		
v/c Ratio		0.04			0.82			0.76		0.25	0.31	
Uniform Delay, d1		7.1			16.2			49.6		43.1	43.9	
Progression Factor		1.00			1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1			8.9			12.9		4.2	2.0	
Delay (s)		7.2			25.1			62.5		47.3	45.9	
Level of Service		A			C			E		D	D	
Approach Delay (s)		7.2			25.1			62.5			46.2	
Approach LOS		A			C			E			D	
Intersection Summary												
HCM 2000 Control Delay		36.7						HCM 2000 Level of Service		D		
HCM 2000 Volume to Capacity ratio		0.80										
Actuated Cycle Length (s)		140.0						Sum of lost time (s)		11.4		
Intersection Capacity Utilization		90.1%						ICU Level of Service		E		
Analysis Period (min)		15										
c Critical Lane Group												

2: Highway 115 NB Ramp/Syer Line & County Road 10 Background (2028) PM Peak w/ Improvements



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔	↔	↔		↔
Traffic Volume (vph)	107	2	7	8	505	174	12	747
Future Volume (vph)	107	2	7	8	505	174	12	747
Lane Group Flow (vph)	0	174	0	28	574	211	0	887
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	31.0	106.4	75.4	75.4
Total Split (%)	24.0%	24.0%	24.0%	24.0%	22.1%	76.0%	53.9%	53.9%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)		5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio		0.81		0.11	1.01	0.16		0.99
Control Delay		78.0		33.4	60.8	5.3		59.9
Queue Delay		0.0		0.0	0.0	0.0		0.0
Total Delay		78.0		33.4	60.8	5.3		59.9
Queue Length 50th (m)		43.8		4.1	~98.4	14.3		239.3
Queue Length 95th (m)		69.4		12.7	#182.3	25.4		#346.7
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)		275		326	569	1299		897
Starvation Cap Reductn		0		0	0	0		0
Spillback Cap Reductn		0		0	0	0		0
Storage Cap Reductn		0		0	0	0		0
Reduced v/c Ratio		0.63		0.09	1.01	0.16		0.99

Intersection Summary

Cycle Length: 140

Actuated Cycle Length: 133.7

Natural Cycle: 150

Control Type: Semi Act-Uncoord


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.


Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	107	2	44	7	8	10	505	174	11	12	747	21
Future Volume (vph)	107	2	44	7	8	10	505	174	11	12	747	21
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor		1.00			1.00		1.00	1.00			1.00	
Frt		0.96			0.95		1.00	0.99			1.00	
Flt Protected		0.97			0.99		0.95	1.00			1.00	
Satd. Flow (prot)		1592			1634		1646	1718			1723	
Flt Permitted		0.77			0.92		0.23	1.00			0.99	
Satd. Flow (perm)		1275			1525		397	1718			1715	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	122	2	50	8	9	11	574	198	12	14	849	24
RTOR Reduction (vph)	0	11	0	0	9	0	0	1	0	0	0	0
Lane Group Flow (vph)	0	163	0	0	19	0	574	210	0	0	887	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		21.3			21.3		101.0	101.0			70.0	
Effective Green, g (s)		21.3			21.3		101.0	101.0			70.0	
Actuated g/C Ratio		0.16			0.16		0.76	0.76			0.52	
Clearance Time (s)		5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)		3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)		203			242		561	1297			897	
v/s Ratio Prot							c0.21	0.12				
v/s Ratio Perm		c0.13			0.01		c0.56				0.52	
v/c Ratio		0.80			0.08		1.02	0.16			0.99	
Uniform Delay, d1		54.2			47.8		26.4	4.6			31.4	
Progression Factor		1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2		20.1			0.1		44.0	0.3			27.4	
Delay (s)		74.3			48.0		70.4	4.8			58.8	
Level of Service		E			D		E	A			E	
Approach Delay (s)		74.3			48.0			52.8			58.8	
Approach LOS		E			D			D			E	
Intersection Summary												
HCM 2000 Control Delay		57.6					HCM 2000 Level of Service		E			
HCM 2000 Volume to Capacity ratio		1.01										
Actuated Cycle Length (s)		133.7					Sum of lost time (s)		14.4			
Intersection Capacity Utilization		105.5%					ICU Level of Service		G			
Analysis Period (min)		15										
c Critical Lane Group												

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Background (2033) AM Peak Hour




Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↔	↔	↔
Traffic Volume (vph)	9	6	359	5	17	112	74	106
Future Volume (vph)	9	6	359	5	17	112	74	106
Lane Group Flow (vph)	0	46	0	398	0	191	79	120
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	64.0	64.0	64.0	64.0	46.0	46.0	46.0	46.0
Total Split (%)	58.2%	58.2%	58.2%	58.2%	41.8%	41.8%	41.8%	41.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9		5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.06		0.65		0.34	0.21	0.19
Control Delay		6.3		24.7		24.4	25.7	24.1
Queue Delay		0.0		0.0		0.0	0.0	0.0
Total Delay		6.3		24.7		24.4	25.7	24.1
Queue Length 50th (m)		1.6		61.5		27.3	12.1	17.8
Queue Length 95th (m)		7.3		98.3		46.7	24.2	31.6
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)							82.0	
Base Capacity (vph)		743		612		570	383	632
Starvation Cap Reductn		0		0		0	0	0
Spillback Cap Reductn		0		0		0	0	0
Storage Cap Reductn		0		0		0	0	0
Reduced v/c Ratio		0.06		0.65		0.34	0.21	0.19

Intersection Summary

Cycle Length: 110
Actuated Cycle Length: 110
Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green
Natural Cycle: 65
Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Background (2033) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	9	6	28	359	5	10	17	112	51	74	106	7
Future Volume (vph)	9	6	28	359	5	10	17	112	51	74	106	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9			5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00			1.00			1.00		1.00	1.00	
Frt		0.91			1.00			0.96		1.00	0.99	
Flt Protected		0.99			0.95			1.00		0.95	1.00	
Satd. Flow (prot)		1458			1572			1557		1662	1719	
Flt Permitted		0.92			0.70			0.97		0.60	1.00	
Satd. Flow (perm)		1357			1155			1518		1043	1719	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	10	6	30	382	5	11	18	119	54	79	113	7
RTOR Reduction (vph)	0	14	0	0	1	0	0	13	0	0	2	0
Lane Group Flow (vph)	0	32	0	0	397	0	0	178	0	79	118	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		59.1			58.2			40.4		40.4	40.4	
Effective Green, g (s)		59.1			58.2			40.4		40.4	40.4	
Actuated g/C Ratio		0.54			0.53			0.37		0.37	0.37	
Clearance Time (s)		4.9			5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0			3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		729			611			557		383	631	
v/s Ratio Prot											0.07	
v/s Ratio Perm		0.02			0.34			0.12		0.08		
v/c Ratio		0.04			0.65			0.32		0.21	0.19	
Uniform Delay, d1		12.1			18.6			25.0		23.8	23.6	
Progression Factor		1.00			1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1			5.3			1.5		1.2	0.7	
Delay (s)		12.2			23.9			26.5		25.0	24.3	
Level of Service		B			C			C		C	C	
Approach Delay (s)		12.2			23.9			26.5			24.6	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay			24.0									
HCM 2000 Volume to Capacity ratio			0.51									
Actuated Cycle Length (s)			110.0									
Intersection Capacity Utilization			66.3%									
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Background (2033) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔	↔	↔		↔
Traffic Volume (vph)	31	1	2	1	644	142	11	459
Future Volume (vph)	31	1	2	1	644	142	11	459
Lane Group Flow (vph)	0	49	0	11	700	155	0	532
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.0	86.4	44.4	44.4
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.0%	72.0%	37.0%	37.0%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)		5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio		0.38		0.07	0.81	0.11		0.80
Control Delay		42.1		27.3	20.0	2.8		38.5
Queue Delay		0.0		0.0	0.0	0.0		0.0
Total Delay		42.1		27.3	20.0	2.8		38.5
Queue Length 50th (m)		7.0		0.6	69.9	5.8		98.1
Queue Length 95th (m)		18.9		6.1	#154.7	12.0		#164.0
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)		314		385	864	1365		669
Starvation Cap Reductn		0		0	0	0		0
Spillback Cap Reductn		0		0	0	0		0
Storage Cap Reductn		0		0	0	0		0
Reduced v/c Ratio		0.16		0.03	0.81	0.11		0.80

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 99.7

Natural Cycle: 120

Control Type: Semi Act-Uncoord

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.


Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	31	1	13	2	1	7	644	142	1	11	459	19
Future Volume (vph)	31	1	13	2	1	7	644	142	1	11	459	19
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor		1.00			1.00		1.00	1.00			1.00	
Frt		0.96			0.90		1.00	1.00			0.99	
Flt Protected		0.97			0.99		0.95	1.00			1.00	
Satd. Flow (prot)		1336			1434		1630	1650			1718	
Flt Permitted		0.79			0.94		0.29	1.00			0.99	
Satd. Flow (perm)		1087			1357		500	1650			1708	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	34	1	14	2	1	8	700	154	1	12	499	21
RTOR Reduction (vph)	0	13	0	0	7	0	0	0	0	0	1	0
Lane Group Flow (vph)	0	36	0	0	4	0	700	155	0	0	531	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		8.4			8.4		81.2	81.2			39.0	
Effective Green, g (s)		8.4			8.4		81.2	81.2			39.0	
Actuated g/C Ratio		0.08			0.08		0.80	0.80			0.39	
Clearance Time (s)		5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)		3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)		90			112		840	1326			659	
v/s Ratio Prot							0.32	0.09				
v/s Ratio Perm		0.03			0.00		0.35				0.31	
v/c Ratio		0.40			0.03		0.83	0.12			0.81	
Uniform Delay, d1		43.9			42.6		13.6	2.1			27.6	
Progression Factor		1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2		2.9			0.1		7.1	0.2			10.1	
Delay (s)		46.8			42.7		20.7	2.3			37.8	
Level of Service		D			D		C	A			D	
Approach Delay (s)		46.8			42.7			17.4			37.8	
Approach LOS		D			D			B			D	
Intersection Summary												
HCM 2000 Control Delay		26.1			HCM 2000 Level of Service			C				
HCM 2000 Volume to Capacity ratio		0.82										
Actuated Cycle Length (s)		101.0			Sum of lost time (s)			14.4				
Intersection Capacity Utilization		89.4%			ICU Level of Service			E				
Analysis Period (min)		15										
c Critical Lane Group												

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Background (2033) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↔	↔	↔
Traffic Volume (vph)	13	9	698	16	23	271	39	136
Future Volume (vph)	13	9	698	16	23	271	39	136
Lane Group Flow (vph)	0	53	0	740	0	329	40	146
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	101.0	101.0	101.0	101.0	39.0	39.0	39.0	39.0
Total Split (%)	72.1%	72.1%	72.1%	72.1%	27.9%	27.9%	27.9%	27.9%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9		5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.06		0.90		0.84	0.32	0.36
Control Delay		3.8		34.9		69.2	52.3	47.2
Queue Delay		0.0		0.0		0.0	0.0	0.0
Total Delay		3.8		34.9		69.2	52.3	47.2
Queue Length 50th (m)		1.9		164.9		91.1	9.7	35.5
Queue Length 95th (m)		6.4		#277.7		#141.7	22.3	56.9
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)							82.0	
Base Capacity (vph)		904		821		394	126	404
Starvation Cap Reductn		0		0		0	0	0
Spillback Cap Reductn		0		0		0	0	0
Storage Cap Reductn		0		0		0	0	0
Reduced v/c Ratio		0.06		0.90		0.84	0.32	0.36

Intersection Summary

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green


Natural Cycle: 90

Control Type: Actuated-Coordinated

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Background (2033) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	13	9	30	698	16	4	23	271	25	39	136	6
Future Volume (vph)	13	9	30	698	16	4	23	271	25	39	136	6
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9			5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00			1.00			1.00		1.00	1.00	
Frt		0.92			1.00			0.99		1.00	0.99	
Flt Protected		0.99			0.95			1.00		0.95	1.00	
Satd. Flow (prot)		1521			1662			1690		1662	1691	
Flt Permitted		0.85			0.69			0.97		0.30	1.00	
Satd. Flow (perm)		1304			1208			1644		533	1691	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	13	9	31	720	16	4	24	279	26	40	140	6
RTOR Reduction (vph)	0	10	0	0	0	0	0	2	0	0	1	0
Lane Group Flow (vph)	0	43	0	0	740	0	0	327	0	40	145	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		96.1			95.2			33.4		33.4	33.4	
Effective Green, g (s)		96.1			95.2			33.4		33.4	33.4	
Actuated g/C Ratio		0.69			0.68			0.24		0.24	0.24	
Clearance Time (s)		4.9			5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0			3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		895			821			392		127	403	
v/s Ratio Prot											0.09	
v/s Ratio Perm		0.03			c0.61			c0.20		0.08		
v/c Ratio		0.05			0.90			0.83		0.31	0.36	
Uniform Delay, d1		7.1			18.5			50.7		43.9	44.4	
Progression Factor		1.00			1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1			15.0			18.4		6.4	2.5	
Delay (s)		7.2			33.5			69.1		50.3	46.9	
Level of Service		A			C			E		D	D	
Approach Delay (s)		7.2			33.5			69.1			47.6	
Approach LOS		A			C			E			D	
Intersection Summary												
HCM 2000 Control Delay		43.4			HCM 2000 Level of Service			D				
HCM 2000 Volume to Capacity ratio		0.88										
Actuated Cycle Length (s)		140.0			Sum of lost time (s)			11.4				
Intersection Capacity Utilization		97.3%			ICU Level of Service			F				
Analysis Period (min)		15										
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Background (2033) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔	↔	↔		↔
Traffic Volume (vph)	120	3	7	9	544	191	13	817
Future Volume (vph)	120	3	7	9	544	191	13	817
Lane Group Flow (vph)	0	195	0	31	618	231	0	975
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	31.0	106.4	75.4	75.4
Total Split (%)	24.0%	24.0%	24.0%	24.0%	22.1%	76.0%	53.9%	53.9%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)		5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio		0.85		0.11	1.16	0.18		1.10
Control Delay		81.4		32.1	116.7	5.9		95.2
Queue Delay		0.0		0.0	0.0	0.0		0.0
Total Delay		81.4		32.1	116.7	5.9		95.2
Queue Length 50th (m)		50.5		4.3	~155.0	17.8		~322.3
Queue Length 95th (m)		#83.0		13.5	#227.3	27.9		#400.5
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)		271		323	532	1279		883
Starvation Cap Reductn		0		0	0	0		0
Spillback Cap Reductn		0		0	0	0		0
Storage Cap Reductn		0		0	0	0		0
Reduced v/c Ratio		0.72		0.10	1.16	0.18		1.10

Intersection Summary

Cycle Length: 140

Actuated Cycle Length: 135.7

Natural Cycle: 150

Control Type: Semi Act-Uncoord


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.


95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	120	3	49	7	9	11	544	191	12	13	817	28
Future Volume (vph)	120	3	49	7	9	11	544	191	12	13	817	28
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor		1.00			1.00		1.00	1.00			1.00	
Frt		0.96			0.94		1.00	0.99			1.00	
Flt Protected		0.97			0.99		0.95	1.00			1.00	
Satd. Flow (prot)		1592			1630		1646	1718			1722	
Flt Permitted		0.77			0.93		0.20	1.00			0.99	
Satd. Flow (perm)		1273			1528		345	1718			1713	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	136	3	56	8	10	12	618	217	14	15	928	32
RTOR Reduction (vph)	0	11	0	0	11	0	0	2	0	0	1	0
Lane Group Flow (vph)	0	184	0	0	20	0	618	229	0	0	974	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		23.3			23.3		100.9	100.9			69.9	
Effective Green, g (s)		23.3			23.3		100.9	100.9			69.9	
Actuated g/C Ratio		0.17			0.17		0.74	0.74			0.52	
Clearance Time (s)		5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)		3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)		218			262		525	1278			883	
v/s Ratio Prot							c0.24	0.13				
v/s Ratio Perm		c0.14			0.01		c0.63				0.57	
v/c Ratio		0.85			0.08		1.18	0.18			1.10	
Uniform Delay, d1		54.4			47.1		29.5	5.1			32.8	
Progression Factor		1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2		24.7			0.1		98.2	0.3			62.6	
Delay (s)		79.1			47.3		127.7	5.4			95.4	
Level of Service		E			D		F	A			F	
Approach Delay (s)		79.1			47.3			94.5			95.4	
Approach LOS		E			D			F			F	
Intersection Summary												
HCM 2000 Control Delay		92.7			HCM 2000 Level of Service			F				
HCM 2000 Volume to Capacity ratio		1.14										
Actuated Cycle Length (s)		135.6			Sum of lost time (s)			14.4				
Intersection Capacity Utilization		113.5%			ICU Level of Service			H				
Analysis Period (min)		15										
c Critical Lane Group												



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↗	↖		↕	↗	↖
Traffic Volume (vph)	9	6	359	5	17	112	74	106
Future Volume (vph)	9	6	359	5	17	112	74	106
Lane Group Flow (vph)	0	46	382	16	0	191	79	120
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	65.0	65.0	65.0	65.0	55.0	55.0	55.0	55.0
Total Split (%)	54.2%	54.2%	54.2%	54.2%	45.8%	45.8%	45.8%	45.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	5.8	5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.06	0.64	0.03		0.30	0.18	0.17
Control Delay		7.9	28.6	9.5		22.6	23.9	22.6
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		7.9	28.6	9.5		22.6	23.9	22.6
Queue Length 50th (m)		1.9	68.0	0.6		27.8	12.3	18.0
Queue Length 95th (m)		8.3	104.4	4.5		46.3	23.8	31.4
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		728	597	625		637	435	709
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.06	0.64	0.03		0.30	0.18	0.17

Intersection Summary

Cycle Length: 120


Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 65

Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Background (2033) AM Peak w/ Improvements

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	9	6	28	359	5	10	17	112	51	74	106	7
Future Volume (vph)	9	6	28	359	5	10	17	112	51	74	106	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.91		1.00	0.90			0.96		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1458		1583	1256			1557		1662	1719	
Flt Permitted		0.97		0.73	1.00			0.97		0.61	1.00	
Satd. Flow (perm)		1423		1212	1256			1519		1059	1719	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	10	6	30	382	5	11	18	119	54	79	113	7
RTOR Reduction (vph)	0	15	0	0	6	0	0	12	0	0	2	0
Lane Group Flow (vph)	0	31	0	382	10	0	0	179	0	79	118	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Effective Green, g (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Actuated g/C Ratio		0.50		0.49	0.49			0.41		0.41	0.41	
Clearance Time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		712		597	619			625		435	707	
v/s Ratio Prot					0.01						0.07	
v/s Ratio Perm		0.02		c0.32				c0.12		0.07		
v/c Ratio		0.04		0.64	0.02			0.29		0.18	0.17	
Uniform Delay, d1		15.3		22.5	15.5			23.5		22.4	22.3	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1		5.2	0.0			1.2		0.9	0.5	
Delay (s)		15.4		27.7	15.6			24.7		23.4	22.8	
Level of Service		B		C	B			C		C	C	
Approach Delay (s)		15.4			27.2			24.7			23.0	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay			25.0			HCM 2000 Level of Service				C		
HCM 2000 Volume to Capacity ratio			0.48									
Actuated Cycle Length (s)			120.0			Sum of lost time (s)			11.4			
Intersection Capacity Utilization			65.4%			ICU Level of Service			C			
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Background (2033) AM Peak w/ Improvements




Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	31	1	2	1	644	142	11	459
Future Volume (vph)	31	1	2	1	644	142	11	459
Lane Group Flow (vph)	34	15	0	11	700	155	0	532
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	51.2	86.4	35.2	35.2
Total Split (%)	28.0%	28.0%	28.0%	28.0%	42.7%	72.0%	29.3%	29.3%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.29	0.10		0.07	0.79	0.11		0.34
Control Delay	48.8	22.3		27.8	12.2	2.3		21.1
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	48.8	22.3		27.8	12.2	2.3		21.1
Queue Length 50th (m)	6.7	0.2		0.6	39.4	5.8		39.3
Queue Length 95th (m)	16.8	6.5		6.1	92.3	11.6		69.8
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	315	364		397	1070	1436		1558
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.11	0.04		0.03	0.65	0.11		0.34


Intersection Summary

Cycle Length: 120
Actuated Cycle Length: 96.4
Natural Cycle: 100
Control Type: Semi Act-Uncoord

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	31	1	13	2	1	7	644	142	1	11	459	19
Future Volume (vph)	31	1	13	2	1	7	644	142	1	11	459	19
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.86			0.90		1.00	1.00			0.99	
Flt Protected	0.95	1.00			0.99		0.95	1.00			1.00	
Satd. Flow (prot)	1374	1220			1434		1630	1650			3262	
Flt Permitted	0.75	1.00			0.93		0.40	1.00			0.95	
Satd. Flow (perm)	1085	1220			1349		678	1650			3098	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	34	1	14	2	1	8	700	154	1	12	499	21
RTOR Reduction (vph)	0	13	0	0	8	0	0	0	0	0	2	0
Lane Group Flow (vph)	34	2	0	0	3	0	700	155	0	0	530	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	6.1	6.1			6.1		81.4	81.4			48.5	
Effective Green, g (s)	6.1	6.1			6.1		81.4	81.4			48.5	
Actuated g/C Ratio	0.06	0.06			0.06		0.82	0.82			0.49	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	66	75			83		845	1358			1519	
v/s Ratio Prot		0.00					0.25	0.09				
v/s Ratio Perm	0.03				0.00		0.43				0.17	
v/c Ratio	0.52	0.02			0.04		0.83	0.11			0.35	
Uniform Delay, d1	45.0	43.6			43.7		5.3	1.7			15.5	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	6.6	0.1			0.2		6.7	0.2			0.6	
Delay (s)	51.6	43.7			43.9		12.1	1.9			16.1	
Level of Service	D	D			D		B	A			B	
Approach Delay (s)		49.2			43.9			10.2			16.1	
Approach LOS		D			D			B			B	
Intersection Summary												
HCM 2000 Control Delay			14.0				HCM 2000 Level of Service			B		
HCM 2000 Volume to Capacity ratio			0.83									
Actuated Cycle Length (s)			98.9				Sum of lost time (s)		14.4			
Intersection Capacity Utilization			77.9%				ICU Level of Service		D			
Analysis Period (min)			15									
c Critical Lane Group												



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↔	↔		↔	↔	↔
Traffic Volume (vph)	13	9	698	16	23	271	39	136
Future Volume (vph)	13	9	698	16	23	271	39	136
Lane Group Flow (vph)	0	53	720	20	0	329	40	146
Turn Type	Perm	NA	pm+pt	NA	Perm	NA	Perm	NA
Protected Phases		4	3	8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	3	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	5.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	9.5	39.2	25.6	25.6	25.6	25.6
Total Split (s)	39.2	39.2	40.8	80.0	40.0	40.0	40.0	40.0
Total Split (%)	32.7%	32.7%	34.0%	66.7%	33.3%	33.3%	33.3%	33.3%
Yellow Time (s)	3.3	3.3	3.0	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	0.0	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	3.0	5.8		5.6	5.6	5.6
Lead/Lag	Lag	Lag	Lead					
Lead-Lag Optimize?	Yes	Yes	Yes					
Recall Mode	Max	Max	None	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.11	0.78	0.02		0.69	0.21	0.30
Control Delay		17.1	20.9	7.7		46.5	36.2	35.0
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		17.1	20.9	7.7		46.5	36.2	35.0
Queue Length 50th (m)		4.0	104.6	1.4		71.8	7.5	27.8
Queue Length 95th (m)		14.2	148.9	4.6		106.2	17.7	46.7
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		482	934	938		474	189	486
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.11	0.77	0.02		0.69	0.21	0.30

Intersection Summary

Cycle Length: 120


Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 80

Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Background (2033) PM Peak w/ Improvements

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	13	9	30	698	16	4	23	271	25	39	136	6
Future Volume (vph)	13	9	30	698	16	4	23	271	25	39	136	6
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.92		1.00	0.97			0.99		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1521		1662	1516			1690		1662	1691	
Flt Permitted		0.95		0.72	1.00			0.97		0.38	1.00	
Satd. Flow (perm)		1466		1258	1516			1647		661	1691	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	13	9	31	720	16	4	24	279	26	40	140	6
RTOR Reduction (vph)	0	21	0	0	2	0	0	3	0	0	1	0
Lane Group Flow (vph)	0	32	0	720	18	0	0	326	0	40	145	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		pm+pt	NA		Perm	NA		Perm	NA	
Protected Phases		4		3	8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		37.8		74.2	74.2			34.4		34.4	34.4	
Effective Green, g (s)		37.8		74.2	74.2			34.4		34.4	34.4	
Actuated g/C Ratio		0.31		0.62	0.62			0.29		0.29	0.29	
Clearance Time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		461		893	937			472		189	484	
v/s Ratio Prot				c0.23	0.01						0.09	
v/s Ratio Perm		0.02		c0.27				c0.20		0.06		
v/c Ratio		0.07		0.81	0.02			0.69		0.21	0.30	
Uniform Delay, d1		28.8		15.6	8.8			38.1		32.5	33.4	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.3		5.4	0.0			8.1		2.5	1.6	
Delay (s)		29.1		20.9	8.9			46.1		35.0	35.0	
Level of Service		C		C	A			D		D	C	
Approach Delay (s)		29.1			20.6			46.1			35.0	
Approach LOS		C			C			D			C	
Intersection Summary												
HCM 2000 Control Delay			29.4				HCM 2000 Level of Service			C		
HCM 2000 Volume to Capacity ratio			0.78									
Actuated Cycle Length (s)			120.0				Sum of lost time (s)			13.5		
Intersection Capacity Utilization			96.1%				ICU Level of Service			F		
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Background (2033) PM Peak w/ Improvements



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	120	3	7	9	544	191	13	817
Future Volume (vph)	120	3	7	9	544	191	13	817
Lane Group Flow (vph)	136	59	0	31	618	231	0	975
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.5	86.4	43.9	43.9
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.4%	72.0%	36.6%	36.6%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.70	0.21		0.12	0.92	0.18		0.90
Control Delay	62.5	12.9		27.0	46.8	5.2		46.2
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	62.5	12.9		27.0	46.8	5.2		46.2
Queue Length 50th (m)	29.2	0.6		3.5	110.2	12.9		107.5
Queue Length 95th (m)	49.2	11.6		11.8	#199.9	26.9		#160.1
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)	318	424		400	672	1272		1089
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.43	0.14		0.08	0.92	0.18		0.90

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 109.5

Natural Cycle: 120

Control Type: Semi Act-Uncoord

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.


Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	120	3	49	7	9	11	544	191	12	13	817	28
Future Volume (vph)	120	3	49	7	9	11	544	191	12	13	817	28
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.86			0.94		1.00	0.99			1.00	
Flt Protected	0.95	1.00			0.99		0.95	1.00			1.00	
Satd. Flow (prot)	1614	1501			1630		1646	1718			3270	
Flt Permitted	0.74	1.00			0.93		0.11	1.00			0.95	
Satd. Flow (perm)	1252	1501			1538		192	1718			3103	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	136	3	56	8	10	12	618	217	14	15	928	32
RTOR Reduction (vph)	0	47	0	0	11	0	0	2	0	0	2	0
Lane Group Flow (vph)	136	12	0	0	20	0	618	229	0	0	973	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	17.1	17.1			17.1		81.0	81.0			38.4	
Effective Green, g (s)	17.1	17.1			17.1		81.0	81.0			38.4	
Actuated g/C Ratio	0.16	0.16			0.16		0.74	0.74			0.35	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	195	234			240		667	1270			1088	
v/s Ratio Prot		0.01					c0.33	0.13				
v/s Ratio Perm	c0.11				0.01		c0.35				0.31	
v/c Ratio	0.70	0.05			0.08		0.93	0.18			0.89	
Uniform Delay, d1	43.8	39.3			39.5		27.0	4.3			33.6	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	10.4	0.1			0.2		18.9	0.3			11.3	
Delay (s)	54.1	39.4			39.7		45.8	4.6			44.9	
Level of Service	D	D			D		D	A			D	
Approach Delay (s)		49.7			39.7			34.6			44.9	
Approach LOS		D			D			C			D	
Intersection Summary												
HCM 2000 Control Delay			41.0				HCM 2000 Level of Service				D	
HCM 2000 Volume to Capacity ratio			0.91									
Actuated Cycle Length (s)			109.5				Sum of lost time (s)			14.4		
Intersection Capacity Utilization			86.7%				ICU Level of Service			E		
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Background (2038) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	9	7	381	6	19	127	83	119
Future Volume (vph)	9	7	381	6	19	127	83	119
Lane Group Flow (vph)	0	50	405	27	0	214	88	136
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	65.0	65.0	65.0	65.0	55.0	55.0	55.0	55.0
Total Split (%)	54.2%	54.2%	54.2%	54.2%	45.8%	45.8%	45.8%	45.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	5.8	5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.07	0.68	0.04		0.34	0.21	0.19
Control Delay		7.7	30.4	7.7		23.7	24.5	22.8
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		7.7	30.4	7.7		23.7	24.5	22.8
Queue Length 50th (m)		2.1	74.3	0.7		32.3	13.8	20.5
Queue Length 95th (m)		8.8	114.0	5.8		52.5	26.5	34.9
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		729	595	620		635	418	708
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.07	0.68	0.04		0.34	0.21	0.19

Intersection Summary

Cycle Length: 120


Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 65

Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Background (2038) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	9	7	31	381	6	20	19	127	55	83	119	8
Future Volume (vph)	9	7	31	381	6	20	19	127	55	83	119	8
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.91		1.00	0.88			0.96		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1458		1583	1237			1557		1662	1717	
Flt Permitted		0.97		0.72	1.00			0.97		0.58	1.00	
Satd. Flow (perm)		1424		1207	1237			1516		1018	1717	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	10	7	33	405	6	21	20	135	59	88	127	9
RTOR Reduction (vph)	0	16	0	0	11	0	0	11	0	0	2	0
Lane Group Flow (vph)	0	34	0	405	16	0	0	203	0	88	134	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Effective Green, g (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Actuated g/C Ratio		0.50		0.49	0.49			0.41		0.41	0.41	
Clearance Time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		713		595	610			624		419	706	
v/s Ratio Prot					0.01						0.08	
v/s Ratio Perm		0.02		c0.34				c0.13		0.09		
v/c Ratio		0.05		0.68	0.03			0.33		0.21	0.19	
Uniform Delay, d1		15.3		23.2	15.6			24.0		22.7	22.5	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1		6.2	0.1			1.4		1.1	0.6	
Delay (s)		15.4		29.4	15.7			25.4		23.9	23.1	
Level of Service		B		C	B			C		C	C	
Approach Delay (s)		15.4			28.5			25.4			23.4	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay			25.8			HCM 2000 Level of Service				C		
HCM 2000 Volume to Capacity ratio			0.52									
Actuated Cycle Length (s)			120.0			Sum of lost time (s)			11.4			
Intersection Capacity Utilization			70.1%			ICU Level of Service				C		
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Background (2038) AM Peak Hour




Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	37	2	3	2	670	155	19	482
Future Volume (vph)	37	2	3	2	670	155	19	482
Lane Group Flow (vph)	40	17	0	15	728	170	0	570
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	51.2	86.4	35.2	35.2
Total Split (%)	28.0%	28.0%	28.0%	28.0%	42.7%	72.0%	29.3%	29.3%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.34	0.11		0.10	0.82	0.12		0.47
Control Delay	51.3	22.5		27.3	16.8	2.8		28.1
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	51.3	22.5		27.3	16.8	2.8		28.1
Queue Length 50th (m)	8.0	0.4		1.0	61.7	6.5		49.6
Queue Length 95th (m)	19.1	7.1		7.3	123.5	13.2		76.4
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	302	358		386	996	1362		1220
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.13	0.05		0.04	0.73	0.12		0.47

Intersection Summary

Cycle Length: 120
Actuated Cycle Length: 99.9
Natural Cycle: 100
Control Type: Semi Act-Uncoord


Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	37	2	14	3	2	9	670	155	2	19	482	23
Future Volume (vph)	37	2	14	3	2	9	670	155	2	19	482	23
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.87			0.91		1.00	1.00			0.99	
Flt Protected	0.95	1.00			0.99		0.95	1.00			1.00	
Satd. Flow (prot)	1374	1244			1433		1630	1649			3257	
Flt Permitted	0.75	1.00			0.94		0.34	1.00			0.94	
Satd. Flow (perm)	1081	1244			1357		580	1649			3069	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	40	2	15	3	2	10	728	168	2	21	524	25
RTOR Reduction (vph)	0	14	0	0	9	0	0	0	0	0	2	0
Lane Group Flow (vph)	40	3	0	0	6	0	728	170	0	0	568	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	8.5	8.5			8.5		81.2	81.2			39.6	
Effective Green, g (s)	8.5	8.5			8.5		81.2	81.2			39.6	
Actuated g/C Ratio	0.08	0.08			0.08		0.80	0.80			0.39	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	90	104			114		866	1324			1202	
v/s Ratio Prot		0.00					0.32	0.10				
v/s Ratio Perm	0.04				0.00		0.35				0.18	
v/c Ratio	0.44	0.03			0.05		0.84	0.13			0.47	
Uniform Delay, d1	44.1	42.5			42.6		10.4	2.2			23.0	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	3.5	0.1			0.2		7.4	0.2			1.3	
Delay (s)	47.5	42.6			42.8		17.8	2.4			24.3	
Level of Service	D	D			D		B	A			C	
Approach Delay (s)		46.1			42.8			14.9			24.3	
Approach LOS		D			D			B			C	
Intersection Summary												
HCM 2000 Control Delay			19.8				HCM 2000 Level of Service			B		
HCM 2000 Volume to Capacity ratio			0.83									
Actuated Cycle Length (s)			101.1				Sum of lost time (s)		14.4			
Intersection Capacity Utilization			79.5%				ICU Level of Service		D			
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Background (2038) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↔	↔		↔	↔	↔
Traffic Volume (vph)	15	10	731	18	26	300	45	157
Future Volume (vph)	15	10	731	18	26	300	45	157
Lane Group Flow (vph)	0	60	754	25	0	365	46	169
Turn Type	Perm	NA	pm+pt	NA	Perm	NA	Perm	NA
Protected Phases		4	3	8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	3	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	5.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	9.5	39.2	25.6	25.6	25.6	25.6
Total Split (s)	39.2	39.2	40.8	80.0	40.0	40.0	40.0	40.0
Total Split (%)	32.7%	32.7%	34.0%	66.7%	33.3%	33.3%	33.3%	33.3%
Yellow Time (s)	3.3	3.3	3.0	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	0.0	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	3.0	5.8		5.6	5.6	5.6
Lead/Lag	Lag	Lag	Lead					
Lead-Lag Optimize?	Yes	Yes	Yes					
Recall Mode	Max	Max	None	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.13	0.82	0.03		0.77	0.27	0.35
Control Delay		16.9	23.4	7.4		51.3	38.3	36.0
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		16.9	23.4	7.4		51.3	38.3	36.0
Queue Length 50th (m)		4.5	113.7	1.7		82.1	8.8	32.8
Queue Length 95th (m)		15.4	162.1	5.2		#126.5	20.2	53.2
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		470	927	938		472	172	486
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.13	0.81	0.03		0.77	0.27	0.35

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp

HCM Signalized Intersection Capacity Analysis

Background (2038) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	15	10	34	731	18	6	26	300	28	45	157	7
Future Volume (vph)	15	10	34	731	18	6	26	300	28	45	157	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.92		1.00	0.96			0.99		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1521		1662	1514			1690		1662	1691	
Flt Permitted		0.95		0.71	1.00			0.97		0.34	1.00	
Satd. Flow (perm)		1460		1235	1514			1641		600	1691	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	15	10	35	754	19	6	27	309	29	46	162	7
RTOR Reduction (vph)	0	24	0	0	2	0	0	3	0	0	1	0
Lane Group Flow (vph)	0	36	0	754	23	0	0	362	0	46	168	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		pm+pt	NA		Perm	NA		Perm	NA	
Protected Phases		4		3	8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		36.7		74.2	74.2			34.4		34.4	34.4	
Effective Green, g (s)		36.7		74.2	74.2			34.4		34.4	34.4	
Actuated g/C Ratio		0.31		0.62	0.62			0.29		0.29	0.29	
Clearance Time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		446		889	936			470		172	484	
v/s Ratio Prot				c0.25	0.01						0.10	
v/s Ratio Perm		0.02		c0.27				c0.22		0.08		
v/c Ratio		0.08		0.85	0.02			0.77		0.27	0.35	
Uniform Delay, d1		29.6		16.4	8.9			39.2		33.1	33.9	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.4		7.6	0.0			11.6		3.8	2.0	
Delay (s)		30.0		23.9	8.9			50.8		36.8	35.9	
Level of Service		C		C	A			D		D	D	
Approach Delay (s)		30.0			23.5			50.8			36.1	
Approach LOS		C			C			D			D	
Intersection Summary												
HCM 2000 Control Delay			32.7			HCM 2000 Level of Service				C		
HCM 2000 Volume to Capacity ratio			0.84									
Actuated Cycle Length (s)			120.0			Sum of lost time (s)			13.5			
Intersection Capacity Utilization			102.0%			ICU Level of Service			G			
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Background (2038) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	135	3	9	14	572	208	16	856
Future Volume (vph)	135	3	9	14	572	208	16	856
Lane Group Flow (vph)	153	62	0	43	650	251	0	1035
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.5	86.4	43.9	43.9
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.4%	72.0%	36.6%	36.6%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.73	0.21		0.16	1.00	0.20		0.97
Control Delay	63.9	12.2		27.2	64.6	5.9		57.4
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	63.9	12.2		27.2	64.6	5.9		57.4
Queue Length 50th (m)	33.4	0.6		5.1	129.3	15.4		120.8
Queue Length 95th (m)	54.7	11.6		14.7	#228.8	31.4		#182.5
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	310	419		401	652	1253		1070
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.49	0.15		0.11	1.00	0.20		0.97

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 111.2

Natural Cycle: 140

Control Type: Semi Act-Uncoord

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10




												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	135	3	52	9	14	15	572	208	13	16	856	39
Future Volume (vph)	135	3	52	9	14	15	572	208	13	16	856	39
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.86			0.95		1.00	0.99			0.99	
Flt Protected	0.95	1.00			0.99		0.95	1.00			1.00	
Satd. Flow (prot)	1614	1500			1638		1646	1718			3263	
Flt Permitted	0.73	1.00			0.94		0.10	1.00			0.95	
Satd. Flow (perm)	1239	1500			1551		167	1718			3091	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	153	3	59	10	16	17	650	236	15	18	973	44
RTOR Reduction (vph)	0	49	0	0	14	0	0	2	0	0	3	0
Lane Group Flow (vph)	153	13	0	0	29	0	650	249	0	0	1032	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	18.8	18.8			18.8		81.0	81.0			38.4	
Effective Green, g (s)	18.8	18.8			18.8		81.0	81.0			38.4	
Actuated g/C Ratio	0.17	0.17			0.17		0.73	0.73			0.35	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	209	253			262		648	1251			1067	
v/s Ratio Prot		0.01					0.36	0.15				
v/s Ratio Perm	0.12				0.02		0.37				0.33	
v/c Ratio	0.73	0.05			0.11		1.00	0.20			0.97	
Uniform Delay, d1	43.8	38.7			39.1		30.4	4.8			35.8	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	12.4	0.1			0.2		36.1	0.4			20.8	
Delay (s)	56.2	38.8			39.3		66.5	5.2			56.6	
Level of Service	E	D			D		E	A			E	
Approach Delay (s)		51.2			39.3			49.4			56.6	
Approach LOS		D			D			D			E	
Intersection Summary												
HCM 2000 Control Delay			52.8				HCM 2000 Level of Service				D	
HCM 2000 Volume to Capacity ratio			0.98									
Actuated Cycle Length (s)			111.2				Sum of lost time (s)			14.4		
Intersection Capacity Utilization			90.9%				ICU Level of Service			E		
Analysis Period (min)			15									
c Critical Lane Group												

Appendix F – Synchro Analysis Output – Total Traffic Volumes

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Total (2028) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↔	↔	↔
Traffic Volume (vph)	8	6	388	4	15	105	66	122
Future Volume (vph)	8	6	388	4	15	105	66	122
Lane Group Flow (vph)	0	42	0	421	0	178	70	137
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	64.0	64.0	64.0	64.0	46.0	46.0	46.0	46.0
Total Split (%)	58.2%	58.2%	58.2%	58.2%	41.8%	41.8%	41.8%	41.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9		5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.06		0.69		0.31	0.18	0.22
Control Delay		6.5		26.3		23.8	25.2	24.5
Queue Delay		0.0		0.0		0.0	0.0	0.0
Total Delay		6.5		26.3		23.8	25.2	24.5
Queue Length 50th (m)		1.5		67.1		25.0	10.6	20.5
Queue Length 95th (m)		6.9		107.5		43.5	21.7	35.5
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)							82.0	
Base Capacity (vph)		742		614		570	392	633
Starvation Cap Reductn		0		0		0	0	0
Spillback Cap Reductn		0		0		0	0	0
Storage Cap Reductn		0		0		0	0	0
Reduced v/c Ratio		0.06		0.69		0.31	0.18	0.22

Intersection Summary

Cycle Length: 110


Actuated Cycle Length: 110

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 65

Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Total (2028) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	8	6	25	388	4	4	15	105	47	66	122	7
Future Volume (vph)	8	6	25	388	4	4	15	105	47	66	122	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9			5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00			1.00			1.00		1.00	1.00	
Frt		0.91			1.00			0.96		1.00	0.99	
Flt Protected		0.99			0.95			1.00		0.95	1.00	
Satd. Flow (prot)		1458			1581			1557		1662	1720	
Flt Permitted		0.92			0.70			0.97		0.61	1.00	
Satd. Flow (perm)		1359			1160			1520		1070	1720	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	9	6	27	413	4	4	16	112	50	70	130	7
RTOR Reduction (vph)	0	12	0	0	0	0	0	13	0	0	2	0
Lane Group Flow (vph)	0	30	0	0	421	0	0	165	0	70	135	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		59.1			58.2			40.4		40.4	40.4	
Effective Green, g (s)		59.1			58.2			40.4		40.4	40.4	
Actuated g/C Ratio		0.54			0.53			0.37		0.37	0.37	
Clearance Time (s)		4.9			5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0			3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		730			613			558		392	631	
v/s Ratio Prot											0.08	
v/s Ratio Perm		0.02			c0.36			c0.11		0.07		
v/c Ratio		0.04			0.69			0.30		0.18	0.21	
Uniform Delay, d1		12.0			19.1			24.7		23.6	23.9	
Progression Factor		1.00			1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1			6.1			1.4		1.0	0.8	
Delay (s)		12.1			25.3			26.1		24.6	24.7	
Level of Service		B			C			C		C	C	
Approach Delay (s)		12.1			25.3			26.1			24.6	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay			24.6									
HCM 2000 Volume to Capacity ratio			0.53									
Actuated Cycle Length (s)			110.0									
Intersection Capacity Utilization			65.4%									
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Total (2028) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔	↔	↔		↔
Traffic Volume (vph)	27	11	5	12	586	127	89	428
Future Volume (vph)	27	11	5	12	586	127	89	428
Lane Group Flow (vph)	0	53	0	33	637	153	0	579
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.0	86.4	44.4	44.4
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.0%	72.0%	37.0%	37.0%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)		5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio		0.39		0.20	0.79	0.11		0.73
Control Delay		44.7		30.3	13.1	2.6		31.9
Queue Delay		0.0		0.0	0.0	0.0		0.0
Total Delay		44.7		30.3	13.1	2.6		31.9
Queue Length 50th (m)		8.4		3.5	30.5	5.4		100.8
Queue Length 95th (m)		21.0		12.8	85.5	11.4		#198.8
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)		336		413	923	1353		793
Starvation Cap Reductn		0		0	0	0		0
Spillback Cap Reductn		0		0	0	0		0
Storage Cap Reductn		0		0	0	0		0
Reduced v/c Ratio		0.16		0.08	0.69	0.11		0.73

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 99.8

Natural Cycle: 110

Control Type: Semi Act-Uncoord

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	27	11	11	5	12	14	586	127	14	89	428	16
Future Volume (vph)	27	11	11	5	12	14	586	127	14	89	428	16
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor		1.00			1.00		1.00	1.00			1.00	
Frt		0.97			0.94		1.00	0.99			1.00	
Flt Protected		0.97			0.99		0.95	1.00			0.99	
Satd. Flow (prot)		1410			1515		1630	1636			1711	
Flt Permitted		0.81			0.94		0.37	1.00			0.91	
Satd. Flow (perm)		1175			1438		633	1636			1578	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	29	12	12	5	13	15	637	138	15	97	465	17
RTOR Reduction (vph)	0	10	0	0	14	0	0	2	0	0	1	0
Lane Group Flow (vph)	0	43	0	0	19	0	637	151	0	0	578	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		8.5			8.5		81.2	81.2			50.2	
Effective Green, g (s)		8.5			8.5		81.2	81.2			50.2	
Actuated g/C Ratio		0.08			0.08		0.80	0.80			0.50	
Clearance Time (s)		5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)		3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)		98			120		784	1313			783	
v/s Ratio Prot							c0.22	0.09				
v/s Ratio Perm		c0.04			0.01		c0.43				0.37	
v/c Ratio		0.44			0.16		0.81	0.12			0.74	
Uniform Delay, d1		44.0			43.0		7.9	2.2			20.2	
Progression Factor		1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2		3.1			0.6		6.4	0.2			6.2	
Delay (s)		47.1			43.6		14.4	2.3			26.4	
Level of Service		D			D		B	A			C	
Approach Delay (s)		47.1			43.6			12.0			26.4	
Approach LOS		D			D			B			C	
Intersection Summary												
HCM 2000 Control Delay		19.8			HCM 2000 Level of Service			B				
HCM 2000 Volume to Capacity ratio		0.80										
Actuated Cycle Length (s)		101.1			Sum of lost time (s)			14.4				
Intersection Capacity Utilization		88.6%			ICU Level of Service			E				
Analysis Period (min)		15										
c Critical Lane Group												

Syer Line Industrial
3: Private Driveway/Street A & Syer Line


HCM Unsignalized Intersection Capacity Analysis

Total (2028) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	102	11	1	0	9	0	1	0	0	0	0	21
Future Volume (Veh/h)	102	11	1	0	9	0	1	0	0	0	0	21
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	111	12	1	0	10	0	1	0	0	0	0	23
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type	None			None								
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	10			13			268	244	12	244	245	10
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	10			13			268	244	12	244	245	10
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	93			100			100	100	100	100	100	98
cM capacity (veh/h)	1610			1619			639	615	1074	672	615	1071
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	124	10	1	23								
Volume Left	111	0	1	0								
Volume Right	1	0	0	23								
cSH	1610	1619	639	1071								
Volume to Capacity	0.07	0.00	0.00	0.02								
Queue Length 95th (m)	1.8	0.0	0.0	0.5								
Control Delay (s)	6.7	0.0	10.6	8.4								
Lane LOS	A		B	A								
Approach Delay (s)	6.7	0.0	10.6	8.4								
Approach LOS			B	A								
Intersection Summary												
Average Delay			6.5									
Intersection Capacity Utilization			23.5%		ICU Level of Service				A			
Analysis Period (min)			15									

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Total (2028) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔		↔	↔	↔
Traffic Volume (vph)	12	8	651	15	21	268	34	124
Future Volume (vph)	12	8	651	15	21	268	34	124
Lane Group Flow (vph)	0	49	0	688	0	330	35	134
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	101.0	101.0	101.0	101.0	39.0	39.0	39.0	39.0
Total Split (%)	72.1%	72.1%	72.1%	72.1%	27.9%	27.9%	27.9%	27.9%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9		5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.05		0.83		0.83	0.28	0.33
Control Delay		3.8		27.8		68.8	50.7	46.2
Queue Delay		0.0		0.0		0.0	0.0	0.0
Total Delay		3.8		27.8		68.8	50.7	46.2
Queue Length 50th (m)		1.7		137.4		91.1	8.4	32.0
Queue Length 95th (m)		5.9		215.5		#142.0	19.9	52.5
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)							82.0	
Base Capacity (vph)		917		824		396	125	404
Starvation Cap Reductn		0		0		0	0	0
Spillback Cap Reductn		0		0		0	0	0
Storage Cap Reductn		0		0		0	0	0
Reduced v/c Ratio		0.05		0.83		0.83	0.28	0.33

Intersection Summary

Cycle Length: 140

Actuated Cycle Length: 140

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Total (2028) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	12	8	28	651	15	2	21	268	31	34	124	6
Future Volume (vph)	12	8	28	651	15	2	21	268	31	34	124	6
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9			5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00			1.00			1.00		1.00	1.00	
Frt		0.92			1.00			0.99		1.00	0.99	
Flt Protected		0.99			0.95			1.00		0.95	1.00	
Satd. Flow (prot)		1520			1663			1688		1662	1690	
Flt Permitted		0.86			0.70			0.97		0.30	1.00	
Satd. Flow (perm)		1323			1212			1648		527	1690	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	12	8	29	671	15	2	22	276	32	35	128	6
RTOR Reduction (vph)	0	9	0	0	0	0	0	3	0	0	2	0
Lane Group Flow (vph)	0	40	0	0	688	0	0	327	0	35	132	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		96.1			95.2			33.4		33.4	33.4	
Effective Green, g (s)		96.1			95.2			33.4		33.4	33.4	
Actuated g/C Ratio		0.69			0.68			0.24		0.24	0.24	
Clearance Time (s)		4.9			5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0			3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		908			824			393		125	403	
v/s Ratio Prot											0.08	
v/s Ratio Perm		0.03			c0.57			c0.20		0.07		
v/c Ratio		0.04			0.83			0.83		0.28	0.33	
Uniform Delay, d1		7.1			16.6			50.6		43.5	44.0	
Progression Factor		1.00			1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1			9.8			18.3		5.5	2.2	
Delay (s)		7.2			26.4			68.9		49.0	46.2	
Level of Service		A			C			E		D	D	
Approach Delay (s)		7.2			26.4			68.9			46.8	
Approach LOS		A			C			E			D	
Intersection Summary												
HCM 2000 Control Delay			39.7									
HCM 2000 Volume to Capacity ratio			0.83									
Actuated Cycle Length (s)			140.0									
Intersection Capacity Utilization			92.7%									
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Total (2028) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔		↔	↔	↔		↔
Traffic Volume (vph)	107	4	18	54	505	174	31	747
Future Volume (vph)	107	4	18	54	505	174	31	747
Lane Group Flow (vph)	0	177	0	126	574	215	0	908
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	31.0	106.4	75.4	75.4
Total Split (%)	24.0%	24.0%	24.0%	24.0%	22.1%	76.0%	53.9%	53.9%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)		5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio		0.90		0.43	1.05	0.17		1.05
Control Delay		93.9		47.0	73.9	5.9		78.5
Queue Delay		0.0		0.0	0.0	0.0		0.0
Total Delay		93.9		47.0	73.9	5.9		78.5
Queue Length 50th (m)		46.5		27.5	~121.4	17.4		~294.6
Queue Length 95th (m)		#84.7		47.2	#187.0	25.7		#363.3
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)					85.0			
Base Capacity (vph)		221		331	548	1265		863
Starvation Cap Reductn		0		0	0	0		0
Spillback Cap Reductn		0		0	0	0		0
Storage Cap Reductn		0		0	0	0		0
Reduced v/c Ratio		0.80		0.38	1.05	0.17		1.05

Intersection Summary

Cycle Length: 140

Actuated Cycle Length: 136.8

Natural Cycle: 150

Control Type: Semi Act-Uncoord


~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	107	4	44	18	54	40	505	174	15	31	747	21
Future Volume (vph)	107	4	44	18	54	40	505	174	15	31	747	21
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor		1.00			1.00		1.00	1.00			1.00	
Frt		0.96			0.95		1.00	0.99			1.00	
Flt Protected		0.97			0.99		0.95	1.00			1.00	
Satd. Flow (prot)		1594			1653		1646	1713			1722	
Flt Permitted		0.63			0.94		0.22	1.00			0.98	
Satd. Flow (perm)		1035			1560		384	1713			1691	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	122	5	50	20	61	45	574	198	17	35	849	24
RTOR Reduction (vph)	0	11	0	0	15	0	0	2	0	0	0	0
Lane Group Flow (vph)	0	166	0	0	111	0	574	213	0	0	908	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		24.5			24.5		100.9	100.9			69.9	
Effective Green, g (s)		24.5			24.5		100.9	100.9			69.9	
Actuated g/C Ratio		0.18			0.18		0.74	0.74			0.51	
Clearance Time (s)		5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)		3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)		185			279		541	1263			864	
v/s Ratio Prot							c0.22	0.12				
v/s Ratio Perm		c0.16			0.07		c0.57				0.54	
v/c Ratio		0.90			0.40		1.06	0.17			1.05	
Uniform Delay, d1		54.9			49.6		27.8	5.4			33.5	
Progression Factor		1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2		38.6			0.9		55.9	0.3			44.7	
Delay (s)		93.5			50.6		83.6	5.7			78.1	
Level of Service		F			D		F	A			E	
Approach Delay (s)		93.5			50.6			62.4			78.1	
Approach LOS		F			D			E			E	
Intersection Summary												
HCM 2000 Control Delay		71.6			HCM 2000 Level of Service			E				
HCM 2000 Volume to Capacity ratio		1.05										
Actuated Cycle Length (s)		136.8			Sum of lost time (s)			14.4				
Intersection Capacity Utilization		106.7%			ICU Level of Service			G				
Analysis Period (min)		15										
c Critical Lane Group												

Syer Line Industrial
3: Private Driveway/Street A & Syer Line


HCM Unsignalized Intersection Capacity Analysis

Total (2028) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	25	24	1	0	23	0	1	0	0	0	0	87
Future Volume (Veh/h)	25	24	1	0	23	0	1	0	0	0	0	87
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	27	26	1	0	25	0	1	0	0	0	0	95
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	25			27			200	106	26	106	106	25
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	25			27			200	106	26	106	106	25
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	98			100			100	100	100	100	100	91
cM capacity (veh/h)	1589			1600			684	775	1055	863	774	1051
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	54	25	1	95								
Volume Left	27	0	1	0								
Volume Right	1	0	0	95								
cSH	1589	1600	684	1051								
Volume to Capacity	0.02	0.00	0.00	0.09								
Queue Length 95th (m)	0.4	0.0	0.0	2.4								
Control Delay (s)	3.7	0.0	10.3	8.8								
Lane LOS	A		B	A								
Approach Delay (s)	3.7	0.0	10.3	8.8								
Approach LOS			B	A								
Intersection Summary												
Average Delay			6.0									
Intersection Capacity Utilization			22.1%		ICU Level of Service				A			
Analysis Period (min)			15									

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Total (2033) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↔	↔		↔	↔	↔
Traffic Volume (vph)	9	6	412	5	17	117	74	132
Future Volume (vph)	9	6	412	5	17	117	74	132
Lane Group Flow (vph)	0	46	438	16	0	198	79	147
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	65.0	65.0	65.0	65.0	55.0	55.0	55.0	55.0
Total Split (%)	54.2%	54.2%	54.2%	54.2%	45.8%	45.8%	45.8%	45.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	5.8	5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.06	0.73	0.03		0.31	0.18	0.21
Control Delay		7.9	33.1	9.5		22.9	24.0	23.2
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		7.9	33.1	9.5		22.9	24.0	23.2
Queue Length 50th (m)		1.9	83.7	0.6		29.1	12.3	22.6
Queue Length 95th (m)		8.3	128.5	4.5		48.3	23.8	37.6
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		728	597	625		636	430	710
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.06	0.73	0.03		0.31	0.18	0.21

Intersection Summary

Cycle Length: 120


Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 65

Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Total (2033) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	9	6	28	412	5	10	17	117	53	74	132	7
Future Volume (vph)	9	6	28	412	5	10	17	117	53	74	132	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.91		1.00	0.90			0.96		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1458		1583	1256			1557		1662	1721	
Flt Permitted		0.97		0.73	1.00			0.97		0.60	1.00	
Satd. Flow (perm)		1423		1212	1256			1517		1046	1721	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	10	6	30	438	5	11	18	124	56	79	140	7
RTOR Reduction (vph)	0	15	0	0	6	0	0	12	0	0	2	0
Lane Group Flow (vph)	0	31	0	438	10	0	0	186	0	79	145	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Effective Green, g (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Actuated g/C Ratio		0.50		0.49	0.49			0.41		0.41	0.41	
Clearance Time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		712		597	619			624		430	708	
v/s Ratio Prot					0.01						0.08	
v/s Ratio Perm		0.02		c0.36				c0.12		0.08		
v/c Ratio		0.04		0.73	0.02			0.30		0.18	0.21	
Uniform Delay, d1		15.3		24.1	15.5			23.7		22.5	22.7	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1		7.8	0.0			1.2		0.9	0.7	
Delay (s)		15.4		31.9	15.6			24.9		23.4	23.3	
Level of Service		B		C	B			C		C	C	
Approach Delay (s)		15.4			31.4			24.9			23.4	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay			27.2			HCM 2000 Level of Service				C		
HCM 2000 Volume to Capacity ratio			0.53									
Actuated Cycle Length (s)			120.0			Sum of lost time (s)			11.4			
Intersection Capacity Utilization			69.2%			ICU Level of Service				C		
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Total (2033) AM Peak Hour




Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	31	11	5	12	644	142	90	459
Future Volume (vph)	31	11	5	12	644	142	90	459
Lane Group Flow (vph)	34	26	0	33	700	169	0	618
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	51.2	86.4	35.2	35.2
Total Split (%)	28.0%	28.0%	28.0%	28.0%	42.7%	72.0%	29.3%	29.3%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.30	0.16		0.20	0.81	0.12		0.54
Control Delay	50.2	28.8		30.5	16.9	2.6		29.0
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	50.2	28.8		30.5	16.9	2.6		29.0
Queue Length 50th (m)	6.7	2.3		3.5	61.5	6.1		54.8
Queue Length 95th (m)	16.8	10.8		12.8	115.5	12.2		85.8
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	298	407		416	984	1358		1145
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.11	0.06		0.08	0.71	0.12		0.54

Intersection Summary

Cycle Length: 120
Actuated Cycle Length: 99.6
Natural Cycle: 100
Control Type: Semi Act-Uncoord

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	31	11	13	5	12	14	644	142	14	90	459	19
Future Volume (vph)	31	11	13	5	12	14	644	142	14	90	459	19
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.92			0.94		1.00	0.99			0.99	
Flt Protected	0.95	1.00			0.99		0.95	1.00			0.99	
Satd. Flow (prot)	1374	1418			1515		1630	1637			3248	
Flt Permitted	0.74	1.00			0.95		0.31	1.00			0.86	
Satd. Flow (perm)	1064	1418			1444		540	1637			2813	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	34	12	14	5	13	15	700	154	15	98	499	21
RTOR Reduction (vph)	0	13	0	0	14	0	0	2	0	0	2	0
Lane Group Flow (vph)	34	13	0	0	19	0	700	167	0	0	616	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	8.3	8.3			8.3		81.2	81.2			40.5	
Effective Green, g (s)	8.3	8.3			8.3		81.2	81.2			40.5	
Actuated g/C Ratio	0.08	0.08			0.08		0.80	0.80			0.40	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	87	116			118		841	1317			1129	
v/s Ratio Prot		0.01					0.31	0.10				
v/s Ratio Perm	0.03				0.01		0.36				0.22	
v/c Ratio	0.39	0.11			0.16		0.83	0.13			0.55	
Uniform Delay, d1	43.9	42.9			43.1		11.1	2.1			23.1	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	2.9	0.4			0.7		7.1	0.2			1.9	
Delay (s)	46.8	43.3			43.7		18.1	2.3			25.0	
Level of Service	D	D			D		B	A			C	
Approach Delay (s)		45.3			43.7			15.1			25.0	
Approach LOS		D			D			B			C	
Intersection Summary												
HCM 2000 Control Delay			20.7				HCM 2000 Level of Service				C	
HCM 2000 Volume to Capacity ratio			0.81									
Actuated Cycle Length (s)			100.9				Sum of lost time (s)			14.4		
Intersection Capacity Utilization			78.5%				ICU Level of Service			D		
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
3: Private Driveway/Street A & Syer Line


HCM Unsignalized Intersection Capacity Analysis

Total (2033) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	102	12	1	0	10	0	1	0	0	0	0	21
Future Volume (Veh/h)	102	12	1	0	10	0	1	0	0	0	0	21
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	111	13	1	0	11	0	1	0	0	0	0	23
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type	None			None								
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	11			14			270	246	14	246	247	11
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	11			14			270	246	14	246	247	11
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	93			100			100	100	100	100	100	98
cM capacity (veh/h)	1608			1617			637	614	1072	670	613	1070
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	125	11	1	23								
Volume Left	111	0	1	0								
Volume Right	1	0	0	23								
cSH	1608	1617	637	1070								
Volume to Capacity	0.07	0.00	0.00	0.02								
Queue Length 95th (m)	1.8	0.0	0.0	0.5								
Control Delay (s)	6.6	0.0	10.7	8.4								
Lane LOS	A		B	A								
Approach Delay (s)	6.6	0.0	10.7	8.4								
Approach LOS			B	A								
Intersection Summary												
Average Delay			6.5									
Intersection Capacity Utilization			23.6%		ICU Level of Service				A			
Analysis Period (min)			15									

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Total (2033) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↔	↔		↔	↔	↔
Traffic Volume (vph)	13	9	711	16	23	293	39	142
Future Volume (vph)	13	9	711	16	23	293	39	142
Lane Group Flow (vph)	0	53	733	20	0	360	40	152
Turn Type	Perm	NA	pm+pt	NA	Perm	NA	Perm	NA
Protected Phases		4	3	8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	3	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	5.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	9.5	39.2	25.6	25.6	25.6	25.6
Total Split (s)	39.2	39.2	36.3	80.0	40.0	40.0	40.0	40.0
Total Split (%)	32.7%	32.7%	30.3%	66.7%	33.3%	33.3%	33.3%	33.3%
Yellow Time (s)	3.3	3.3	3.0	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	0.0	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	3.0	5.8		5.6	5.6	5.6
Lead/Lag	Lag	Lag	Lead					
Lead-Lag Optimize?	Yes	Yes	Yes					
Recall Mode	Max	Max	None	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.10	0.80	0.02		0.76	0.23	0.31
Control Delay		15.4	22.2	7.7		50.3	37.1	35.3
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		15.4	22.2	7.7		50.3	37.1	35.3
Queue Length 50th (m)		3.8	107.9	1.4		80.5	7.6	29.1
Queue Length 95th (m)		13.4	153.6	4.6		#119.3	18.0	48.3
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		511	920	938		474	173	486
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.10	0.80	0.02		0.76	0.23	0.31

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green


Natural Cycle: 90

Control Type: Actuated-Coordinated

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Total (2033) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	13	9	30	711	16	4	23	293	33	39	142	6
Future Volume (vph)	13	9	30	711	16	4	23	293	33	39	142	6
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.92		1.00	0.97			0.99		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1521		1662	1516			1688		1662	1691	
Flt Permitted		0.95		0.72	1.00			0.97		0.35	1.00	
Satd. Flow (perm)		1467		1262	1516			1648		605	1691	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	13	9	31	733	16	4	24	302	34	40	146	6
RTOR Reduction (vph)	0	21	0	0	2	0	0	3	0	0	1	0
Lane Group Flow (vph)	0	32	0	733	18	0	0	357	0	40	151	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		pm+pt	NA		Perm	NA		Perm	NA	
Protected Phases		4		3	8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		40.2		74.2	74.2			34.4		34.4	34.4	
Effective Green, g (s)		40.2		74.2	74.2			34.4		34.4	34.4	
Actuated g/C Ratio		0.34		0.62	0.62			0.29		0.29	0.29	
Clearance Time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		491		886	937			472		173	484	
v/s Ratio Prot				c0.22	0.01						0.09	
v/s Ratio Perm		0.02		c0.29				c0.22		0.07		
v/c Ratio		0.07		0.83	0.02			0.76		0.23	0.31	
Uniform Delay, d1		27.1		16.1	8.8			39.0		32.7	33.5	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.3		6.4	0.0			10.8		3.1	1.7	
Delay (s)		27.4		22.5	8.9			49.8		35.8	35.2	
Level of Service		C		C	A			D		D	D	
Approach Delay (s)		27.4			22.1			49.8			35.3	
Approach LOS		C			C			D			D	
Intersection Summary												
HCM 2000 Control Delay			31.5									
HCM 2000 Volume to Capacity ratio			0.82									
Actuated Cycle Length (s)			120.0									
Intersection Capacity Utilization			98.7%									
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Total (2033) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	120	5	18	55	544	191	32	817
Future Volume (vph)	120	5	18	55	544	191	32	817
Lane Group Flow (vph)	136	62	0	130	618	235	0	996
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.5	86.4	43.9	43.9
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.4%	72.0%	36.6%	36.6%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.80	0.20		0.45	0.95	0.19		0.95
Control Delay	75.0	13.2		38.6	54.5	5.9		54.3
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	75.0	13.2		38.6	54.5	5.9		54.3
Queue Length 50th (m)	30.2	1.2		22.2	119.4	14.5		116.1
Queue Length 95th (m)	51.6	12.2		39.9	#211.4	29.1		#173.5
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	249	419		410	650	1247		1052
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.55	0.15		0.32	0.95	0.19		0.95

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 111.6

Natural Cycle: 130

Control Type: Semi Act-Uncoord

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	120	5	49	18	55	41	544	191	16	32	817	28
Future Volume (vph)	120	5	49	18	55	41	544	191	16	32	817	28
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.86			0.95		1.00	0.99			1.00	
Flt Protected	0.95	1.00			0.99		0.95	1.00			1.00	
Satd. Flow (prot)	1614	1513			1652		1646	1714			3267	
Flt Permitted	0.59	1.00			0.95		0.10	1.00			0.93	
Satd. Flow (perm)	999	1513			1578		168	1714			3053	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	136	6	56	20	62	47	618	217	18	36	928	32
RTOR Reduction (vph)	0	46	0	0	18	0	0	2	0	0	2	0
Lane Group Flow (vph)	136	16	0	0	112	0	618	233	0	0	994	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	19.2	19.2			19.2		81.0	81.0			38.4	
Effective Green, g (s)	19.2	19.2			19.2		81.0	81.0			38.4	
Actuated g/C Ratio	0.17	0.17			0.17		0.73	0.73			0.34	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	171	260			271		646	1244			1050	
v/s Ratio Prot		0.01					0.34	0.14				
v/s Ratio Perm	0.14				0.07		0.36				0.33	
v/c Ratio	0.80	0.06			0.41		0.96	0.19			0.95	
Uniform Delay, d1	44.3	38.7			41.2		29.4	4.9			35.6	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	22.0	0.1			1.0		24.9	0.3			17.6	
Delay (s)	66.3	38.7			42.2		54.3	5.2			53.2	
Level of Service	E	D			D		D	A			D	
Approach Delay (s)		57.7			42.2			40.7			53.2	
Approach LOS		E			D			D			D	
Intersection Summary												
HCM 2000 Control Delay			48.1				HCM 2000 Level of Service				D	
HCM 2000 Volume to Capacity ratio			0.95									
Actuated Cycle Length (s)			111.6				Sum of lost time (s)			14.4		
Intersection Capacity Utilization			87.3%				ICU Level of Service			E		
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
3: Private Driveway/Street A & Syer Line


HCM Unsignalized Intersection Capacity Analysis

Total (2033) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	25	27	1	0	26	0	1	0	0	0	0	87
Future Volume (Veh/h)	25	27	1	0	26	0	1	0	0	0	0	87
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	27	29	1	0	28	0	1	0	0	0	0	95
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	28			30			206	112	30	112	112	28
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	28			30			206	112	30	112	112	28
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	98			100			100	100	100	100	100	91
cM capacity (veh/h)	1585			1596			678	769	1051	855	769	1047
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	57	28	1	95								
Volume Left	27	0	1	0								
Volume Right	1	0	0	95								
cSH	1585	1596	678	1047								
Volume to Capacity	0.02	0.00	0.00	0.09								
Queue Length 95th (m)	0.4	0.0	0.0	2.4								
Control Delay (s)	3.5	0.0	10.3	8.8								
Lane LOS	A		B	A								
Approach Delay (s)	3.5	0.0	10.3	8.8								
Approach LOS			B	A								
Intersection Summary												
Average Delay			5.8									
Intersection Capacity Utilization			22.3%		ICU Level of Service				A			
Analysis Period (min)			15									

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Total (2038) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↔	↔		↔	↔	↔
Traffic Volume (vph)	9	7	434	6	19	132	83	145
Future Volume (vph)	9	7	434	6	19	132	83	145
Lane Group Flow (vph)	0	50	462	27	0	221	88	163
Turn Type	Perm	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		4		8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	39.2	39.2	25.6	25.6	25.6	25.6
Total Split (s)	65.0	65.0	65.0	65.0	55.0	55.0	55.0	55.0
Total Split (%)	54.2%	54.2%	54.2%	54.2%	45.8%	45.8%	45.8%	45.8%
Yellow Time (s)	3.3	3.3	4.2	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	5.8	5.8		5.6	5.6	5.6
Lead/Lag								
Lead-Lag Optimize?								
Recall Mode	Max	Max	Max	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.07	0.78	0.04		0.35	0.21	0.23
Control Delay		7.7	35.8	7.7		23.9	24.6	23.6
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		7.7	35.8	7.7		23.9	24.6	23.6
Queue Length 50th (m)		2.1	91.2	0.7		33.7	13.8	25.4
Queue Length 95th (m)		8.8	140.6	5.8		54.5	26.5	41.5
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		729	595	620		634	413	709
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.07	0.78	0.04		0.35	0.21	0.23

Intersection Summary

Cycle Length: 120


Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 65

Control Type: Actuated-Coordinated

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

HCM Signalized Intersection Capacity Analysis


1: County Road 10 & Syer Line/Highway 115 SB Ramp

Total (2038) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	9	7	31	434	6	20	19	132	57	83	145	8
Future Volume (vph)	9	7	31	434	6	20	19	132	57	83	145	8
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.91		1.00	0.88			0.96		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1458		1583	1237			1557		1662	1719	
Flt Permitted		0.97		0.72	1.00			0.97		0.57	1.00	
Satd. Flow (perm)		1424		1207	1237			1514		1005	1719	
Peak-hour factor, PHF	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94	0.94
Adj. Flow (vph)	10	7	33	462	6	21	20	140	61	88	154	9
RTOR Reduction (vph)	0	16	0	0	11	0	0	11	0	0	2	0
Lane Group Flow (vph)	0	34	0	462	16	0	0	210	0	88	161	0
Heavy Vehicles (%)	14%	20%	4%	5%	25%	25%	8%	11%	0%	0%	1%	0%
Turn Type	Perm	NA		Perm	NA		Perm	NA		Perm	NA	
Protected Phases		4			8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Effective Green, g (s)		60.1		59.2	59.2			49.4		49.4	49.4	
Actuated g/C Ratio		0.50		0.49	0.49			0.41		0.41	0.41	
Clearance Time (s)		4.9		5.8	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		713		595	610			623		413	707	
v/s Ratio Prot					0.01						0.09	
v/s Ratio Perm		0.02		c0.38				c0.14		0.09		
v/c Ratio		0.05		0.78	0.03			0.34		0.21	0.23	
Uniform Delay, d1		15.3		25.0	15.6			24.1		22.8	22.9	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.1		9.6	0.1			1.5		1.2	0.8	
Delay (s)		15.4		34.6	15.7			25.6		23.9	23.7	
Level of Service		B		C	B			C		C	C	
Approach Delay (s)		15.4			33.5			25.6			23.8	
Approach LOS		B			C			C			C	
Intersection Summary												
HCM 2000 Control Delay			28.5									
HCM 2000 Volume to Capacity ratio			0.58									
Actuated Cycle Length (s)			120.0									
Intersection Capacity Utilization			73.9%									
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Total (2038) AM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	37	12	6	13	670	155	98	482
Future Volume (vph)	37	12	6	13	670	155	98	482
Lane Group Flow (vph)	40	28	0	38	728	184	0	656
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	51.2	86.4	35.2	35.2
Total Split (%)	28.0%	28.0%	28.0%	28.0%	42.7%	72.0%	29.3%	29.3%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.35	0.17		0.23	0.82	0.14		0.68
Control Delay	51.6	28.3		30.9	20.4	2.8		35.7
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	51.6	28.3		30.9	20.4	2.8		35.7
Queue Length 50th (m)	8.0	2.5		4.1	77.3	6.7		66.5
Queue Length 95th (m)	19.1	11.2		14.1	147.2	13.9		#100.2
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	296	408		405	948	1354		960
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.14	0.07		0.09	0.77	0.14		0.68

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 99.9


Natural Cycle: 110

Control Type: Semi Act-Uncoord

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	37	12	14	6	13	16	670	155	15	98	482	23
Future Volume (vph)	37	12	14	6	13	16	670	155	15	98	482	23
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.92			0.94		1.00	0.99			0.99	
Flt Protected	0.95	1.00			0.99		0.95	1.00			0.99	
Satd. Flow (prot)	1374	1419			1492		1630	1637			3245	
Flt Permitted	0.73	1.00			0.93		0.26	1.00			0.85	
Satd. Flow (perm)	1059	1419			1405		446	1637			2786	
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	40	13	15	7	14	17	728	168	16	107	524	25
RTOR Reduction (vph)	0	14	0	0	16	0	0	2	0	0	2	0
Lane Group Flow (vph)	40	14	0	0	22	0	728	182	0	0	654	0
Heavy Vehicles (%)	21%	0%	25%	50%	0%	0%	2%	6%	0%	0%	1%	7%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	8.6	8.6			8.6		81.2	81.2			34.4	
Effective Green, g (s)	8.6	8.6			8.6		81.2	81.2			34.4	
Actuated g/C Ratio	0.08	0.08			0.08		0.80	0.80			0.34	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	89	120			119		870	1313			947	
v/s Ratio Prot		0.01					c0.36	0.11				
v/s Ratio Perm	c0.04				0.02		c0.31				0.23	
v/c Ratio	0.45	0.12			0.19		0.84	0.14			0.69	
Uniform Delay, d1	44.0	42.8			43.1		13.8	2.2			28.8	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	3.6	0.4			0.8		7.0	0.2			4.1	
Delay (s)	47.6	43.2			43.8		20.8	2.4			32.9	
Level of Service	D	D			D		C	A			C	
Approach Delay (s)		45.8			43.8			17.1			32.9	
Approach LOS		D			D			B			C	
Intersection Summary												
HCM 2000 Control Delay			25.1				HCM 2000 Level of Service			C		
HCM 2000 Volume to Capacity ratio			0.82									
Actuated Cycle Length (s)			101.2				Sum of lost time (s)		14.4			
Intersection Capacity Utilization			81.7%				ICU Level of Service		D			
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
3: Private Driveway/Street A & Syer Line


HCM Unsignalized Intersection Capacity Analysis

Total (2038) AM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	102	13	1	0	11	0	1	0	0	0	0	21
Future Volume (Veh/h)	102	13	1	0	11	0	1	0	0	0	0	21
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	111	14	1	0	12	0	1	0	0	0	0	23
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type	None			None								
Median storage veh												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	12			15			272	248	14	248	249	12
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	12			15			272	248	14	248	249	12
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	93			100			100	100	100	100	100	98
cM capacity (veh/h)	1607			1616			635	612	1071	668	612	1069
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	126	12	1	23								
Volume Left	111	0	1	0								
Volume Right	1	0	0	23								
cSH	1607	1616	635	1069								
Volume to Capacity	0.07	0.00	0.00	0.02								
Queue Length 95th (m)	1.8	0.0	0.0	0.5								
Control Delay (s)	6.6	0.0	10.7	8.4								
Lane LOS	A		B	A								
Approach Delay (s)	6.6	0.0	10.7	8.4								
Approach LOS			B	A								
Intersection Summary												
Average Delay			6.4									
Intersection Capacity Utilization			23.6%		ICU Level of Service				A			
Analysis Period (min)			15									

Syer Line Industrial
1: County Road 10 & Syer Line/Highway 115 SB Ramp

Queues
Total (2038) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		↔	↔	↔		↔	↔	↔
Traffic Volume (vph)	15	10	744	18	26	322	45	163
Future Volume (vph)	15	10	744	18	26	322	45	163
Lane Group Flow (vph)	0	60	767	25	0	396	46	175
Turn Type	Perm	NA	pm+pt	NA	Perm	NA	Perm	NA
Protected Phases		4	3	8		2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	3	8	2	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	5.0	10.0	20.0	20.0	20.0	20.0
Minimum Split (s)	39.2	39.2	9.5	39.2	25.6	25.6	25.6	25.6
Total Split (s)	39.2	39.2	40.8	80.0	40.0	40.0	40.0	40.0
Total Split (%)	32.7%	32.7%	34.0%	66.7%	33.3%	33.3%	33.3%	33.3%
Yellow Time (s)	3.3	3.3	3.0	4.2	4.6	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	0.0	1.6	1.0	1.0	1.0	1.0
Lost Time Adjust (s)		0.0	0.0	0.0		0.0	0.0	0.0
Total Lost Time (s)		4.9	3.0	5.8		5.6	5.6	5.6
Lead/Lag	Lag	Lag	Lead					
Lead-Lag Optimize?	Yes	Yes	Yes					
Recall Mode	Max	Max	None	Max	C-Max	C-Max	C-Max	C-Max
v/c Ratio		0.13	0.83	0.03		0.84	0.29	0.36
Control Delay		16.9	24.3	7.4		56.7	39.7	36.3
Queue Delay		0.0	0.0	0.0		0.0	0.0	0.0
Total Delay		16.9	24.3	7.4		56.7	39.7	36.3
Queue Length 50th (m)		4.5	117.2	1.7		91.3	8.9	34.1
Queue Length 95th (m)		15.4	167.7	5.2		#144.8	20.6	55.1
Internal Link Dist (m)		592.7		625.0		491.5		559.6
Turn Bay Length (m)			100.0				82.0	
Base Capacity (vph)		464	926	938		473	157	486
Starvation Cap Reductn		0	0	0		0	0	0
Spillback Cap Reductn		0	0	0		0	0	0
Storage Cap Reductn		0	0	0		0	0	0
Reduced v/c Ratio		0.13	0.83	0.03		0.84	0.29	0.36

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 120

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 1: County Road 10 & Syer Line/Highway 115 SB Ramp



Syer Line Industrial

1: County Road 10 & Syer Line/Highway 115 SB Ramp


HCM Signalized Intersection Capacity Analysis

Total (2038) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	15	10	34	744	18	6	26	322	36	45	163	7
Future Volume (vph)	15	10	34	744	18	6	26	322	36	45	163	7
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Lane Util. Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Frt		0.92		1.00	0.96			0.99		1.00	0.99	
Flt Protected		0.99		0.95	1.00			1.00		0.95	1.00	
Satd. Flow (prot)		1521		1662	1514			1688		1662	1691	
Flt Permitted		0.95		0.71	1.00			0.97		0.31	1.00	
Satd. Flow (perm)		1459		1234	1514			1642		547	1691	
Peak-hour factor, PHF	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97	0.97
Adj. Flow (vph)	15	10	35	767	19	6	27	332	37	46	168	7
RTOR Reduction (vph)	0	24	0	0	2	0	0	3	0	0	1	0
Lane Group Flow (vph)	0	36	0	767	23	0	0	393	0	46	174	0
Heavy Vehicles (%)	0%	14%	4%	0%	15%	0%	5%	2%	0%	0%	3%	0%
Turn Type	Perm	NA		pm+pt	NA		Perm	NA		Perm	NA	
Protected Phases		4		3	8			2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)		36.2		74.2	74.2			34.4		34.4	34.4	
Effective Green, g (s)		36.2		74.2	74.2			34.4		34.4	34.4	
Actuated g/C Ratio		0.30		0.62	0.62			0.29		0.29	0.29	
Clearance Time (s)		4.9		3.0	5.8			5.6		5.6	5.6	
Vehicle Extension (s)		3.0		3.0	3.0			3.0		3.0	3.0	
Lane Grp Cap (vph)		440		891	936			470		156	484	
v/s Ratio Prot				c0.26	0.01						0.10	
v/s Ratio Perm		0.02		c0.27				c0.24		0.08		
v/c Ratio		0.08		0.86	0.02			0.84		0.29	0.36	
Uniform Delay, d1		30.0		16.7	8.9			40.2		33.3	34.0	
Progression Factor		1.00		1.00	1.00			1.00		1.00	1.00	
Incremental Delay, d2		0.4		8.5	0.0			16.1		4.8	2.1	
Delay (s)		30.4		25.2	8.9			56.2		38.1	36.1	
Level of Service		C		C	A			E		D	D	
Approach Delay (s)		30.4			24.7			56.2			36.5	
Approach LOS		C			C			E			D	
Intersection Summary												
HCM 2000 Control Delay			35.2									
HCM 2000 Volume to Capacity ratio			0.87									
Actuated Cycle Length (s)			120.0									
Intersection Capacity Utilization			104.6%									
Analysis Period (min)			15									
c Critical Lane Group												

Syer Line Industrial
2: Highway 115 NB Ramp/Syer Line & County Road 10

Queues
Total (2038) PM Peak Hour



Lane Group	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations								
Traffic Volume (vph)	135	5	20	60	572	208	35	856
Future Volume (vph)	135	5	20	60	572	208	35	856
Lane Group Flow (vph)	153	65	0	142	650	255	0	1057
Turn Type	Perm	NA	Perm	NA	pm+pt	NA	Perm	NA
Protected Phases		4		8	5	2		6
Permitted Phases	4		8		2		6	
Detector Phase	4	4	8	8	5	2	6	6
Switch Phase								
Minimum Initial (s)	10.0	10.0	10.0	10.0	5.0	20.0	20.0	20.0
Minimum Split (s)	33.6	33.6	33.6	33.6	9.5	25.6	25.6	25.6
Total Split (s)	33.6	33.6	33.6	33.6	42.5	86.4	43.9	43.9
Total Split (%)	28.0%	28.0%	28.0%	28.0%	35.4%	72.0%	36.6%	36.6%
Yellow Time (s)	4.2	4.2	4.2	4.2	3.0	4.6	4.6	4.6
All-Red Time (s)	1.6	1.6	1.6	1.6	0.0	1.0	1.0	1.0
Lost Time Adjust (s)	0.0	0.0		0.0	0.0	0.0		0.0
Total Lost Time (s)	5.8	5.8		5.8	3.0	5.6		5.6
Lead/Lag					Lead		Lag	Lag
Lead-Lag Optimize?					Yes		Yes	Yes
Recall Mode	None	None	None	None	None	Max	Max	Max
v/c Ratio	0.85	0.20		0.46	1.02	0.21		1.03
Control Delay	80.6	12.6		38.8	71.4	6.6		73.5
Queue Delay	0.0	0.0		0.0	0.0	0.0		0.0
Total Delay	80.6	12.6		38.8	71.4	6.6		73.5
Queue Length 50th (m)	34.8	1.2		25.0	~148.1	17.9		~141.7
Queue Length 95th (m)	#61.6	12.4		43.5	#228.8	31.8		#191.2
Internal Link Dist (m)		658.6		1175.6		599.4		491.5
Turn Bay Length (m)	100.0				85.0			
Base Capacity (vph)	238	415		402	638	1224		1028
Starvation Cap Reductn	0	0		0	0	0		0
Spillback Cap Reductn	0	0		0	0	0		0
Storage Cap Reductn	0	0		0	0	0		0
Reduced v/c Ratio	0.64	0.16		0.35	1.02	0.21		1.03

Intersection Summary

Cycle Length: 120

Actuated Cycle Length: 113.7

Natural Cycle: 150

Control Type: Semi Act-Uncoord

~ Volume exceeds capacity, queue is theoretically infinite.

Queue shown is maximum after two cycles.

95th percentile volume exceeds capacity, queue may be longer.

Queue shown is maximum after two cycles.

Splits and Phases: 2: Highway 115 NB Ramp/Syer Line & County Road 10



												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (vph)	135	5	52	20	60	45	572	208	17	35	856	39
Future Volume (vph)	135	5	52	20	60	45	572	208	17	35	856	39
Ideal Flow (vphpl)	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750	1750
Total Lost time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Lane Util. Factor	1.00	1.00			1.00		1.00	1.00			0.95	
Frt	1.00	0.86			0.95		1.00	0.99			0.99	
Flt Protected	0.95	1.00			0.99		0.95	1.00			1.00	
Satd. Flow (prot)	1614	1512			1652		1646	1715			3261	
Flt Permitted	0.57	1.00			0.94		0.10	1.00			0.93	
Satd. Flow (perm)	971	1512			1573		167	1715			3036	
Peak-hour factor, PHF	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Adj. Flow (vph)	153	6	59	23	68	51	650	236	19	40	973	44
RTOR Reduction (vph)	0	48	0	0	18	0	0	2	0	0	3	0
Lane Group Flow (vph)	153	17	0	0	124	0	650	253	0	0	1054	0
Heavy Vehicles (%)	3%	0%	0%	0%	0%	0%	1%	1%	0%	0%	1%	5%
Turn Type	Perm	NA		Perm	NA		pm+pt	NA		Perm	NA	
Protected Phases		4			8		5	2			6	
Permitted Phases	4			8			2			6		
Actuated Green, G (s)	21.2	21.2			21.2		81.0	81.0			38.4	
Effective Green, g (s)	21.2	21.2			21.2		81.0	81.0			38.4	
Actuated g/C Ratio	0.19	0.19			0.19		0.71	0.71			0.34	
Clearance Time (s)	5.8	5.8			5.8		3.0	5.6			5.6	
Vehicle Extension (s)	3.0	3.0			3.0		3.0	3.0			3.0	
Lane Grp Cap (vph)	181	282			293		634	1222			1026	
v/s Ratio Prot		0.01					c0.36	0.15				
v/s Ratio Perm	c0.16				0.08		c0.37				0.35	
v/c Ratio	0.85	0.06			0.42		1.03	0.21			1.03	
Uniform Delay, d1	44.6	38.0			40.8		31.4	5.5			37.6	
Progression Factor	1.00	1.00			1.00		1.00	1.00			1.00	
Incremental Delay, d2	28.6	0.1			1.0		42.3	0.4			35.4	
Delay (s)	73.3	38.1			41.8		73.7	5.9			73.0	
Level of Service	E	D			D		E	A			E	
Approach Delay (s)		62.8			41.8			54.6			73.0	
Approach LOS		E			D			D			E	
Intersection Summary												
HCM 2000 Control Delay			63.0				HCM 2000 Level of Service			E		
HCM 2000 Volume to Capacity ratio			1.01									
Actuated Cycle Length (s)			113.6				Sum of lost time (s)		14.4			
Intersection Capacity Utilization			91.5%				ICU Level of Service		F			
Analysis Period (min)			15									
c Critical Lane Group												


Syer Line Industrial
3: Private Driveway/Street A & Syer Line

HCM Unsignalized Intersection Capacity Analysis

Total (2038) PM Peak Hour

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	25	30	1	0	28	0	1	0	0	0	0	87
Future Volume (Veh/h)	25	30	1	0	28	0	1	0	0	0	0	87
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Hourly flow rate (vph)	27	33	1	0	30	0	1	0	0	0	0	95
Pedestrians												
Lane Width (m)												
Walking Speed (m/s)												
Percent Blockage												
Right turn flare (veh)												
Median type		None			None							
Median storage (veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	30			34			212	118	34	118	118	30
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	30			34			212	118	34	118	118	30
tC, single (s)	4.1			4.1			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	98			100			100	100	100	100	100	91
cM capacity (veh/h)	1583			1591			672	763	1046	847	763	1044
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	61	30	1	95								
Volume Left	27	0	1	0								
Volume Right	1	0	0	95								
cSH	1583	1591	672	1044								
Volume to Capacity	0.02	0.00	0.00	0.09								
Queue Length 95th (m)	0.4	0.0	0.0	2.4								
Control Delay (s)	3.3	0.0	10.4	8.8								
Lane LOS	A		B	A								
Approach Delay (s)	3.3	0.0	10.4	8.8								
Approach LOS			B	A								
Intersection Summary												
Average Delay			5.6									
Intersection Capacity Utilization			22.5%		ICU Level of Service				A			
Analysis Period (min)			15									

Appendix G – MTO Left Turn Analysis

Exhibit 9A-22

--- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW

..... TRAFFIC SIGNALS MAY BE WARRANTED IN
"FREE FLOW" URBAN AREAS

Highway 115 SB Ramp & Syer Line / County Road 10

2023 Existing - Northbound

Critical Case - PM Peak Hour





Exhibit 9A-22

--- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW

..... TRAFFIC SIGNALS MAY BE WARRANTED IN
"FREE FLOW" URBAN AREAS

Highway 115 SB Ramp & Syer Line / County Road 10

2028 Background - Northbound

Critical Case - PM Peak Hour





Exhibit 9A-22

--- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL AREAS OR URBAN AREAS WITH RESTRICTED FLOW

..... TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS

Highway 115 SB Ramp & Syer Line / County Road 10

2033 Background - Northbound

Critical Case - PM Peak Hour





Exhibit 9A-22

--- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW

..... TRAFFIC SIGNALS MAY BE WARRANTED IN
"FREE FLOW" URBAN AREAS

Highway 115 SB Ramp & Syer Line / County Road 10

2028 Total - Northbound

Critical Case - PM Peak Hour





Exhibit 9A-22


--- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW



..... TRAFFIC SIGNALS MAY BE WARRANTED IN
"FREE FLOW" URBAN AREAS

Highway 115 SB Ramp & Syer Line / County Road 10

2038 Total - Northbound


Critical Case - PM Peak Hour




Highway 115 NB Ramp & Syer Line / County Road 102023 Existing - Southbound **Exhibit 9A-22****Critical Case - PM Peak Hour**


Highway 115 NB Ramp & Syer Line / County Road 102028 Background - Southbound **Exhibit 9A-22**

Critical Case - PM Peak Hour



- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL AREAS OR URBAN AREAS WITH RESTRICTED FLOW
- TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS



Highway 115 NB Ramp & Syer Line / County Road 10**2038 Total - Southbound Exhibit 9A-22****Critical Case - PM Peak Hour**

- TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL AREAS OR URBAN AREAS WITH RESTRICTED FLOW
- TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS






Exhibit 9A-9**Syer Line / Street A****2038 Total - Eastbound****Critical Case - AM Peak Hour**

Appendix H – OTM Signal Justification Sheets

Justification No. 7 - 2028 Background Traffic

Highway 115 SB Ramp & Syer Line / County Road 10

Justification	Description		Compliance			Signal Warrant	Underground Provisions Warrant
			Sectional		Entire %		
			Free Flow	Numerical			
1. Minimum Vehicular Volume	A. Vehicle volume, all approaches (average hour)	480	465	97%	81%	NO	NO
	B. Vehicle volume, along minor streets (average hour)	120	271	226%		YES	YES
2. Delay to cross traffic	A. Vehicle volume, major street (average hour)	480	174	36%	30%	NO	NO
	B. Combined vehicle and pedestrian volume crossing artery from minor streets (average hour)	50	253	506%		YES	YES

Justification No. 7 - 2038 Total Traffic

Highway 115 SB Ramp & Syer Line / County Road 10

Justification	Description		Compliance			Signal Warrant	Underground Provisions Warrant
			Sectional		Entire %		
			Rest. Flow	Numerical			
1. Minimum Vehicular Volume	A. Vehicle volume, all approaches (average hour)	480	593	124%	103%	YES	YES
	B. Vehicle volume, along minor streets (average hour)	120	333	278%		YES	YES
2. Delay to cross traffic	A. Vehicle volume, major street (average hour)	480	233	49%	41%	NO	NO
	B. Combined vehicle and pedestrian volume crossing artery from minor streets (average hour)	50	306	613%		YES	YES

Justification No. 7 - 2023 Existing Traffic

Highway 115 NB Ramp & Syer Line / County Road 10

Justification	Description		Compliance			Signal Warrant	Underground Provisions Warrant
			Sectional		Entire %		
			Free Flow	Numerical			
1. Minimum Vehicular Volume	A. Vehicle volume, all approaches (average hour)	480	476	99%	34%	NO	NO
	B. Vehicle volume, along minor streets (average hour)	120	48	40%		NO	NO
2. Delay to cross traffic	A. Vehicle volume, major street (average hour)	480	416	87%	57%	NO	NO
	B. Combined vehicle and pedestrian volume crossing artery from minor streets (average hour)	50	34	68%		NO	NO

Justification No. 7 - 2038 Background Traffic

Highway 115 NB Ramp & Syer Line / County Road 10

Justification	Description		Compliance			Signal Warrant	Underground Provisions Warrant
			Sectional		Entire %		
			Rest. Flow	Numerical			
1. Minimum Vehicular Volume	A. Vehicle volume, all approaches (average hour)	480	896	187%	72%	YES	YES
	B. Vehicle volume, along minor streets (average hour)	120	104	86%		NO	NO
2. Delay to cross traffic	A. Vehicle volume, major street (average hour)	480	769	160%	113%	YES	YES
	B. Combined vehicle and pedestrian volume crossing artery from minor streets (average hour)	50	68	135%		YES	YES

Justification No. 7 - 2038 Background Traffic

Syer Line / Street A

Justification	Description		Compliance			Signal Warrant	Underground Provisions Warrant
			Sectional		Entire %		
			Rest. Flow	Numerical			
1. Minimum Vehicular Volume	A. Vehicle volume, all approaches (average hour)	720	80	11%	7%	NO	NO
	B. Vehicle volume, along minor streets (average hour)	255	28	11%		NO	NO
2. Delay to cross traffic	A. Vehicle volume, major street (average hour)	720	52	7%	0%	NO	NO
	B. Combined vehicle and pedestrian volume crossing artery from minor streets (average hour)	75	1	1%		NO	NO

Appendix I – Transportation Tomorrow Survey – Excerpt

Residential Distribution

Fri Feb 11 2022 15:42:07 GMT-0500 (Eastern Standard Time) - Run Time: 2702ms

Cross Tabulation Query Form - Trip - 2016 v1.1

Row: Planning district of origin - pd_orig

Column: Planning district of destination - pd_dest

Filters:

(Planning district of destination - pd_dest In 104); and

(Start time of trip - start_time In 700 - 900); and

(Trip purpose of destination - purp_dest In W, R)

Trip 2016

ROW : pd_orig

COLUMN : pd_dest

Cross Tabulation Query Form - Trip - 2016 v1.1

Filter Variables

Planning district of origin X ▾

Planning district of desti... X ▾

(Optional) Table Attribute ▾

Group Attributes

Row Grouping

Column Grouping

Table Grouping

Grouping file: Choose File No file chosen

Filter Selection +

☐ Planning district of destination ▾ In ▾

104

And ▾

☐ Start time of trip ▾ In ▾

700 - 900

And ▾

☐ Trip purpose of destination ▾ In ▾

W, R

Add

Delete

Output

☒ Comma-delimited table☐ Column format

Expansion Factor On

Click to Select Load

Load

Execute Query

Select All

Save As

Mon Mar 21 2022 17:47:25 GMT-0400 (Eastern Daylight Time) - Run Time: 2644ms

Cross Tabulation Query Form - Trip - 2016 v1.1

Row: Planning district of origin - pd_orig

Column: Planning district of destination - pd_dest

Filters:

Planning district of destination - pd_dest In 104

and

Start time of trip - start_time In 700 - 900

and

Trip purpose of destination - purp_dest In W, R

Trip 2016

Table:

,Cavan Monaghan

Ajax,11

Oshawa,26

Clarington,63

Kawartha Lakes,260

Peterborough,669

Cavan Monaghan,204

Otonabee-South Monaghan,128

Asphodel-Norwood,5

Dummer-Douro,40

Selwyn,95

Employment Distribution

Tue Feb 15 2022 16:33:06 GMT-0500 (Eastern Standard Time) - Run Time: 2537ms

Cross Tabulation Query Form - Trip - 2016 v1.1

Row: Planning district of destination - pd_dest

Column: Planning district of origin - pd_orig

Filters:

(Planning district of origin - pd_orig In 104,); and

(Start time of trip - start_time In 700 - 900); and

(Trip purpose of destination - purp_dest In W, R)

Trip 2016

ROW : pd_dest

COLUMN : pd_orig

Cross Tabulation Query Form - Trip - 2016 v1.1

Filter Variables

Planning district of desti... X

Planning district of origin X

(Optional) Table Attribute

Group Attributes

Row Grouping

Column Grouping

Table Grouping

Grouping file: Choose File No file chosen

Filter Selection +

☐ Planning district of origin In

104

And

☐ Start time of trip In

700 - 900

And

☐ Trip purpose of destination In

W, R

Add Delete

Output

☒ Comma-delimited table ☐ Column format

Expansion Factor On

Click to Select Load

Load

Execute Query

Select All

Save As

Mon Mar 21 2022 17:50:10 GMT-0400 (Eastern Daylight Time) - Run Time: 2479ms

Cross Tabulation Query Form - Trip - 2016 v1.1

Row: Planning district of destination - pd_dest

Column: Planning district of origin - pd_orig

Filters:

Planning district of origin - pd_orig In 104

and

Start time of trip - start_time In 700 - 900

and

Trip purpose of destination - purp_dest In W, R

Trip 2016

Table:

,Cavan Monaghan

PD 1 of Toronto,35

PD 16 of Toronto,37

Ajax,26

Whitby,27

Oshawa,36

Clarington,152

Whitchurch-Stouffville,39

Mississauga,39

Kawartha Lakes,41

Peterborough,1122

Cavan Monaghan,204

Otonabee-South Monaghan,20

Asphodel-Norwood,11

Selwyn,39

Hastings,45

External,5